



## Edgetek™ ATC-15GB / 000 NATURAL UV

Acetal (POM) Copolymer

### Key Characteristics

#### Product Description

The Engineered Materials group of PolyOne offers a POM range of unfilled, filled and impact grades compounds, available under the brand name of Edgetek, using POM homopolymer or copolymer as base resin. Available in a wide range of physical properties, these materials are specified where certain key performance issues are critical. In addition to the standard range, products can be custom-formulated to meet your specific requirements or colours, offering you both product and design flexibility.

#### General

Material Status	• Commercial: Active
Regional Availability	• Asia Pacific • Europe
Filler / Reinforcement	• Glass Bead, 15% Filler by Weight
Features	• UV Stabilized
Uses	• Automotive Applications • Electrical/Electronic Applications • Consumer Applications • Industrial Applications
Appearance	• Natural Color
Processing Method	• Injection Molding

### Technical Properties <sup>1</sup>

Physical	Typical Value (English)	Typical Value (SI)	Test Method
Density <sup>2</sup>	1.48 g/cm <sup>3</sup>	1.48 g/cm <sup>3</sup>	ISO 1183
Melt Volume-Flow Rate (MVR) (190°C/2.16 kg)	6.00 to 9.00 cm <sup>3</sup> /10min	6.00 to 9.00 cm <sup>3</sup> /10min	ISO 1133
Molding Shrinkage - Flow (0.0787 in (2.00 mm))	0.015 to 0.031 in/in	1.5 to 3.1 %	ISO 294-4
Molding Shrinkage - Across Flow (0.0787 in (2.00 mm))	0.016 to 0.022 in/in	1.6 to 2.2 %	ISO 294-4
Mechanical	Typical Value (English)	Typical Value (SI)	Test Method
Tensile Modulus	377000 psi	2600 MPa	ISO 527-2
Tensile Stress (Yield)	6090 psi	42.0 MPa	ISO 527-2
Tensile Strain (Break)	20 %	20 %	ISO 527-2
Flexural Modulus	363000 psi	2500 MPa	ISO 178
Flexural Strength	10900 psi	75.0 MPa	ISO 178
Impact	Typical Value (English)	Typical Value (SI)	Test Method
Charpy Notched Impact Strength (73°F (23°C))	1.4 ft·lb/in <sup>2</sup>	3.0 kJ/m <sup>2</sup>	ISO 179
Charpy Unnotched Impact Strength 73°F (23°C)	26 ft·lb/in <sup>2</sup>	55 kJ/m <sup>2</sup>	ISO 179
Thermal	Typical Value (English)	Typical Value (SI)	Test Method
Heat Deflection Temperature 66 psi (0.45 MPa), Unannealed	293 °F	145 °C	ISO 75-2/B
Heat Deflection Temperature 264 psi (1.8 MPa), Unannealed	194 °F	90.0 °C	ISO 75-2/A
Vicat Softening Temperature	320 °F	160 °C	ISO 306
Melting Temperature (DSC)	329 to 338 °F	165 to 170 °C	ISO 3146
Electrical	Typical Value (English)	Typical Value (SI)	Test Method
Comparative Tracking Index	< 600 V	< 600 V	IEC 60112

Copyright © 2019 PolyOne Corporation. PolyOne makes no representations, guarantees, or warranties of any kind with respect to the Information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the Information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the Information. PolyOne makes no warranties or guarantees respecting suitability of either PolyOne's products or the Information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the Information and/or use or handling of any product. POLYONE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the Information or products reflected by the Information. This data sheet shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.

Flammability	Typical Value (English)	Typical Value (SI)	Test Method
Flame Rating	HB	HB	UL 94
Flammability	< 4 in/min	< 100 mm/min	FMVSS

### Processing Information

Injection	Typical Value (English)	Typical Value (SI)
Drying Temperature	176 to 212 °F	80 to 100 °C
Drying Time	2.0 to 4.0 hr	2.0 to 4.0 hr
Processing (Melt) Temp	410 to 428 °F	210 to 220 °C
Mold Temperature	140 to 212 °F	60 to 100 °C

### Notes

<sup>1</sup> Typical values are not to be construed as specifications.

<sup>2</sup> +-.0.02

### CONTACT INFORMATION

#### Americas

United States - Avon Lake  
+1 440 930 1000

United States - McHenry  
+1 815 385 8500

#### Asia

China - Guangzhou  
+86 20 8732 7260

China - Shenzhen  
+86 755 2969 2888

China - Suzhou  
+86 512 6823 24 38

China - Suzhou  
+86 512 6265 2600

Hong Kong -  
+852 2690 5332

Taiwan - Yonghe City,  
+886 9396 99740, +886 2929 1849

#### Europe

Germany - Gaggenau  
+49 7225 6802 0

Spain - Barbastro (Huesca)  
+34 974 310 314



*Beyond Polymers.*

*Better Business Solutions.™*

[www.polyone.com](http://www.polyone.com)

#### PolyOne Americas

33587 Walker Road  
Avon Lake, Ohio 44012  
United States  
+1 440 930 1000  
+1 866 POLYONE

#### PolyOne Asia

No. 88 Guoshoujing Road  
Z.J Hi-tech Park, Pudong  
Shanghai, 201203, China  
+86 21 5080 1188

#### PolyOne Europe

6 Giallewee  
+352 269 050 35

Copyright ©, 2019 PolyOne Corporation. PolyOne makes no representations, guarantees, or warranties of any kind with respect to the Information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the Information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the Information. PolyOne makes no warranties or guarantees respecting suitability of either PolyOne's products or the Information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the Information and/or use or handling of any product. POLYONE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the Information or products reflected by the Information. This data sheet shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.