



Syncure™ S1054A Natural Crosslinked Polyethylene

Key Characteristics

Product Description

Graft Resin component for PolyOne's Syncure™ system, which is a two-step, silane-grafted, moisture-crosslinkable polyethylene system. Graft Resins have approximate shelf life of 6 months from the date of production. Please consult PolyOne for its use past 6 months.

General

Material Status	• Commercial: Active
Regional Availability	• Africa & Middle East • Asia Pacific • Europe • North America
Uses	• Wire & Cable Applications
Forms	• Pellets

Technical Properties ¹

Physical	Typical Value (English)	Typical Value (SI)	Test Method
Density	0.919 g/cm ³	0.919 g/cm ³	ASTM D1505
Apparent Density ²	0.50 g/cm ³	0.50 g/cm ³	Internal Method
Melt Mass-Flow Rate (MFR) ³ (190°C/2.16 kg)	0.58 g/10 min	0.58 g/10 min	ASTM D1238
Gel Content ⁴	73 %	73 %	ASTM D2765
Mechanical	Typical Value (English)	Typical Value (SI)	Test Method
Tensile Strength ⁵ (Break)	2500 psi	17.2 MPa	ASTM D638
Tensile Elongation ⁵ (Break)	450 %	450 %	ASTM D638
Thermal	Typical Value (English)	Typical Value (SI)	Test Method
Deformation ⁶ (268°F (131°C))	6.0 %	6.0 %	UL 1581
Hot Creep Elongation ⁷	49 %	49 %	
Aging	Typical Value (English)	Typical Value (SI)	
Retention of Tensile Elongation ⁸ 250°F (121°C), 75.0 mil (1.91 mm)	93 %	93 %	
Retention of Tensile Strength ⁸ 250°F (121°C), 75.0 mil (1.91 mm)	99 %	99 %	

Additional Information

Oven Aging, Tensile, Elongation, Deformation, Hot Creep, and Gel measured on a 95 phr S1054A / 5 phr S1000B system; and cured by autoclave for 9 hours.

Processing Information

Injection	Typical Value (English)	Typical Value (SI)
Drying Temperature	160 °F	71.1 °C
Drying Time	3.0 to 4.0 hr	3.0 to 4.0 hr
Rear Temperature	400 to 420 °F	204 to 216 °C
Middle Temperature	340 to 400 °F	171 to 204 °C
Front Temperature	350 to 400 °F	177 to 204 °C
Nozzle Temperature	350 to 420 °F	177 to 216 °C
Mold Temperature	80.0 to 150 °F	26.7 to 65.6 °C

Copyright ©, 2016 PolyOne Corporation. PolyOne makes no representations, guarantees, or warranties of any kind with respect to the Information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the Information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the Information. PolyOne makes no warranties or guarantees respecting suitability of either PolyOne's products or the Information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the Information and/or use or handling of any product. POLYONE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the Information or products reflected by the Information. This data sheet shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.

Notes

¹ Typical values are not to be construed as specifications.

² Geon® 1169

³ Procedure A

⁴ Crosslinked PE, Method B (NonReferee Test)

⁵ Type IV, 20 in/min (510 mm/min)

⁶ 500 g, 1hr

⁷ SYV-40

⁸ 336 hr, UL Standard

CONTACT INFORMATION

Americas

United States - Avon Lake
+1 440 930 1000

United States - McHenry
+1 815 385 8500

Asia

China - Guangzhou
+86 20 8732 7260

China - Shenzhen
+86 755 2969 2888

China - Suzhou
+86 512 6823 24 38

China - Suzhou
+86 512 6265 2600

Hong Kong -
+852 2690 5332

Taiwan - Yonghe City,
+886 9396 99740, +886 2929 1849

Europe

Germany - Gaggenau
+49 7225 6802 0

Spain - Barbastro (Huesca)
+34 974 310 314



Beyond Polymers.

Better Business Solutions.™

www.polyone.com

PolyOne Americas

33587 Walker Road
Avon Lake, Ohio 44012
United States
+1 440 930 1000
+1 866 POLYONE

PolyOne Asia

No. 88 Guoshoujing Road
Z.J Hi-tech Park, Pudong
Shanghai, 201203, China
+86 21 5080 1188

PolyOne Europe

6 Giällewee
+352 269 050 35

Copyright ©, 2016 PolyOne Corporation. PolyOne makes no representations, guarantees, or warranties of any kind with respect to the Information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the Information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the Information. PolyOne makes no warranties or guarantees respecting suitability of either PolyOne's products or the Information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the Information and/or use or handling of any product. POLYONE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the Information or products reflected by the Information. This data sheet shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.