



Therma-Tech™ TT9200-5003 EC Grey

Polyphenylene Sulfide

Key Characteristics

Product Description

Therma-Tech™ Thermal Management Compounds have been engineered to combine the heat transfer and cooling capabilities of metals with the design freedom, weight reduction and cost advantages of thermoplastics. These materials provide the benefits of proprietary conductive additive technologies and the performance of select engineering thermoplastic resins. Therma-Tech compounds have been shown to improve thermal conductivity up to 100-times that of conventional plastics and can be used in a wide range of thermal management applications.

General

Material Status	• Commercial: Active		
Regional Availability	• Africa & Middle East • Asia Pacific	• Europe • Latin America	• North America
Filler / Reinforcement	• Glass Fiber		
Features	• Electrically Conductive	• Thermally Conductive	
Uses	• Automotive Applications • Automotive Under the Hood*	• Consumer Applications • Electrical/Electronic Applications	• Housings • Industrial Applications
RoHS Compliance	• RoHS Compliant		
Forms	• Pellets		
Processing Method	• Extrusion	• Injection Molding	

Technical Properties ¹

Physical	Typical Value (English)	Typical Value (SI)	Test Method
Specific Gravity	1.78	1.78	ISO 1183
Molding Shrinkage - Flow (Injection Molded)	2.0E-3 to 4.0E-3 in/in	0.20 to 0.40 %	ISO 294-4
Mechanical	Typical Value (English)	Typical Value (SI)	Test Method
Tensile Modulus ²	2.54E+6 psi	17500 MPa	ISO 527
Tensile Stress (Break)	8410 psi	58.0 MPa	ISO 527-2/1/50
Tensile Elongation ³ (Break)	0.30 to 0.50 %	0.30 to 0.50 %	ISO 527
Flexural Modulus ⁴ (Injection Molded)	1.96E+6 psi	13500 MPa	ISO 178
Flexural Strength ⁴ (Injection Molded)	10900 psi	75.0 MPa	ISO 178
Impact	Typical Value (English)	Typical Value (SI)	Test Method
Charpy Notched Impact Strength (73°F (23°C))	1.1 ft·lb/in ²	2.3 kJ/m ²	ISO 179
Charpy Unnotched Impact Strength 73°F (23°C)	1.9 ft·lb/in ²	3.9 kJ/m ²	ISO 179
Thermal	Typical Value (English)	Typical Value (SI)	Test Method
Heat Deflection Temperature 264 psi (1.8 MPa), Annealed	500 °F	260 °C	ISO 75-2/A
Thermal Conductivity			
73°F (23°C) ⁵	15 to 18 Btu·in/hr/ft ² /°F	2.2 to 2.6 W/m/K	ISO 8302
73°F (23°C) ⁶	24 to 28 Btu·in/hr/ft ² /°F	3.5 to 4.0 W/m/K	ASTM E1461
73°F (23°C) ⁷	110 to 120 Btu·in/hr/ft ² /°F	16 to 18 W/m/K	ASTM E1461
Electrical	Typical Value (English)	Typical Value (SI)	Test Method
Surface Resistivity	< 1.0E+4 ohms	< 1.0E+4 ohms	IEC 60093

Copyright © 2016 PolyOne Corporation. PolyOne makes no representations, guarantees, or warranties of any kind with respect to the Information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the Information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the Information. PolyOne makes no warranties or guarantees respecting suitability of either PolyOne's products or the Information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the Information and/or use or handling of any product. POLYONE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the Information or products reflected by the Information. This data sheet shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.

Flammability	Typical Value (English)	Typical Value (SI)	Test Method
Flame Rating			UL 94
0.06 in (1.5 mm)	5VA	5VA	
0.12 in (3.0 mm)	5VA	5VA	
Glow Wire Flammability Index			IEC 60695-2-12
0.031 in (0.8 mm)	1760 °F	960 °C	
0.06 in (1.6 mm)	1760 °F	960 °C	
0.12 in (3.0 mm)	> 1760 °F	> 960 °C	
Glow Wire Ignition Temperature			IEC 60695-2-13
0.12 in (3.0 mm)	> 1760 °F	> 960 °C	

Processing Information

Injection	Typical Value (English)	Typical Value (SI)
Processing (Melt) Temp	590 to 644 °F	310 to 340 °C
Mold Temperature	284 to 338 °F	140 to 170 °C

Notes

- ¹ Typical values are not to be construed as specifications.
- ² Type I, 0.039 in/min (1.0 mm/min)
- ³ Type I, 2.0 in/min (50 mm/min)
- ⁴ 0.39 in/min (10 mm/min)
- ⁵ Through Plane with Modified Transient Plane Source technique, C-Therm TCi™
- ⁶ Through-Plane
- ⁷ In-Plane

CONTACT INFORMATION

Americas

United States - Avon Lake
+1 440 930 1000

United States - McHenry
+1 815 385 8500

Asia

China - Guangzhou
+86 20 8732 7260

China - Shenzhen
+86 755 2969 2888

China - Suzhou
+86 512 6823 24 38

China - Suzhou
+86 512 6265 2600

Hong Kong -
+852 2690 5332

Taiwan - Yonghe City,
+886 9396 99740, +886 2929 1849

Europe

Germany - Gaggenau
+49 7225 6802 0

Spain - Barbastró (Huesca)
+34 974 310 314



Beyond Polymers.

Better Business Solutions. SM

www.polyone.com

PolyOne Americas

33587 Walker Road
Avon Lake, Ohio 44012
United States
+1 440 930 1000
+1 866 POLYONE

PolyOne Asia

No. 88 Guoshoujing Road
Z.J Hi-tech Park, Pudong
Shanghai, 201203, China
+86 21 5080 1188

PolyOne Europe

6 Giällewee
+352 269 050 35

Copyright ©, 2016 PolyOne Corporation. PolyOne makes no representations, guarantees, or warranties of any kind with respect to the Information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the Information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the Information. PolyOne makes no warranties or guarantees respecting suitability of either PolyOne's products or the Information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the Information and/or use or handling of any product. POLYONE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the Information or products reflected by the Information. This data sheet shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.