

# PRIMACOR™ 3540

## Copolymer

### Introduction

PRIMACOR™ 3540 Copolymer is an ethylene acrylic acid copolymer suitable for extrusion coating and extrusion lamination applications.

PRIMACOR™ 3540 Copolymer exhibits:

- Extrusion coating adhesive polymer
- Enhanced adhesion retention

Complies with:

• US. FDA 21 CFR 177.1310(b)

• EU. No 10/2011

Additives:

Antiblock: No

Slip: No

### **Properties**

		Nominal Value (English)	Nominal Value (SI)	Test Method	
Resin Properties	Density	0.936 g/cm <sup>3</sup>	0.936 g/cm <sup>3</sup>	ASTM D792	
	Melt Index (2.16 kg @190°C)	7.0 g/10min	7.0 g/10min	ASTM D1238	
	Comonomer Content <sup>1</sup>	8.5 %	8.5 %	SK Method	
	Vicat Softening Temperature	185.0 °F	85.0 °C	ASTM D1525	
	Melting Temperature (DSC)	208.4 °F	98.0 °C	SK Method	
Extrusion	Melt Temperature	500 - 572 °F	260 - 300 °C		
	Draw Down <sup>2</sup>	230 ft/min	70 m/min	SK Method	
	Neck-in <sup>3</sup>	3.2 in.	81.0 mm	SK Method	
Extrusion Condition <sup>4</sup>	<ul> <li>Extruder: A</li> <li>Screw Size: 89 mm (3.5 in.); 30:1 L/D</li> <li>Die Gap: 0.6 mm (24 mil)</li> <li>Chill Roll Finish: Matte</li> <li>Chill Roll Temperature: 15 - 20 °C (59 - 68 °F)</li> <li>Melt Temperature: 290 °C (554 °F)</li> <li>Air Gap: 250 mm (9.84 in.)</li> <li>Haul Off Speed: 100 m/min (328 ft/min)</li> </ul>				

Comonomer content measured by direct titration procedure.

<sup>3</sup> 25 g/m<sup>2</sup> (554 °F (290 °C))

#### Notes

These are *typical values* and are *not be construed as specifications*. The physical properties are highly dependent on the manufacturing conditions. So customers should confirm performances by their own tests.

 $<sup>^{2}</sup>$  Acceleration from 15 g/m $^{2}$  at 100 m/min (554 °F (290 °C))

<sup>&</sup>lt;sup>4</sup> Equipment used to process this resin should be constructed of corrosion resistant materials. Dies and adapters are recommended to be stainless steels and/or duplex chrome or nickel plated.



For additional sales, order and technical assistance

Customer Service Representative	inquiry@sk.com		
		America	
Asia Pacific		Houston	+1-713-850-0005
Shanghai (Head Quarter)	+86-21-6197-0243		
Shanghai (TS&D)	+86-21-6197-0128	Europe	
Seoul	+82-2-2121-6745	Frankfurt	+49-6967738103
Tokyo	+81-3-3591-0343	Madrid	+34-910477688
Southeast Asia/Australia		Middle East/Africa	
Singapore	+65-6671-1566	Dubai	+971-4-252-5277

Revised: Oct. 31<sup>st</sup>, 2017 Copyright SK global chemical