

SAMYANG CORPORATION

407 3-Ga Palbok-Dong Cheonju, YKCheonbuk 560-200 Korea, Republic of

TRILEN: TRILEN ML950(x)

Polypropylene (PP), pellets

(x) - Represents any number 1-9 incl.



| Flammability | Value | Test Method |
|--------------|---------|----------------------|
| Flame Rating | | |
| 1.5 mm, ALL | НВ | UL 94 |
| 3.0 mm, ALL | НВ | UL 94 |
| 3.0 mm, ALL | HB40 | IEC 60695-11-10, -20 |
| 1.5 mm, ALL | HB75 | IEC 60695-11-10, -20 |
| Thermal | Value | Test Method |
| RTI Elec | | UL 746 |
| 1.5 mm | 65.0 °C | |
| 3.0 mm | 65.0 °C | |
| RTI Imp | | UL 746 |
| 1.5 mm | 65.0 °C | |
| 3.0 mm | 65.0 °C | |
| RTI Str | | UL 746 |
| 1.5 mm | 65.0 °C | |
| 3.0 mm | 65.0 °C | |
| | | |

Page 1 of 1

UL and the UL logo are trademarks of UL LLC Copyright © 2021 All Rights Reserved. | www.ul.com

Form Number: E121254-103774288

Report Date: 7/6/2018
Last Revised: 7/5/2018 11:18:38 PM