

SAMYANG CORPORATION

407 3-Ga Palbok-Dong

Cheonju, YKCheonbuk 560-200 Korea, Republic of



TRILOY: 2(xx)GNH(e)

Polycarbonate/Acrylonitrile Butadiene Styrene (PC/ABS), pellets

- (e) May be replaced by one, two, or three numbers and/or letter(s) denoting customer code, except TP260D.
- (xx) Represents any number 00-99 incl. to denote customer code.

Flammability	Value	Test Method
Flame Rating		UL 94
1.4 mm, ALL	V-0	IEC 60695-11-10, -20
1.5 mm, ALL	V-0	
2.0 mm, ALL	V-0	
3.0 mm, ALL	V-0	
Thermal	Value	Test Method
RTI Elec		UL 746
1.4 mm	60.0°C	
1.5 mm	60.0°C	
2.0 mm	60.0°C	
3.0 mm	60.0°C	
RTI Imp		UL 746
1.4 mm	60.0°C	
1.5 mm	60.0°C	
2.0 mm	60.0°C	
3.0 mm	60.0 °C	
RTI Str		UL 746
1.4 mm	60.0 °C	
1.5 mm	60.0 °C	
2.0 mm	60.0 °C	
3.0 mm	60.0 °C	

UL and the UL logo are trademarks of UL LLC Copyright © 2021 All Rights Reserved. | www.ul.com

Page 1 of 1

Form Number: E121254-100810203

Report Date: 12/7/2010

Last Revised: 3/4/2020 7:02:47 PM