

SAMYANG CORPORATION

407 3-Ga Palbok-Dong Cheonju, YKCheonbuk 560-200 Korea, Republic of



TRILOY: CF210(e), EM(e)210NH

Polycarbonate/Acrylonitrile Butadiene Styrene (PC/ABS), pellets

(e) - May be replaced by one, two, or three numbers and/or letter(s) denoting customer code, except TP260D.

Flammability	Value	Test Method
Flame Rating		UL 94
1.0 mm, ALL	V-2	IEC 60695-11-10, -20
1.2 mm, ALL	V-2	
1.5 mm, ALL	V-0	
2.0 mm, ALL	V-0	
3.0 mm, ALL	V-0	
Thermal	Value	Test Method
RTI Elec		UL 746
1.0 mm	60.0°C	
1.2 mm	60.0°C	
1.5 mm	60.0°C	
2.0 mm	60.0 °C	
3.0 mm	60.0 °C	
RTI Imp		UL 746
1.0 mm	60.0 °C	
1.2 mm	60.0 °C	
1.5 mm	60.0 °C	
2.0 mm	60.0 °C	
3.0 mm	60.0 °C	
RTI Str		UL 746
1.0 mm	60.0 °C	
1.2 mm	60.0°C	
1.5 mm	60.0°C	
2.0 mm	60.0°C	
3.0 mm	60.0°C	

UL and the UL logo are trademarks of UL LLC Copyright © 2021 All Rights Reserved. | www.ul.com

Page 1 of 1

Form Number: E121254-100632488

Report Date: 3/11/2010
Last Revised: 10/24/2018 6:41:17 PM