

## SAMYANG CORPORATION

407 3-Ga Palbok-Dong Cheonju, YKCheonbuk 560-200 Korea, Republic of



## TRIMMA: FT61(xx)(e)

Polymethyl Methacrylate (PMMA), pellets

- (e) May be replaced by one, two, or three numbers and/or letter(s) denoting customer code, except TP260D.
- (xx) Represents any number 00-99 incl. to denote customer code.

Flammability	Value	Test Method
Flame Rating		
1.5 mm, ALL	НВ	UL 94
3.0 mm, ALL	НВ	UL 94
3.0 mm, ALL	HB40	IEC 60695-11-10, -20
1.5 mm, ALL	HB75	IEC 60695-11-10, -20
Thermal	Value	Test Method
RTI Elec		UL 746
1.5 mm	50.0 °C	
3.0 mm	50.0 °C	
RTI Imp		UL 746
1.5 mm	50.0 °C	
3.0 mm	50.0 °C	
RTI Str		UL 746
1.5 mm	50.0 °C	
3.0 mm	50.0 °C	

Page 1 of 1 Form Number: E121254-100101834

Report Date: 6/10/2008 Last Revised: 10/22/2008

UL and the UL logo are trademarks of UL LLC Copyright © 2021 All Rights Reserved. | www.ul.com