

## SAMYANG CORPORATION

407 3-Ga Palbok-Dong

Cheonju, YKCheonbuk 560-200 Korea, Republic of



## TRIREX: NH3025N(e)

Polycarbonate (PC), pellets

(e) - May be replaced by one, two, or three numbers and/or letter(s) denoting customer code, except TP260D.

Flammability	Value	Test Method
Flame Rating		UL 94
1.5 mm, ALL	V-0, 5VB	IEC 60695-11-10, -20
2.0 mm, ALL	V-0, 5VB	
2.5 mm, ALL	V-0, 5VB	
3.0 mm, ALL	V-0, 5VB	
Thermal	Value	Test Method
RTI Elec		UL 746
1.5 mm	80.0°C	
2.0 mm	80.0°C	
2.5 mm	80.0°C	
3.0 mm	80.0°C	
RTI Imp		UL 746
1.5 mm	80.0°C	
2.0 mm	80.0°C	
2.5 mm	80.0°C	
3.0 mm	80.0°C	
RTI Str		UL 746
1.5 mm	80.0°C	
2.0 mm	80.0°C	
2.5 mm	80.0°C	
3.0 mm	80.0°C	

Page 1 of 1 Form Number: E121254-100158082

Report Date: 8/17/2006 Last Revised: 11/27/2008

UL and the UL logo are trademarks of UL LLC Copyright © 2021 All Rights Reserved. | www.ul.com