

SAMYANG CORPORATION

407 3-Ga Palbok-Dong

Cheonju, YKCheonbuk 560-200 Korea, Republic of



TRIREX: VB30(xx)G(e) Polycarbonate (PC), pellets

(e) - May be replaced by one, two, or three numbers and/or letter(s) denoting customer code, except TP260D.

(xx) - Represents any number 00-99 incl. to denote customer code.

Flammability	Value	Test Method
Flame Rating		UL 94
0.8 mm, ALL	V-2	IEC 60695-11-10, -20
1.2 mm, ALL	V-2	
2.0 to 2.2 mm, ALL	V-2	
Thermal	Value	Test Method
RTI Elec		UL 746
0.8 mm	80.0°C	
1.2 mm	80.0°C	
2.0 to 2.2 mm	80.0°C	
RTI Imp		UL 746
0.8 mm	80.0°C	
1.2 mm	80.0°C	
2.0 to 2.2 mm	80.0 °C	
RTI Str		UL 746
0.8 mm	80.0 °C	
1.2 mm	80.0 °C	
2.0 to 2.2 mm	80.0°C	

Page 1 of 1 Form Number: E121254-100857353

Report Date: 1/31/2011 Last Revised: 1/31/2011

UL and the UL logo are trademarks of UL LLC Copyright © 2021 All Rights Reserved. | www.ul.com