

Material Safety Data Sheet (MSDS)

Page : 1/6

Product Name : KEPAMID 6150GF+ (All Color)

Revision Date : February. 13, 2015 (Re. 0)

1. Identification of the substance/mixture and of the company/undertaking product identifier

Product identifier: **KEPAMID 6150GF+ (All Color)**
“+”: Blank or replaced with (H)

Product Description: PPA (Polyphthalamide)

Relevant identified uses of the substance or mixture and uses advised against : Extrusion, Injection (Except usage)

Details of the supplier of the safety data sheet

Company Identification KOREA ENGINEERING PLASTICS Co., Ltd.
450, KONGDUCK-DONG, MAPO-GU, SEOUL, KOREA
Tel) 82-2-707-6831~9 www.kepital.com

Manufacturer Identification KOREA ENGINEERING PLASTICS Co., Ltd. Pyongtaek plant
402, CHUPAL-RI, PAENGUNG, PYONGTAEK, KYUNGGI-DO
Tel) 82-31-691-3822~3 www.kepital.com

Emergency telephone number Tel) +49(0)611-962-7383
KEP Europe GmbH Rheingaustrasse 190-196 65203 Wiesbaden, Germany

2. Hazards Identification

Classification of the substance or mixture

No need for classification according to GHS criteria for this product.

Label elements & Statements of hazard

The product does not require a hazard warning label in accordance with EC Directives.

Other hazards

NFPA(SCALE 0-4) : Health =1, Flammability =1, Physical Hazard=0
(Note : These ratings are determined by Korea Engineering Plastics Co., Ltd.)

3. Composition, Information on Ingredients

Composition:	INGREDIENT	CAS NUMBER	Content(%)
	Polyphthalamide	25776-72-1	50 ± 5
	Glass Fiber	65997-17-3	50 ± 5
	Stabilizer etc.		< 3

4. First Aid Measures

Description of first aid measures

Inhalation

Pellets is not likely to be inhaled due to physical form. When gas and fumes from molten plastics is inhaled, remove to fresh air. Seek medical attention if breathing difficulties occur.

Skin Contact

If hot and molten polymer or hot vapors contact skin, cool rapidly with cold water. If polymer is stuck to skin, do not remove, and seek medical attention. And allow adhered polymer to come off naturally. Removal of adhered polymer may result in

Product Name : KEPAMID 6150GF+ (All Color)**Revision Date** : February. 13, 2015 (Re. 0)

more tissue damage than if polymer is allowed to come off over them.

Eye Contact Immediately flush eyes with plenty of water for at least 15 minutes. Seek medical attention if discomfort persists.

Ingestion If a significant quantity has been swallowed, give two glasses of water to dilute. Seek medical attention.

Most important symptoms and effects, both acute and delayed

No significant reaction of the human body to the product known.

Information on: Phosphine

Thermal decomposition of phosphorous may emit phosphine. The PEL/TLV for phosphine is 0.3 ppm ACGIH, OSHA (Final); 1 ppm STEL ACGIH, OSHA (Final).

Inhalation of phosphine may result in severe pulmonary irritation, cough, headache, chest tightness, dizziness, lethargy and stupor. Delayed pulmonary edema may result. Inhalation also results in CNS effects including nausea, dizziness, fatigue, ataxia, seizures and possibly coma. Cardiac arrhythmias may also be noted. Gastric disturbances including nausea, vomiting, abdominal pain and diarrhea may also be noted. Liver and kidney damage may also be noted. Exposure to 8 ppm concentrations at 1 or 2 hrs/day were found to be fatal to humans.

Information on: Phosphorous

Inhalation of vapors or smoke from products containing red phosphorus may result in respiratory tract irritation, lung injury or systemic effects. In animal studies, red phosphorus was reported to cause adverse lung and kidney effects.

5. Fire Fighting Measures**Suitable extinguishing media**

Carbon dioxide, Dry Chemical, Foam or Water spray. Dry powder, Solid extinguishing agent

Special hazards arising from the substance or mixture

Hazardous Product of Combustion : Carbon monoxide and Carbon dioxide, Formaldehyde vapors

Hazardous of fire, explosion :

- Overheating may result in release of formaldehyde, which may irritate the eyes, skin and respiratory tract.
- Base resin dust/powder has a US Bureau of Mines relative dust explosion hazard rating of severe.

Advice for fire-fighters

Firefighters should wear self-contained breathing apparatus and full fire-fighting turn-out gear (bunker gear). Keep personnel removed from and upwind of fire. Water should be used to keep fire-exposed containers cool. Product burns with a very hot, but very faint blue flame. Water, foam and dry chemical may cause damage to electrical equipment.

6. Accidental Release Measures**Personal precautions, protective equipment**

- High risk of slipping due to leakage/spillage of product. In Case of Spill or Leak, sweep or gather up spills and place in proper container for recovery or disposal. Keep unnecessary people away, isolate hazard area and deny entry.
- Information regarding personal protection can be found in section 8.

Environmental precautions

No special environmental precautions necessary.

Methods and material for containment and cleaning up

Product Name : KEPAMID 6150GF+ (All Color)

Revision Date : February. 13, 2015 (Re. 0)

Move to the approved place based on the disposal regulation.

7. Handling and Storage

Precautions for safe handling

Do not handle hot or molten material without appropriate protective equipment. Maintain good housekeeping in work areas. Do not exceed recommended process temperature to minimize release of decomposition products. Do not smoke in areas where polymer dust is present. Appropriate measures should be taken to control the generation and accumulation of dust during conveying and processing operations.

Conditions for safe storage, including any incompatibilities

Store in well-ventilated area away from heat and sunlight. Keep Container closed to prevent contamination.

8. Exposure Controls, Personal Protection

Exposure controls

Local Exhaust : Recommended when appropriate to control employee exposure to dust or process vapors.

General : May not be adequate as the sole means to control employee exposure.

Protective Equipment

Eyes Safety eyewear recommended

Skin

When thermal or melt processing, wear long pants, long sleeves, well insulated gloves, and face shield when there is a chance of contact.

Inhalation

A NIOSH approved respirator is recommended if there is a possibility of dust generation above permissible exposure limits or that decomposition vapors may be generated.

Control parameter

Operations involving grinding and machining of parts should be reviewed to assure that particulate levels are kept below recommended standards. Formaldehyde is a hazardous degradation product.

Ingredient	Agency	Value
Nuisance/Inert Dust	PEL (OSHA)	15 mg/cu m (total)
		5 mg/cu m (respirable)
Nuisance Particulates	TLV(ACGIP)	10 mg/cu m (total)
		3 mg/cu m (respirable)

9. Physical and Chemical Properties

Physical Form : Solid / Pellets
Odor : Slight, specific
Odor threshold : No data available
pH Value : Not applicable
Melting Point : 305~325 deg C
Boiling Point and Range : Not applicable (Solid)
Flash Point : No data available.
Evaporation rate: Not applicable
Inflammability: No data available
Explosion range : No data available
Vapor Pressure : No data available

Product Name : KEPAMID 6150GF+ (All Color)**Revision Date** : February. 13, 2015 (Re. 0)

Water Solubility : Negligible < 0.1%
Relative vapor density : Not applicable
Specific Gravity : 1.58 - 1.64
Partitioning coefficient n-octanol/water (log Kow): No data available
Ignition temperature : No data available
Decomposition temperature : > 350 °C
Viscosity : No data available
Molecular weight : Not applicable

10. Stability and Reactivity**Reactivity** : Stable under normal conditions of use.**Chemical Stability** : Stable under normal conditions of use and storage.**Condition to Avoid**

Avoid prolonged exposure at or above the recommended processing temperature..

Decomposition

Decomposition of this material depends on the length of time exposed to elevated temperatures and may be accelerated by contaminants, pigments and other additives.

Hazardous Polymerization : Will not occur.**11. Toxicological Information****Information on toxicological effects**

No specific information available on the product.

12. Ecological Information**Toxicity** : No specific information available on the product.**Persistence and degradability** : No specific information available on the product. Product is insoluble in water.**Bio accumulative potential** : This material is considered to be non-biodegradable.**Mobility in soil** : No specific information available on the product.**Results of PBT and vPvB assessment**

The product does not fulfill the criteria for PBT(persistent/bioaccumulative/toxic) or vPvB(very persistent/very bioaccumulative).

13. Disposal Considerations**Waste treatment methods**

Recycling is encouraged. Dispose in accordance with all applicable regulations. This product, as shipped, is not a RCRA hazardous waste under present EPA regulations.

14. Transport Information**UN No.** : Not classified as a dangerous good under transport regulations. (UN RTDG)**Shipping information** : Not applicable

Product Name : KEPAMID 6150GF+ (All Color)**Revision Date** : February. 13, 2015 (Re. 0)**Transport hazardous grade** : Not applicable**Container grade** : Not applicable**Marine Pollution** : Not applicable**Safety measure for transport** : Not applicable- **Fire** : No available data- **Leak** : No available data**15. Regulatory Information****Safety, health and environmental regulation/legislation specific for the substance or mixture****U.S. Regulations****TSCA** : All the ingredients are listed in the TSCA Inventory or are compliant with the TSCA polymer Exemption Rule.**SARA** : This product does not contain any toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and of 40 CFR 372.**Labeling According to EEC Directives** : Not subject to labeling.**Germany Regulations** : Not classified according to German "Hazardous Substance" regulations.**EU regulation** : Not contain materials listed in ;**WEEE** (Waste on Electrical and Electronic Equipment): EU-Directive 2002/96/EC**RoHS**(Restriction of Hazardous Substances in electrical and electronic equipment) : EU-Directive 2002/95/EC**Directive 2003/11/EC**: Restriction (ban) of Pentabromodiphenylether and octabromodiphenylether**16. Other Information****Source**

- Hazardous Substances Data Bank (HSDB)
- UN RTDG (Recommendations on the Transport of Dangerous Good) Rev.17
- International Uniform Chemical Information Database (IUCLID)

Revision : 0 (February. 13, 2015)**Disclaimer**

This product is not intended for use in medical applications involving permanent implantation in the human body.

The information contained herein is based on the present state of our knowledge. We don't suggest or guarantee that any hazards listed herein are the only ones that exist. Korea Engineering Plastics Co., Ltd. makes no warranty of any kind concerning the safe use of this material in your process or in combination with other substances. Effects can be aggravated by other materials and this material may aggravate the effects of other materials. Users have the sole responsibility to determine the suitability of the materials of any use and the manner of use contemplated. Users must meet all applicable safety and health standards.

- The End of MSDS -