

# Material Safety Data Sheet (MSDS)

Page : 1/6

Product Name : KEPEX 3930GF+ (All Color)

Revision Date : May. 3, 2013 (Re. 0)

## 1. Identification of the substance/mixture and of the company/undertaking product identifier

Product identifier: **KEPEX 3930GF+ (All Color)**

“ + ” : Blank or replaced with (U)

Product Description: Poly(1,4-butylene terephthalate)

Relevant identified uses of the substance or mixture and uses advised against : Extrusion, Injection (Except usage)

### Details of the supplier of the safety data sheet

Company Identification KOREA ENGINEERING PLASTICS Co., Ltd.  
450, KONGDUCK-DONG, MAPO-GU, SEOUL, KOREA  
Tel) 82-2-707-6831~9 [www.kepital.com](http://www.kepital.com)

Manufacturer Identification KOREA ENGINEERING PLASTICS Co., Ltd. Pyongtaek plant  
402, CHUPAL-RI, PAENGUNG, PYONGTAEK, KYUNGGI-DO  
Tel) 82-31-691-3822~3 [www.kepital.com](http://www.kepital.com)

Emergency telephone number Tel) +49(0)611-962-7383  
KEP Europe GmbH Rheingastrasse 190-196 65203 Wiesbaden, Germany

## 2. Hazards Identification

### Classification of the substance or mixture

No need for classification according to GHS criteria for this product.

### Possible Hazards:

No specific dangers known, if the regulations/notes for storage and handling are considered.

Danger of burns while handling the hot product.

### Label elements & Statements of hazard

The product does not require a hazard warning label in accordance with EC Directives and GHS criteria.

### Other hazards

NFPA(SCALE 0-4) : Health =1, Flammability =1, Physical Hazard=0

(Note : These ratings are determined by Korea Engineering Plastics Co., Ltd.)

## 3. Composition, Information on Ingredients

| Composition: | INGREDIENT      | CAS NUMBER             | Content(%) |
|--------------|-----------------|------------------------|------------|
|              | PBT, PET        | 26062-94-2, 25038-59-9 | 50 ± 5     |
|              | Glass fiber     | 65997-17-3             | 30 ± 5     |
|              | ABS             | 9003-56-9              | 20 ± 5     |
|              | Stabilizer etc. |                        | < 3        |

## 4. First Aid Measures

### Description of first aid measures

**Product Name** : KEPEX 3930GF+ (All color)**Revision Date** : May. 3, 2013 (Re.0)**Inhalation**

Pellets is not likely to be inhaled due to physical form. When gas and fumes from molten plastics is inhaled, remove to fresh air. Seek medical attention if breathing difficulties occur.

**Skin Contact**

If hot and molten polymer or hot vapors contact skin, cool rapidly with cold water. If polymer is stuck to skin, do not remove, and seek medical attention. And allow adhered polymer to come off naturally. Removal of adhered polymer may result in more tissue damage than if polymer is allowed to come off over them.

**Eye Contact** Immediately flush eyes with plenty of water for at least 15 minutes. Seek medical attention if discomfort persists.

**Ingestion** If a significant quantity has been swallowed, give two glasses of water to dilute. Seek medical attention.

**Most important symptoms and effects, both acute and delayed**

No significant reaction of the human body to the product known.

**5. Fire Fighting Measures****Suitable extinguishing media**

Carbon dioxide, Dry Chemical, Foam or Water spray. Dry powder, Solid extinguishing agent

**Special hazards arising from the substance or mixture**

Hazardous Product of Combustion : Carbon monoxide and Carbon dioxide, Formaldehyde vapors

Hazardous of fire, explosion :

- Overheating may result in release of formaldehyde, which may irritate the eyes, skin and respiratory tract.
- Base resin dust/powder has a US Bureau of Mines relative dust explosion hazard rating of severe.

**Advice for fire-fighters**

Firefighters should wear self-contained breathing apparatus and full fire-fighting turn-out gear (bunker gear). Keep personnel removed from and upwind of fire. Water should be used to keep fire-exposed containers cool. Product burns with a very hot, but very faint blue flame. Water, foam and dry chemical may cause damage to electrical equipment.

**6. Accidental Release Measures****Personal precautions, protective equipment**

- High risk of slipping due to leakage/spillage of product. In Case of Spill or Leak, sweep or gather up spills and place in proper container for recovery or disposal. Keep unnecessary people away, isolate hazard area and deny entry.
- Information regarding personal protection can be found in section 8.

**Environmental precautions**

No special environmental precautions necessary.

**Methods and material for containment and cleaning up**

Move to the approved place based on the disposal regulation.

**7. Handling and Storage****Precautions for safe handling**

Do not handle hot or molten material without appropriate protective equipment. Maintain good housekeeping in work areas. Do not exceed recommended process temperature to minimize release of decomposition products. Do not smoke in areas where polymer dust is present. Appropriate measures should be taken to control the generation and accumulation of dust during conveying and processing operations.

Product Name : KEPEX 3930GF+ (All color)

Revision Date : May. 3, 2013 (Re.0)

**Conditions for safe storage, including any incompatibilities**

Store in well-ventilated area away from heat and sunlight. Keep Container closed to prevent contamination.

**8. Exposure Controls, Personal Protection****Exposure controls****Local Exhaust** : Recommended when appropriate to control employee exposure to dust or process vapors.**General** : May not be adequate as the sole means to control employee exposure.**Protective Equipment****Eyes** Safety eyewear recommended**Skin**

When thermal or melt processing, wear long pants, long sleeves, well insulated gloves, and face shield when there is a chance of contact.

**Inhalation**

A NIOSH approved respirator is recommended if there is a possibility of dust generation above permissible exposure limits or that decomposition vapors may be generated.

**Control parameter**

Operations involving grinding and machining of parts should be reviewed to assure that particulate levels are kept below recommended standards. Formaldehyde is a hazardous degradation product.

| Ingredient            | Agency      | Value                  |
|-----------------------|-------------|------------------------|
| Nuisance/Inert Dust   | PEL (OSHA ) | 15 mg/cu m (total)     |
|                       |             | 5 mg/cu m (respirable) |
| Nuisance Particulates | TLV(ACGIP)  | 10 mg/cu m (total)     |
|                       |             | 3 mg/cu m (respirable) |

**9. Physical and Chemical Properties**

**Physical Form** : Solid / Pellets  
**Odor** : Slight, specific  
**Odor threshold** : No data available  
**pH Value** : Not applicable  
**Melting Point** : 220~270 deg C  
**Boiling Point and Range** : Not applicable (Solid)  
**Flash Point** : No data available  
**Evaporation rate** : Not applicable  
**Inflammability** : No data available  
**Explosion range** : No data available  
**Vapor Pressure** : No data available  
**Water Solubility** : Negligible < 0.1%  
**Relative vapor density** : Not applicable  
**Specific Gravity** : 1.43 - 1.49  
**Partitioning coefficient n-octanol/water (log Kow)** : No data available  
**Ignition temperature** : No data available  
**Decomposition temperature** : No data available  
**Viscosity** : No data available, the product is a solid  
**Molecular weight** : Not applicable

Product Name : KEPEX 3930GF+ (All color)

Revision Date : May. 3, 2013 (Re.0)

## 10. Stability and Reactivity

**Reactivity :** Stable under normal conditions of use.

**Chemical Stability :** Stable under normal conditions of use and storage.

**Possibility of hazardous reactions:** No hazardous reactions known. The product is chemically stable.

### Condition to Avoid

Avoid prolonged exposure at or above the recommended processing temperature.

### Incompatible materials

Substance to avoid: No substance known that should be avoided.

**Hazardous decomposition products:** Carbon monoxide, ammonia, aliphatic amines, amides, nitriles,  $\epsilon$ -caprolactam, cyclopentanone, hydrogen cyanide which may be toxic, flammable and/or irritating.

### Hazardous Polymerization :

## 11. Toxicological Information

**It is generally considered biologically inert.**

**Acute toxicity :** No data available

**Irritation :** No data available

.

**Sensitization :** No data available

.

**Genetic toxicity :** No data available

**Carcinogenicity :** No data available

.

**Reproductive toxicity :** No data available

**Developmental toxicity :** No data available

**Other relevant toxicity information :** No data available

## 12. Ecological Information

**Toxicity :** No specific information available on the product.

**Persistence and degradability :** No specific information available on the product. Product is insoluble in water.

**Bio accumulative potential :** This material is considered to be non-biodegradable.

**Mobility in soil :** No specific information available on the product.

### Results of PBT and vPvB assessment

The product does not fulfill the criteria for PBT(persistent/bioaccumulative/toxic) or vPvB(very persistent/very bioaccumulative).

Product Name : KEPEX 3930GF+ (All color)

Revision Date : May. 3, 2013 (Re.0)

### 13. Disposal Considerations

#### Waste treatment methods

Recycling is encouraged. Dispose in accordance with all applicable regulations. This product, as shipped, is not a RCRA hazardous waste under present EPA regulations.

### 14. Transport Information

**UN No. :** Not classified as a dangerous good under transport regulations. (UN RTDG)

**Shipping information :** Not applicable

**Transport hazardous grade :** Not applicable

**Container grade :** Not applicable

**Marine Pollution :** Not applicable

**Safety measure for transport :** Not applicable

- **Fire :** No available data

- **Leak :** No available data

### 15. Regulatory Information

#### Safety, health and environmental regulation/legislation specific for the substance or mixture

##### U.S. Regulations

**TSCA :** All the ingredients are listed in the TSCA Inventory or are compliant with the TSCA polymer Exemption Rule.

**SARA :** This product does not contain any toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and of 40 CFR 372.

**Labeling According to EEC Directives :** Not subject to labeling.

**Germany Regulations :** Not classified according to German "Hazardous Substance" regulations.

**EU regulation :** Not contain materials listed in ;

**WEEE** (Waste on Electrical and Electronic Equipment): EU-Directive 2002/96/EC

**RoHS**(Restriction of Hazardous Substances in electrical and electronic equipment) : EU-Directive 2002/95/EC

**Directive 2003/11/EC:** Restriction (ban) of Pentabromodiphenylether and octabromodiphenylether

### 16. Other Information

#### Source

- Hazardous Substances Data Bank (HSDB)
- UN RTDG (Recommendations on the Transport of Dangerous Good) Rev.17
- International Uniform Chemical Information Database (IUCLID)

**Revision : 0** (May. 3, 2013 )

#### Disclaimer

This product is not intended for use in medical applications involving permanent implantation in the human body.

The information contained herein is based on the present state of our knowledge. We don't suggest or guarantee that any hazards listed herein are the only ones that exist. Korea Engineering Plastics Co., Ltd. makes no warranty of any kind concerning the safe use of this material in your process or in combination with other substances.

**Product Name** : KEPEX 3930GF+ (All color)**Revision Date** : May. 3, 2013 (Re.0)

---

Effects can be aggravated by other materials and this material may aggravate the effects of other materials. Users have the sole responsibility to determine the suitability of the materials of any use and the manner of use contemplated. Users must meet all applicable safety and health standards.

**- The End of MSDS -**