## Acetal Copolymer KEPITAL®

**TX-21** 

- Grade.

-

•

.....

				KEPITAL TX-21
		4 GEN 4 D 502		1.00
		ASTM D792	-	1.39
	23 , 60%RH	ASTM D570	%	0.22
	100 2.16 kg	ASTM D1238	a/10min	14
	190 , 2.16 kg 10 /min	ASTM D1238 ASTM D3418	g/10min	165
	$4.6 \text{kg}_{\text{f}}/\text{cm}^2$	ASTM D3418 ASTM D648		158
	$18.6 \mathrm{kg_f/cm^2}$	AS 1 W D046		110
	20 80	ASTM D696	10 <sup>-5</sup> cm/cm/	13
	t 0.8mm	UL94	-	НВ
	23	ASTM D638	$kg_f/cm^2$	550
	23	ASTM D638	%	65
	23	ASTM D790	$kg_f/cm^2$	800
	23	ASTM D790	$10^4 \mathrm{kg_f/cm^2}$	2.45
	t 2mm	ASTM D732	$kg_f/cm^2$	
Izod	t 3.2mm	ASTM D256	kg <sub>f</sub> • cm/cm	7.5
Rockwell	M scale	ASTM D785	_	M80
	$10^6$ Hz	ASTM D150	_	
	$10^6$ Hz	ASTM D150	_	
		ASTM D257		$1   10^{16}$
		ASTM D257	• cm	$1   10^{14}$
		ASTM D149	kV/mm	
(// )	t 3mm, 100mm		%	2.0
			$ extstyle m ilde{ extstyle M}/ extstyle k extstyle g_{ m f}$ • km	0.10
			$ extstyle{mm}^3/kg_{ m f}$ • km	0.03
( <b>µ</b> )			-	0.18
			-	0.23

) 1. , . . .

2.