

## WPP PP PPC2TF2HS-Natural

## Washington Penn Plastic Co. Inc. - Polypropylene Copolymer

Wednesday, October 9, 2019

General Information					
General					
Material Status	Commercial: Active				
Availability	<ul><li>Africa &amp; Middle East</li><li>Asia Pacific</li></ul>	<ul><li>Europe</li><li>Latin America</li></ul>	North America		
Filler / Reinforcement	<ul> <li>Talc, 20% Filler by Weight</li> </ul>				
Features	<ul> <li>Copolymer</li> </ul>	<ul> <li>Good Impact Resistance</li> </ul>	<ul> <li>Good Stiffness</li> </ul>		
Appearance	<ul> <li>Colors Available</li> </ul>				
Processing Method	Blow Molding	<ul> <li>Sheet Extrusion</li> </ul>			

ASTM & ISO Properties <sup>1</sup>					
Physical	Nominal Value	Unit	Test Method		
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	7.0	g/10 min	ASTM D1238		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength <sup>2</sup> (Yield)	24.8	MPa	ASTM D638		
Flexural Modulus <sup>3</sup>	2340	MPa	ASTM D790		
Impact	Nominal Value	Unit	Test Method		
Notched Izod Impact (23°C)	53	J/m	ASTM D256		
Additional Information					

Tested at  $23 \pm 2^{\circ}$ C (73.4 ± 3.6°F) and  $50 \pm 5\%$  relative humidity unless otherwise noted.

## **Notes**

<sup>1</sup> Typical properties: these are not to be construed as specifications.



<sup>&</sup>lt;sup>2</sup> 51 mm/min

<sup>3 13</sup> mm/min