



The MSDS format adheres to the standards and regulatory requirements
of the United States and may not meet regulatory requirements
in other countries.

DuPont
Material Safety Data Sheet

Page 1

"DELTRIN" ACETAL RESIN CUSTOM COLORS ON SYNONYM LIST DEL001
DEL001 Revised 23-AUG-2006

CHEMICAL PRODUCT/COMPANY IDENTIFICATION

Material Identification

"DELTRIN" is a registered trademark of DuPont.

Tradenames and Synonyms

"DELTRIN" 100 BK602,
"DELTRIN" 100 BL6002,
"DELTRIN" 100 BL6003,
"DELTRIN" 100 BN6003,
"DELTRIN" 100 BNA089,
"DELTRIN" 100 GY1007,
"DELTRIN" 100 GY1061,
"DELTRIN" 100 GYA124,
"DELTRIN" 100 WT760,
"DELTRIN" 100 YL403,
"DELTRIN" 100 YL6003,
"DELTRIN" 500 BK602,
"DELTRIN" 500 BK656,
"DELTRIN" 500 BL734,
"DELTRIN" 500 BL1071,
"DELTRIN" 500 BL1076,
"DELTRIN" 500 BL8084,
"DELTRIN" 500 BLH707,
"DELTRIN" 500 BLH787,
"DELTRIN" 500 BN1079,
"DELTRIN" 500 BN1096,
"DELTRIN" 500 BN6001,
"DELTRIN" 500 BN6003,
"DELTRIN" 500 BN7008,
"DELTRIN" 500 GN1061,
"DELTRIN" 500 GN1071,
"DELTRIN" 500 GN1072,
"DELTRIN" 500 GN6001,
"DELTRIN" 500 GN6002,
"DELTRIN" 500 GN6006,
"DELTRIN" 500 GNH755,
"DELTRIN" 500 GY1007,
"DELTRIN" 500 GY1073,
"DELTRIN" 500 GY1095,
"DELTRIN" 500 GY1107,

(CHEMICAL PRODUCT/COMPANY IDENTIFICATION - Continued)

"DELRIN" 500 GY1125,
"DELRIN" 500 GY1130,
"DELRIN" 500 GY1133,
"DELRIN" 500 GY6001,
"DELRIN" 500 GY6002,
"DELRIN" 500 GY6004,
"DELRIN" 500 GYA214,
"DELRIN" 500 GYA601,
"DELRIN" 500 GYA214,
"DELRIN" 500 GYA601,
"DELRIN" 500 ORH625,
"DELRIN" 500 RD1058,
"DELRIN" 500 VTH621,
"DELRIN" 500 WT602,
"DELRIN" 500 WT610,
"DELRIN" 500 WT760,
"DELRIN" 500 WT1068,
"DELRIN" 500 WT6002,
"DELRIN" 500 YL6003,
"DELRIN" 500 YL7013,
"DELRIN" 500 YLH645,
"DELRIN" 500CL BK602,
"DELRIN" 500CL GY1170,
"DELRIN" 500CL GYB6002,
"DELRIN" 507 GN6001,
"DELRIN" 507 GN6006,
"DELRIN" 507 GY6002,
"DELRIN" 507 GY6030,
"DELRIN" 507 GY7080,
"DELRIN" 507 GY807,
"DELRIN" 507 OR6002,
"DELRIN" 507 RD6001,
"DELRIN" 507 RD836,
"DELRIN" 507 VT642,
"DELRIN" 507 WT602,
"DELRIN" 507 WT610,
"DELRIN" 900 AL1002,
"DELRIN" 900 BNH845,
"DELRIN" 900 BK602,
"DELRIN" 900 GK658,
"DELRIN" 900 GYA204,
"DELRIN" 900 WT6002,
"DELRIN" 907 GY9003,
"DELRIN" 907 GY9022,
"DELRIN" DE8502 BK602,
"DELRIN" DE8502 NC010,
"DELRIN" DE9070 RD1001,
"DELRIN" DE9101 BK602,
"DELRIN" RSM100BK2,

Company Identification

MANUFACTURER/DISTRIBUTOR
DuPont Engineering Polymers

(CHEMICAL PRODUCT/COMPANY IDENTIFICATION - Continued)

1007 Market Street
Wilmington, DE 19898

PHONE NUMBERS

Product Information : 1-(800)-441-7515
Transport Emergency : 1-(800)-424-9300
Medical Emergency : 1-(800)-441-3637-----
COMPOSITION/INFORMATION ON INGREDIENTS

Components

Material	CAS Number	%
ACETAL POLYMER		>97
STABILIZER		<2
PIGMENT		<1
CARBON BLACK	1333-86-4	0-0.5
FORMALDEHYDE	50-00-0	<0.005

Components (Remarks)

Material is not known to contain Toxic Chemicals under Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

Additives in this product do not present a respiration hazard unless the product is ground to a powder of respirable size and the dust is inhaled. All dusts are potentially injurious to the respiratory tract if respirable particles are generated and inhaled in sufficiently high concentrations. Good industrial hygiene practices, as with all dusts, should include precautions to prevent inhalation of respirable particles.

HAZARDS IDENTIFICATION

Potential Health Effects

ADDITIONAL HEALTH EFFECTS

Read the specific datasheet for product to be used before using this resin, as well as the Delrin Molding Guide.

ACETAL POLYMER

There are no known effects from exposure to the Delrin polymer itself. If overheated, the polymer releases formaldehyde which may cause skin, eye, and respiratory irritation and allergic reactions.

(HAZARDS IDENTIFICATION - Continued)

Significant skin permeation and systemic toxicity after contact appears unlikely. There are inconclusive or unverified reports of human sensitization.

CARBON BLACK

Immediate effects of overexposure to Carbon Black by inhalation may include irritation of the nose, throat, and lungs with cough, difficulty breathing or shortness of breath.

If particles from Carbon Black contact the eye, mechanical irritation with tearing, pain or blurred vision may result.

Significant skin permeation, and systemic toxicity, after contact with Carbon Black appears unlikely. There are no reports of human sensitization.

Epidemiologic studies demonstrate no significant risk of human cancer from exposure to Carbon Black. While some reports cite an increased incidence of pulmonary abnormalities, such as decreased pulmonary function and radiological changes among Carbon Black workers, other reports show no correlation between exposure and effects on pulmonary function or disease.

Increased susceptibility to the effects of Carbon Black may be observed in persons with pre-existing disease of the lungs.

Carcinogenicity Information

The following components are listed by IARC, NTP, OSHA or ACGIH as carcinogens.

Material	IARC	NTP	OSHA	ACGIH
CARBON BLACK	2B			
FORMALDEHYDE	1	X	X	A2

FIRST AID MEASURES-----
First Aid

INHALATION

No specific intervention is indicated as the compound is not likely to be hazardous by inhalation. Consult a physician if necessary. If exposed to fumes from overheating or combustion, move to fresh air. Consult a physician if symptoms persist.

SKIN CONTACT

The compound is not likely to be hazardous by skin contact, but cleansing the skin after use is advisable. If molten polymer gets on skin, cool rapidly with cold water. Do not attempt to peel polymer from skin. Obtain medical treatment for thermal burn.

EYE CONTACT

(FIRST AID MEASURES - Continued)

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

INGESTION

No specific intervention is indicated as compound is not likely to be hazardous by ingestion.

FIRE FIGHTING MEASURES

Flammable Properties

Flash Point : Not Applicable

"Delrin" dust cloud ignition temperature is 440 degrees C (824 degrees F).

Fire and Explosion Hazards:

Like most organic materials in powder form, dust generated from this product may form a flammable dust-air mixture. Potential for a dust explosion may exist. Minimize the generation and accumulation of dust. Keep away from sources of ignition. Burns with invisible flame. Hazardous gases/vapors produced in fire are carbon monoxide, formaldehyde.

Extinguishing Media

Water, Foam, Dry Chemical, CO2.

Fire Fighting Instructions

Keep personnel removed and upwind of fire. Wear self-contained breathing apparatus.

ACCIDENTAL RELEASE MEASURES

Safeguards (Personnel)

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

Spilled material is a slipping hazard.

Spill Clean Up

Spilled material is a slipping hazard.

Sweep up to avoid slipping hazard.

HANDLING AND STORAGE

Handling (Personnel)

See FIRST AID and PERSONAL PROTECTIVE EQUIPMENT SECTIONS.

Handling (Physical Aspects)

Open container only in well-ventilated area.

Minimize the generation and accumulation of dust.

Storage

Store in a well ventilated area away from heat and sunlight.

Keep container closed to prevent contamination.

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls

VENTILATION When hot processing this material, use local and/or general exhaust ventilation to control the concentration of vapors and fumes below exposure limits.

In cutting or grinding operations with this material, use local exhaust to control the concentration of dust below exposure limits.

Personal Protective Equipment

Eye/Face Protection

Wear safety glasses. Wear coverall chemical splash goggles and face shield when possibility exists for eye or face contact due to splashing or spraying of molten material. A full face mask positive-pressure air-supplied respirator provides protection from eye irritation.

Respirators

When temperatures exceed 230 degrees C and ventilation is inadequate to maintain concentrations below exposure limits, use a positive-pressure air-supplied respirator. Air- purifying respirators may not provide adequate protection.

During grinding, sawing, routing, drilling or sanding operations use a NIOSH/MSHA approved air-purifying respirator with dust/mist cartridge or canister if airborne particulate concentrations are expected to exceed permissible exposure levels.

Protective Clothing

(EXPOSURE CONTROLS/PERSONAL PROTECTION - Continued)

If there is potential contact with hot/molten material, wear heat resistant clothing and footwear.

Wear leather or cotton gloves when grinding, sawing, routing, drilling or sanding.

Exposure Guidelines

Exposure Limits

"DELTRIN" ACETAL RESIN CUSTOM COLORS ON SYNONYM LIST DEL001

PEL (OSHA) : Particulates (Not Otherwise Regulated)
15 mg/m³, 8 Hr. TWA, total dust
5 mg/m³, 8 Hr. TWA, respirable dust

Other Applicable Exposure Limits

CARBON BLACK

PEL (OSHA) : 3.5 mg/m³, 8 Hr. TWA
TLV (ACGIH) : 3.5 mg/m³, 8 Hr. TWA, A4
AEL * (DuPont) : 0.5 mg/m³, 8 & 12 Hr. TWA, (Polynuclear
Aromatic Hydrocarbon Content <0.1%)
Includes Channel, Lamp, and Thermal
Black

FORMALDEHYDE

PEL (OSHA) : 0.75 ppm, 0.92 mg/m³, 8 Hr. TWA
STEL 2 ppm, 2.5 mg/m³
TLV (ACGIH) : Ceiling 0.3 ppm, A2
Sensitizer
AEL * (DuPont) : 0.5 ppm, 8 & 12 Hr. TWA
1 ppm, 15 minute TWA

* AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence.

PHYSICAL AND CHEMICAL PROPERTIES

Physical Data

Melting Point : 175-183 C (347-361 F)
Solubility in Water : Insoluble
Odor : Slight formaldehyde
Form : Pellets
Specific Gravity : >1

STABILITY AND REACTIVITY

Chemical Stability

Stable at normal temperatures and storage conditions.

Conditions to Avoid

Maintain polymer melt temperatures below 230 C (446 F) . Avoid prolonged exposure at or above the recommended processing temperatures.

Incompatibility with Other Materials

Incompatible with strong acids and bases (decomposes forming formaldehyde) and strong oxidizing agents. At melt temperatures, acetal resins are incompatible with halogenated polymers such as PVC and PVDC and any elastomers containing halogenated polymers. Even small amounts of such contaminants can cause sudden and spontaneous formaldehyde gas formation. Workplace fume concentrations well above threshold levels are a likely result. Unsafe pressurization of equipment, e.g., extruders, molds, can also result.

Do not contaminate either virgin resin or rework. Do not mix this resin with pigments or additives other than those designated by DuPont. Do not mix this grade with other grades of Delrin, nor with any other resins, without first consulting DuPont. Doing any of the above may change the thermal stability of this resin and potentially cause decomposition.

Decomposition

Decomposition of this material depends on the length of time it is exposed to elevated temperatures. At the recommended processing temperature of 210-220 C (410-428 F), decomposition should not be significant until after 30 minutes. Decomposition may be accelerated by contaminants, pigments, and/or other additives.

Autoclaving with pressurized steam may lead to a rapid decomposition and should be done for only minimum amounts of time. COOL COMPLETELY BEFORE OPENING the autoclave.

Hazardous gas/vapor produced is formaldehyde.

Polymerization

Polymerization will not occur.

TOXICOLOGICAL INFORMATION

Animal Data

Delrin

Inhalation 6 hour LC50: > 22,000 mg/m3 in rats

Oral LD50: > 11,000 mg/kg in rats

Delrin is not a skin irritant, and is not a skin sensitizer in animals.

Single or repeated inhalation exposures to high concentrations of Delrin dust resulted in collapse of some areas of the lungs, other areas were over-inflated. This effect was seen as late as 11-19 days post-exposure.

No toxic effect were observed in animals ingesting Delrin.

No animal test reports are available to define carcinogenic, mutagenic, developmental, or reproductive hazards.

Carbon Black

Oral ALD, rat: > 25,100 mg/kg

Repeated inhalation exposure of animals to Carbon Black caused inflammation of the respiratory tract, lungs and emphysema.

Repeated exposure to high doses of Carbon Black by ingestion or skin contact caused no significant toxicological effects.

No adequate studies have been conducted in animals to define the carcinogenicity of Carbon Black by ingestion. In several skin painting studies using various Carbon Blacks no carcinogenicity was observed. Tests by inhalation for carcinogenicity in rats show significant increases in lung tumors in female rats but not male rats. In another study using female mice exposed by inhalation to Carbon Black there was no increase in the incidence of respiratory tract tumors. Researchers conducting the rat inhalation studies believe that these effects probably result from the massive accumulation of small dust particles in the lung which overwhelm the normal lung clearance mechanisms. This represents "lung overload" phenomenon, rather than a specific chemical effect of the dust particle in the lung.

Tests have shown that this material does not cause genetic damage in bacterial or mammalian cell cultures. Tests in animals for genetic toxicity have produced mostly negative results. No animal data are available to define developmental or reproductive toxicity.

ECOLOGICAL INFORMATION

Ecotoxicological Information

AQUATIC TOXICITY:

No information is available. Toxicity is expected to be low based on insolubility in water. Do not discharge to streams, ponds, lakes or sewers.

DISPOSAL CONSIDERATIONS

Waste Disposal

Preferred options for disposal are (1) recycling, (2) incineration with energy recovery, and (3) landfill. The high fuel value of this product makes option 2 very desirable for material that cannot be recycled, but incinerator must be capable of scrubbing out acidic combustion products. Treatment, storage, transportation, and disposal must be in accordance with applicable federal, state/provincial, and local regulations.

TRANSPORTATION INFORMATION

Shipping Information

Not regulated in transportation by DOT/IMO/IATA.

REGULATORY INFORMATION

U.S. Federal Regulations

TSCA Inventory Status : In compliance with TSCA Inventory requirements for commercial purposes.

State Regulations (U.S.)

STATE RIGHT-TO-KNOW

No substances on the state hazardous substances list, for the states indicated below, are used in the manufacture of products on this Material Safety Data Sheet, with the exceptions indicated.

SUBSTANCES ON THE PENNSYLVANIA HAZARDOUS SUBSTANCES LIST PRESENT AT A CONCENTRATION OF 1 % OR MORE (0.01% FOR SPECIAL HAZARDOUS SUBSTANCES)- Carbon black.

WARNING - SUBSTANCES KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM- Formaldehyde.

(REGULATORY INFORMATION - Continued)

The State of California, under Proposition 65, regulates Carbon Black - airborne, unbound particles of respirable size as a carcinogen. In this product, carbon black is not supplied in the form regulated in California.

SUBSTANCES ON THE NEW JERSEY WORKPLACE HAZARDOUS SUBSTANCE LIST
PRESENT AT A CONCENTRATION OF 1% OR MORE (0.1% FOR SUBSTANCES
IDENTIFIED AS CARCINOGENS, MUTAGENS OR TERATOGENS)- Carbon black.

OTHER INFORMATION

Additional Information

MEDICAL USE: CAUTION: Do not use in medical applications
involving permanent implantation in the human body. For other
medical applications see DuPont CAUTION Bulletin No. H-50102.

The data in this Material Safety Data Sheet relates only to the
specific material designated herein and does not relate to use in
combination with any other material or in any process.

Responsibility for MSDS : REGULATORY AFFAIRS
DUPONT ENGINEERING POLYMERS
Address : CHESTNUT RUN PLAZA 713
WILMINGTON, DE 19880-0713
Telephone : 302-999-4257

Indicates updated section.

This information is based upon technical information believed to be
reliable. It is subject to revision as additional knowledge and
experience is gained.

End of MSDS