

**ZYTEL® Nylon resin**Ref. 150000000699
Version 2.0Revision Date 04.08.2020
Issue Date 04.08.2020

This Product Safety Information Sheet is provided as general information for health and safety guidance.

SECTION 1: Identification of the substance/mixture and of the company/undertaking**Product identifier**

Product name : ZYTEL® Nylon resin

Types : 73G15HSL, 73G15L (1); 73G20HSL, 73G20L (2); 73G25HSL, 73G25L (3); 73G30HSL, 73G30L, 73G30W, FE270041 (4); 73G35HSL, 73G35L (5); 73G40, 73G40HSL, 73G40HSLA (6); 73G45, 73G45HSL, 73G45L (7); 73G50HSL, 73G50HSLA, 73G50L (8)

Recycling code : 1) ISO 11469 : >PA6-GF15<; 2) ISO 11469 : >PA6-GF20<; 3) ISO 11469 : >PA6-GF25<; 4) ISO 11469 : >PA6-GF30<; 5) ISO 11469 : >PA6-GF35<; 6) ISO 11469 : >PA6-GF40<; 7) ISO 11469 : >PA6-GF45<; 8) ISO 11469 : >PA6-GF50<

Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Resin for moulding and/or extrusion

Details of the supplier

Company : Performance Specialty Products Iberica S.L.
Avda. Diagonal, 571
ES-08029 Barcelona
Spain

Telephone : +34-98-512-4000

Telefax : +34-98-512-4090

E-mail address : sds-support@che.dupont.com

Emergency telephone number

Emergency telephone number : +(44)-870-8200418 (CHEMTREC)

SECTION 2: Hazards identification**Classification of the substance or mixture****Classification according to Regulation (EU) 1272/2008 (CLP)**

Not a classified substance or mixture according to Regulation (EC) No. 1272/2008.

Label elements**Labelling according to Regulation (EU) 1272/2008 (CLP)**

**ZYTEL® Nylon resin**Ref. 150000000699
Version 2.0Revision Date 04.08.2020
Issue Date 04.08.2020

Not a classified substance or mixture according to Regulation (EC) No. 1272/2008.

Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
None.

SECTION 3: Composition/information on ingredients

Chemical nature of the substance/mixture : Polyamide
: Glass fibre
: Additives

This product does not contain any components that require disclosure.

SECTION 4: First aid measures**Description of first aid measures**

General advice : Remove from exposure, lie down. Never give anything by mouth to an unconscious person. No hazards which require special first aid measures. If a person vomits when lying on his back, place him in the recovery position.

Inhalation : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. Consult a physician after significant exposure.

Skin contact : Cool skin rapidly with cold water after contact with molten material. Do not peel polymer from the skin. Obtain medical attention.

Eye contact : Flush eyes with water as a precaution. Obtain medical attention.

Ingestion : No hazards which require special first aid measures. Drink water as a precaution.

SECTION 5: Firefighting measures**Extinguishing media**

Suitable extinguishing media : Carbon dioxide (CO₂), Dry powder, Foam, Water

**ZYTEL® Nylon resin**Ref. 150000000699
Version 2.0Revision Date 04.08.2020
Issue Date 04.08.2020**Special hazards arising from the substance or mixture**

Specific hazards during firefighting : Large molten masses may ignite spontaneously in air. Water quenching is good practice. Under conditions giving incomplete combustion, hazardous gases produced may consist of: Carbon monoxide Carbon dioxide (CO₂) (see also section 10)

Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus. Wear suitable protective equipment.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Do not allow run-off from fire fighting to enter drains or water courses. Burns after ignition without external heat source (IEC 60695-11-10 : HB).

SECTION 6: Accidental release measures**Personal precautions, protective equipment and emergency procedures**

Personal precautions : Ventilate the area. Refer to protective measures listed in sections 7 and 8.

Environmental precautions

Environmental precautions : Try to prevent the material from entering drains or water courses. Do not contaminate surface water.

Methods and materials for containment and cleaning up

Methods for cleaning up : Clean up promptly by sweeping or vacuum. Sweep up or vacuum up spillage and collect in suitable container for disposal.

Other information : Use mechanical handling equipment.

SECTION 7: Handling and storage**Precautions for safe handling**

Advice on safe handling : Protect from contamination. When opening containers, avoid breathing vapours that may be emanating. Open container only in well-ventilated area. Provide appropriate exhaust ventilation at dryers, machinery and at places where dust or volatiles can be generated. General precaution for all plastics and elastomers: For personal protection see section 8. In case of insufficient ventilation, wear suitable respiratory equipment. No special handling advice required.

Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).

Dust explosion class : no data available

**ZYTEL ® Nylon resin**Ref. 150000000699
Version 2.0Revision Date 04.08.2020
Issue Date 04.08.2020**Conditions for safe storage, including any incompatibilities**

- Requirements for storage areas and containers : No special storage conditions required. Keep container tightly closed in a dry and well-ventilated place. Protect from contamination.
- Further information on storage conditions : none
- Advice on common storage : No special restrictions on storage with other products.
- Other data : No decomposition if stored and applied as directed.

SECTION 8: Exposure controls/personal protection

If sub-section is empty then no values are applicable. For further information on any control parameters provided, please refer to the relevant regulation.

Exposure controls

- Eye protection : Safety glasses with side-shields Wear tightly fitting chemical splash goggles and face shield when possibility exists for eye and face contact due to spattering or splashing of molten material.
- Hand protection : Material: Heat insulating gloves
Protective gloves (Type : Kevlar® - heat resistant, use possible until worn out)
- Skin and body protection : If there is a potential for contact with hot/molten material wear heat resistant clothing and footwear. Regular cleaning of equipment, work area and clothing.
- Hygiene measures : Wash hands before breaks and at the end of workday. General precaution for all plastics and elastomers: Do not breathe fumes evolved from hot polymer.
- Respiratory protection : When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Suitable respiratory equipment: Half mask with a particle filter FFP2/FFP3 (EN149)

SECTION 9: Physical and chemical properties**Information on basic physical and chemical properties**

- Form : pellets
- Colour : various
- Odour : none
- pH : Not applicable

**ZYTEL® Nylon resin**Ref. 150000000699
Version 2.0Revision Date 04.08.2020
Issue Date 04.08.2020

Melting point/range	: 220 - 225 °C
Flash point	: Not applicable
Ignition temperature	: 450 °C
Thermal decomposition	: > 300 °C
Density	: 1,25 - 1,70 g/cm ³ , Method: ISO 1183
Water solubility	: insoluble

Other information

No other data to be specially mentioned.

SECTION 10: Stability and reactivity

Possibility of hazardous reactions	: None. Further information : During drying, cleaning and moulding, small amounts of hazardous gases and/or particulate matter may be released. These may irritate eyes, nose and throat. Large molten masses may give off hazardous gases. Water quenching is good practice. Stable under normal conditions.
Conditions to avoid	: Avoid heating for prolonged periods above the recommended upper processing limit.
Incompatible materials	: Strong acids and oxidizing agents
Hazardous decomposition products	: Acrolein acetaldehydes Ammonia Cyclopentanone Hydrogen cyanide (hydrocyanic acid) Caprolactam

SECTION 11: Toxicological information

The product contains no substances which at their given concentration, are considered to be hazardous to health.

SECTION 12: Ecological information

The product contains no substances classified as hazardous to the environment in concentrations which should be taken into account.

SECTION 13: Disposal considerations**Waste treatment methods**

Product : Like most thermoplastic plastics the product can be recycled. Where possible

**ZYTEL® Nylon resin**Ref. 150000000699
Version 2.0Revision Date 04.08.2020
Issue Date 04.08.2020

recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Can be landfilled, when in compliance with local regulations. Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

European Waste Catalogue number : 07 02 99: Wastes not otherwise specified.

SECTION 14: Transport information**ADR**

- | | |
|-----------------------------------|----------------|
| 14.1. UN number: | Not applicable |
| 14.2. UN proper shipping name: | Not applicable |
| 14.3. Transport hazard class(es): | Not applicable |
| 14.4. Packing group: | Not applicable |
| 14.5. Environmental hazards: | none |

- 14.6. Special precautions for user:
Not classified as dangerous in the meaning of transport regulations.

IATA_C

- | | |
|-----------------------------------|----------------|
| 14.1. UN number: | Not applicable |
| 14.2. UN proper shipping name: | Not applicable |
| 14.3. Transport hazard class(es): | Not applicable |
| 14.4. Packing group: | Not applicable |
| 14.5. Environmental hazards: | none |

- 14.6. Special precautions for user:
Not classified as dangerous in the meaning of transport regulations.

IMDG

- | | |
|-----------------------------------|----------------|
| 14.1. UN number: | Not applicable |
| 14.2. UN proper shipping name: | Not applicable |
| 14.3. Transport hazard class(es): | Not applicable |
| 14.4. Packing group: | Not applicable |
| 14.5. Environmental hazards: | none |

- 14.6. Special precautions for user:
Not classified as dangerous in the meaning of transport regulations.

- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code
Not applicable

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Other regulations :

No specific information about other regulations/legislation to be mentioned.

**ZYTEL® Nylon resin**Ref. 150000000699
Version 2.0Revision Date 04.08.2020
Issue Date 04.08.2020**SECTION 16: Other information****Abbreviations and acronyms**

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute toxicity estimate
CAS-No.	Chemical Abstracts Service number
CLP	Classification, Labelling and Packaging
EbC50	Concentration at which 50% reduction of biomass is observed
EC50	Median effective concentration
EN	European Norm
EPA	Environmental Protection Agency
ErC50	Concentration at which a 50% inhibition of growth rate is observed
EyC50	Concentration at which 50 % inhibition of yield is observed
IATA_C	International Air Transport Association (Cargo)
IBC	International Bulk Chemical Code
ICAO	International Civil Aviation Organization
ISO	International Standard Organization
IMDG	International Maritime Dangerous Goods
LC50	Median Lethal Concentration
LD50	Median Lethal Dose
LOEC	Lowest Observed Effect Concentration
LOEL	Lowest observed effect level
MARPOL	International Convention for the Prevention of Marine Pollution from Ships
n.o.s.	Not Otherwise Specified
NOAEC	No Observed Adverse Effect Concentration
NOAEL	No observed adverse effect level
NOEC	No Observed Effect Concentration
NOEL	No Observed Effect Level
OECD	Organisation for Economic Co-operation and Development
OPPTS	Office of Prevention, Pesticides and Toxic Substances
PBT	Persistent, Bioaccumulative and Toxic
STEL	Short term exposure limit
TWA	Time Weighted Average (TWA):
vPvB	very Persistent and very Bioaccumulative

Restrictions on use

Do not use DuPont materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless the material has been provided from DuPont under a written contract that is consistent with DuPont policy regarding medical applications and expressly acknowledges the contemplated use. For further information, please contact your DuPont representative. You may also request a copy of the DuPont POLICY Regarding Medical Applications and DuPont CAUTION Regarding Medical Applications.

Further information

Before use read DuPont's safety information.

® Registered trademark of E.I. du Pont de Nemours and Company

™ Trademark of E.I. du Pont de Nemours and Company.

An Exposure Scenario (ES) is not required.



ZYTEL® Nylon resin

Ref. 150000000699
Version 2.0

Revision Date 04.08.2020
Issue Date 04.08.2020

Significant change from previous version is denoted with a double bar.

The information provided in this Product Safety Information Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The above information relates only to the specific materials(s) designated herein and may not be valid for such materials or in any process or if the material is altered or processed, unless specified in the text.