## **Preliminary Technical Data Sheet** CAPILENE® CE 85 B



## **Specialty Polypropylene**

## **Product Description**

CAPILENE® CE 85 B is a specialty polypropylene combining typical advantages of polypropylene random and heterophasic copolymers, and is designed for extrusion applications.

The grade is being in development status, this is a preliminary data sheet and subjected to changes.

Features:	Excellent impact Very low stress whitening Good organoleptic properties Excellent transparency		<ul><li>High gloss</li><li>Short cycle time</li><li>Clarified</li><li>Mold release</li></ul>		
Uses:	Detergent and cosmetics clear containers High clarity films		<ul><li>Corrugated sheets</li><li>Profiles</li></ul>		
Processing Methods:	Blow Molding Sheet extrusion		• Thermoforming		
Properties		Method	Typical Value*	Unit	
Physical					
Melt Flow Rate	(230°C/2.16 kg)	ISO 1133	1.8	g/10 min	
Mechanical					
Flexural Modulus	(5 mm/min)	ISO 178	800	MPa	
Izod Impact Strength, notched	(+23°C)	ISO 180	35	kJ/m²	
Izod Impact Strength, notched	(+0°C)	ISO 180	20	kJ/m²	
Izod Impact Strength, notched	(-20°C)	ISO 180	4	kJ/m²	
Thermal					
Vicat Softening Temperature	(10 N)	ISO 306	131	°C	
<b>Heat Deflection Temperature</b>	(0.45 MPa)	ISO 75-2	74	°C	
Optical					
Haze	(1 mm plaque)	ASTM D1003	10	%	
Haze	(50 µm film)	ASTM D1003	3	%	

<sup>\*</sup>Typical values; not to be construed as specifications.

## Health, Quality, Regulations and Safety

This product is not classified as dangerous substance. Material safety data sheets, international standards certificates (e.g. ISO 9001) and other regulatory documents are available on our website. Carmel Olefins products have not been tested and therefore not validated for use in pharmaceutical/medical applications, and their suitability for these uses cannot be guaranteed. It is the customer's responsibility to test and approve their technical and regulatory suitability in order to satisfy themselves as to the particular purpose and application(s).

Carmel Olefins Ltd. POB 1468 Haifa 31014 Israel

Email: techserv@caol.co.il

Date: January 2022 Website: http://www.Carmel-Olefins.co.il

The information contained herein is to our knowledge accurate and reliable as of the date of publication. Carmel Olefins recommends its customers to review both the manufacturing processes and applications of Carmel Olefins products to ensure, that the products are not used for purposes they are not intended or tested for. Carmel Olefins extends no warranties and makes no representations as to the accuracy or completeness of the information contained herein and assumes no responsibility regarding the consequences of its use or for any printing errors. Our products are intended for sale to industrial and commercial customers. Data in this document relates only to the specific product and may not be valid for any combination of this product with other materials. It is the customer's responsibility to inspect and test our products in order to satisfy himself as to the suitability of the products for the customer's particular purpose. The customer is responsible for its employees' safety and the appropriate, safe and legal use, processing, handling and disposing of our products and packaging. Carmel Olefins shall not be liable for any consequential, incidental or indirect damages resulting from this statement or its use.