

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



VAMAC® ULTRA XF-OR ethylene acrylic elastomer VAML (US)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	2024/08/27	300000005744	Date of first issue: 2024/08/27

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : VAMAC® ULTRA XF-OR ethylene acrylic elastomer VAML (US)
Product code : 000000000027042849

Manufacturer or supplier's details

Company : Celanese (Shanghai) International Trading Co., Ltd
赛拉尼斯(上海)国际贸易有限公司
Address : 4560 Jinke Road, Zhangjiang, Pudong
Shanghai, China 201210
Telephone : 86-21-38619288
Emergency telephone : CHEMTREC International phone number: +1-703-527 3887,
+86 532 8388-9090 (China, 24h)
E-mail address : HazCom@celanese.com

Recommended use of the chemical and restrictions on use

Recommended use : Polymer
Restrictions on use : For manufacturing and research use only

Emergency Overview

Appearance	: bales
Color	: translucent
Odor	: acrylate

Not a hazardous substance or mixture.

GHS Classification

Not a hazardous substance or mixture according to the Globally Harmonized System (GHS).

GHS label elements

Not a hazardous substance or mixture according to the Globally Harmonized System (GHS).

Physical and chemical hazards

Not classified based on available information.

Health hazards

Not classified based on available information.

Environmental hazards

Not classified based on available information.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



VAMAC® ULTRA XF-OR ethylene acrylic elastomer VAML (US)

Version 1.0	Revision Date: 2024/08/27	SDS Number: 300000005744	Date of last issue: - Date of first issue: 2024/08/27
----------------	------------------------------	-----------------------------	--

Substance / Mixture : Mixture

Components

This product does not contain any components that require disclosure according to country regulations.

4. FIRST AID MEASURES

General advice	: Remove from exposure, lie down. Never give anything by mouth to an unconscious person.
If inhaled	: If inhaled, remove to fresh air. Call a physician. If not breathing, give artificial respiration.
In case of skin contact	: In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Cool skin rapidly with cold water after contact with molten material. Do not attempt to remove material from the skin. Obtain medical treatment for thermal burn.
In case of eye contact	: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.
If swallowed	: Not a probable route of exposure. However, in case of accidental ingestion, call a physician.
Most important symptoms and effects, both acute and delayed	: None known.
Notes to physician	: Treat symptomatically

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Water Foam Dry chemical Carbon dioxide (CO2)
Specific hazards during fire fighting	: Combustible Large molten masses may ignite spontaneously in air. Water quenching is good practice.
Hazardous combustion products	: Hazardous combustion products may include: (see also section 10)
Specific extinguishing methods	: Evacuate personnel and keep upwind of fire. The solid polymer can only be burned with difficulty.
Special protective equipment for fire-fighters	: Wear self-contained breathing apparatus and protective suit.

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



VAMAC® ULTRA XF-OR ethylene acrylic elastomer VAML (US)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	2024/08/27	300000005744	Date of first issue: 2024/08/27

6. ACCIDENTAL RELEASE MEASURES

Environmental precautions : Do not discharge to streams, ponds, lakes or sewers.

Methods and materials for containment and cleaning up : Shovel or sweep up.

7. HANDLING AND STORAGE

Handling

Advice on safe handling : When opening containers, avoid breathing vapours that may be emanating.
Open container only in well-ventilated area.
Do not breathe vapours or fumes that may be evolved during processing.
Before using, read the product bulletin.

Avoidance of contact : Strong acids
and
Oxidizing agents

Storage

Conditions for safe storage : Keep containers tightly closed in a cool, well-ventilated place.
Keep container closed to prevent contamination.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Dust (inhalable and respirable fraction)	Not Assigned	TWA (Respirable particulate matter)	3 mg/m ³	ACGIH
		TWA (Inhalable particulate matter)	10 mg/m ³	ACGIH

Engineering measures : When hot processing this material, use local and/or general exhaust ventilation to maintain the concentration of vapors and fumes below exposure limits.
Local exhaust ventilation is preferred.
See Bulletin "Proper Use of Local Exhaust Ventilation During Processing of Plastics".
Use sufficient ventilation to keep employee exposure below recommended limits.

Personal protective equipment

Respiratory protection : A respiratory protection program that meets country requirements must be followed whenever workplace conditions warrant respirator use.

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



VAMAC® ULTRA XF-OR ethylene acrylic elastomer VAML (US)

Version 1.0	Revision Date: 2024/08/27	SDS Number: 300000005744	Date of last issue: - Date of first issue: 2024/08/27
----------------	------------------------------	-----------------------------	--

Eye/face protection	: Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer. Wear safety glasses with side shields. Wear tightly fitting chemical splash goggles and face shield when possibility exists for eye and face contact due to splattering or splashing of molten material.
Skin and body protection	: Where there is potential for skin contact, have available and wear as appropriate, impervious gloves, apron, pants, jacket, hood and boots. If there is a potential for contact with hot/molten material wear heat resistant clothing and footwear.
Hand protection Material	: Protective gloves

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: bales
Color	: translucent
Odor	: acrylate
Odor Threshold	: 0.0048 - 20 ppm Methyl acrylate
Flash point	: ca. 212.5 °C (1,016 hPa) Method: Setaflash closed cup - SCC, closed cup
Relative density	: 1 - 1.1
Solubility(ies) Water solubility	: insoluble
Decomposition temperature	: > 282 °C Thermal decomposition of the resin accelerates above temperature listed. Decomposition can occur below the recommended processing temperature limit. Decomposition is a function of both processing temperature and time at that temperature.

10. STABILITY AND REACTIVITY

Reactivity	: Stable at normal ambient temperature and pressure.
Possibility of hazardous reactions	: Polymerization will not occur. Stable at normal ambient temperature and pressure. Large molten masses may give off hazardous gases. Water quenching is good practice.

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



VAMAC® ULTRA XF-OR ethylene acrylic elastomer VAML (US)

Version 1.0	Revision Date: 2024/08/27	SDS Number: 300000005744	Date of last issue: - Date of first issue: 2024/08/27
----------------	------------------------------	-----------------------------	--

Conditions to avoid	: Temperature > 282 °C Decomposes on heating. At temperatures above the "conditions to avoid" temperature, thermal decomposition of the resin accelerates. Decomposition can occur below the recommended processing temperature limit. Decomposition is a function of both processing temperature and time at that temperature.
Incompatible materials	: Strong acids and Oxidizing agents
Hazardous decomposition products	: Hazardous decomposition products may include: Alcohols Ketones Aldehydes Acrolein Esters Carboxylic acid Organic acids Acrylic acid maleic anhydride Formaldehyde acetaldehydes Carbon dioxide (CO ₂) Carbon monoxide Phosphonic acid Oxides of phosphorus

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitization

Skin sensitization

Not classified due to lack of data.

Respiratory sensitization

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



VAMAC® ULTRA XF-OR ethylene acrylic elastomer VAML (US)

Version 1.0	Revision Date: 2024/08/27	SDS Number: 300000005744	Date of last issue: - Date of first issue: 2024/08/27
----------------	------------------------------	-----------------------------	--

STOT-single exposure

Not classified due to lack of data.

STOT-repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

Further information

Product:

Remarks : No data is available on the product itself.

12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : There is no data available for this product.
Toxicity is expected to be low based on insolubility in water.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Preferred options for disposal are recycling, incineration with energy recovery, and landfill.
The high fuel value of this product makes incineration very desirable for material that cannot be recycled.
Treatment, storage, transportation, and disposal must be in accordance with applicable federal, state/provincial, and local regulations.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : Not applicable
Proper shipping name : Not applicable

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



VAMAC® ULTRA XF-OR ethylene acrylic elastomer VAML (US)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	2024/08/27	300000005744	Date of first issue: 2024/08/27

Class	: Not applicable
Subsidiary risk	: Not applicable
Packing group	: Not applicable
Labels	: Not applicable
Environmentally hazardous	: no

IATA-DGR

UN/ID No.	: Not applicable
Proper shipping name	: Not applicable
Class	: Not applicable
Subsidiary risk	: Not applicable
Packing group	: Not applicable
Labels	: Not applicable
Packing instruction (cargo aircraft)	: Not applicable
Packing instruction (passenger aircraft)	: Not applicable

IMDG-Code

UN number	: Not applicable
Proper shipping name	: Not applicable
Class	: Not applicable
Subsidiary risk	: Not applicable
Packing group	: Not applicable
Labels	: Not applicable
EmS Code	: Not applicable
Marine pollutant	: no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

GB 6944/12268

UN number	: Not applicable
Proper shipping name	: Not applicable
Class	: Not applicable
Subsidiary risk	: Not applicable
Packing group	: Not applicable
Labels	: Not applicable
Marine pollutant	: no

Special precautions for user

Remarks	: Not classified as dangerous in the meaning of transport regulations.
---------	--

15. REGULATORY INFORMATION

National regulatory information

Law on the Prevention and Control of Occupational Diseases

Regulations on Safety Management of Hazardous Chemicals

Catalogue of Hazardous Chemicals	: Not applicable
----------------------------------	------------------

Hazardous Chemicals for Priority Management under	: Neither banned nor restricted
---	---------------------------------

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



VAMAC® ULTRA XF-OR ethylene acrylic elastomer VAML (US)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	2024/08/27	300000005744	Date of first issue: 2024/08/27

SAWS

Regulation of Environmental Management on the First Import of Chemicals and the Import and Export of Toxic Chemicals

China Severely Restricted Toxic Chemicals for Import : Neither banned nor restricted and Export

Regulation on the Administration of Precursor Chemicals

Catalogue and Classification of Precursor Chemicals : Not listed

16. OTHER INFORMATION

Revision Date : 2024/08/27
Date format : yyyy/mm/dd

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIH / TWA : 8-hour, time-weighted average

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



VAMAC® ULTRA XF-OR ethylene acrylic elastomer VAML (US)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	2024/08/27	300000005744	Date of first issue: 2024/08/27

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CN / EN