

**TPETPEFILMS KG**

Version 2.0

Revision Date 05/29/2015

Ref. 130000042744

This SDS adheres to the standards and regulatory requirements of the United States and may not meet the regulatory requirements in other countries.

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : TPETPEFILMS KG  
Restrictions on use : Do not use product for anything outside of the above specified uses  
Manufacturer/Supplier : Celanese Sales U.S. Ltd.  
222 West Las Colinas Boulevard Suite 900N  
Irving, TX 75039

Telephone : +1-800-441-7515 (outside the U.S. ++1 972-443-4000 E-mail address: HazCom  
E-mail address : 1-800-441-3637 (outside the U.S. 1-302-774-1139)  
Transport Emergency : Domestic NA: 800-424-9300 International, CALL +1 703-527-3887 (collect calls

**SECTION 2. HAZARDS IDENTIFICATION**

Not classified as a hazardous substance or mixture according to the Occupational Safety and Health Administration (OSHA) Hazard Communication Standard 2012.

**Other hazards**

The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity: < 10 %

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

This product does not contain any components that require disclosure according to OSHA Hazard Communication Standard 2012.

**SECTION 4. FIRST AID MEASURES**

General advice : No applicable data available.

**TPETPEFILMS KG**

Version 2.0

Revision Date 05/29/2015

Ref. 130000042744

Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.
Skin contact	: The material is not likely to be hazardous by skin contact, but cleaning the skin after use is advisable.
Eye contact	: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.
Ingestion	: No specific intervention is indicated. Consult a physician if necessary.
Most important symptoms/effects, acute and delayed	: No applicable data available.
Protection of first-aiders	: No applicable data available.
Notes to physician	: No applicable data available.

**SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media	: Water, Foam, Dry chemical, Carbon dioxide (CO <sub>2</sub> )
Unsuitable extinguishing media	: No applicable data available.
Specific hazards	: Combustible . Large molten masses may ignite spontaneously in air. Water quenching is good practice. Minimize the generation and accumulation of dust. Failure or malfunction of temperature control systems on processing equipment, such as extruders, may create explosion hazards. (see also section 10) Carbon monoxide, Carbon dioxide.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus and protective suit.
Further information	: Evacuate personnel and keep upwind of fire.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

**TPETPEFILMS KG**

Version 2.0

Revision Date 05/29/2015

Ref. 130000042744

- Safeguards (Personnel) : Spilled material is a slipping hazard.
- Environmental precautions : Do not discharge to streams, ponds, lakes or sewers.
- Spill Cleanup : Sweep up to prevent slipping hazard.
- Accidental Release Measures : No applicable data available.

**SECTION 7. HANDLING AND STORAGE**

- Handling (Personnel) : Provide appropriate exhaust ventilation at dryers, machinery and at places where dust or volatiles can be generated. Static charge may be generated upon processing and unwrapping. Static charges can accumulate and lead to a spark capable of starting a fire. Grounding and elimination of the static charge is recommended. Wash hands thoroughly after handling.
- Handling (Physical Aspects) : No applicable data available.
- Dust explosion class : No applicable data available.
- Storage : Store in a cool, dry place. Keep container closed to prevent contamination. Keep in an area equipped with sprinklers.
- Storage period : No applicable data available.
- Storage temperature : No applicable data available.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

- Engineering controls : General mechanical ventilation is normally adequate but use local exhaust where necessary to maintain exposures below acceptable limits. Use local exhaust to completely remove vapors and fumes liberated during hot processing from the work area. Use static controls. Static charge may be generated upon processing and unwrapping. Static charges can cause explosions in solvent and dust laden atmospheres. See Bulletin "Proper Use of Local Exhaust Ventilation During Processing of Plastics".
- Personal protective equipment  
Respiratory protection : A respiratory protection program that meets country requirements must be followed whenever workplace conditions warrant respirator use. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer. Consult the OSHA respiratory protection information located at

**TPETPEFILMS KG**

Version 2.0

Revision Date 05/29/2015

Ref. 130000042744

29CFR 1910.134. Use a positive pressure air supplied respirator if exposure levels are not known or there are any other circumstances where air purifying respirators may not provide adequate protection.

Hand protection : Additional protection: Protective gloves should be worn when the potential exists for prolonged or repeated skin contact.

Eye protection : Wear safety glasses with side shields. A full-face mask respirator provides protection from eye irritation.

**Exposure Guidelines  
Exposure Limit Values**

This product does not contain any exposure limits that require disclosure according to OSHA Hazard Communication Standard 2012.

**Non-Constituent(s)**

Dust (inhalable and respirable fraction)			
Permissible exposure limit:	(OSHA)	5 mg/m <sup>3</sup>	8 hr. TWA Respirable fraction.
Permissible exposure limit:	(OSHA)	15 mg/m <sup>3</sup>	8 hr. TWA Total dust.
TLV	(ACGIH)	3 mg/m <sup>3</sup>	TWA Respirable particles.
TLV	(ACGIH)	10 mg/m <sup>3</sup>	TWA Inhalable particles.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**
**Appearance**

Physical state : solid  
Form : film  
Color : No applicable data available.

Odor : none

Odor threshold : No applicable data available.

**TPETPEFILMS KG**

Version 2.0

Revision Date 05/29/2015

Ref. 130000042744

pH	: No applicable data available.
Melting point/freezing point	: Melting point/range > 130 °C (> 266 °F)
Boiling point/boiling range	: No applicable data available.
Flash point	: Not applicable
Evaporation rate	: No applicable data available.
Flammability (solid, gas)	: No applicable data available.
Upper explosion limit	: No applicable data available.
Lower explosion limit	: No applicable data available.
Vapour Pressure	: No applicable data available.
Vapour density	: No applicable data available.
Specific gravity (Relative density)	: > 1
Water solubility	: insoluble
Solubility(ies)	: No applicable data available.
Partition coefficient: n-octanol/water	: No applicable data available.
Auto-ignition temperature	: No applicable data available.
Decomposition temperature	: Thermal decomposition of the resin accelerates above temperature listed.  Decomposition can occur below the recommended processing temperature limit.  Decomposition is a function of both processing temperature and time at that temperature.
Viscosity, kinematic	: No applicable data available.

**TPETPEFILMS KG**

Version 2.0

Revision Date 05/29/2015

Ref. 130000042744

Viscosity, dynamic : No applicable data available.

**SECTION 10. STABILITY AND REACTIVITY**

- Reactivity : No applicable data available.
- Chemical stability : No applicable data available.
- Possibility of hazardous reactions : Polymerization will not occur.
- Conditions to avoid : Heating in air. Abnormally long processing time or high temperatures can produce irritating and toxic fumes.  
Decomposes on heating.  
At temperatures above the "conditions to avoid" temperature, thermal decomposition of the resin accelerates.  
Decomposition can occur below the recommended processing temperature limit.  
Decomposition is a function of both processing temperature and time at that temperature.
- Incompatible materials : Strong acids Strong bases, Strong oxidizing agents
- Hazardous decomposition products : Hazardous thermal decomposition products may include:, Organic acids, Aldehydes, Alcohols, Nitrogen oxides (NOx)  
Tetrahydrofuran , Carbon dioxide, Carbon monoxide, Acetic acid, 2-Methylpropene, Acetaldehyde, Formic acid...%, Acrolein, Propionaldehyde

**SECTION 11. TOXICOLOGICAL INFORMATION**

TPETPEFILMS KG

Further information : No data is available on the product itself. For additional toxicity data, write to the company address or call the non-emergency number shown in Section 1.

**Carcinogenicity**

The carcinogenicity classifications for this product and/or its ingredients have been determined according to HazCom 2012, Appendix A.6. The classifications may differ from those listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or those found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition).

This product does not contain any reportable carcinogens according to OSHA Hazard Communication

**TPETPEFILMS KG**

Version 2.0

Revision Date 05/29/2015

Ref. 130000042744

Standard 2012.

**SECTION 12. ECOLOGICAL INFORMATION**

Additional ecological information : No data is available on the product itself. Toxicity is expected to be low based on insolubility in water.

**SECTION 13. DISPOSAL CONSIDERATIONS**

Waste disposal methods - Product : Preferred options for disposal are recycling or incineration with energy recovery. The high fuel value of this product makes incineration very desirable for material that cannot be recycled. Treatment, storage, transportation, and disposal must be in accordance with applicable federal, state/provincial, and local regulations.

Contaminated packaging : No applicable data available.

**SECTION 14. TRANSPORT INFORMATION**

Not classified as dangerous in the meaning of transport regulations.

**SECTION 15. REGULATORY INFORMATION**

TSCA : In compliance with TSCA Inventory requirements for commercial purposes.

SARA 313 Regulated Chemical(s) : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

PA Right to Know Regulated Chemical(s) : Substances on the Pennsylvania Hazardous Substances List present at a concentration of 1% or more (0.01% for Special Hazardous Substances): Titanium dioxide

**TPETPEFILMS KG**

Version 2.0

Revision Date 05/29/2015

Ref. 130000042744

NJ Right to Know  
Regulated Chemical(s) : Substances on the New Jersey Workplace Hazardous Substance List present at a concentration of 1% or more (0.1% for substances identified as carcinogens, mutagens or teratogens): Titanium dioxide

California Prop. 65 : WARNING! This product contains a chemical or chemicals known to the State of California to cause cancer.  
WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

**SECTION 16. OTHER INFORMATION**

Read the product information datasheet for this product or the molding guide for this resin family. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling.

Revision Date : 05/29/2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Significant change from previous version is denoted with a double bar.