

Cyclohexane

Sales Specification

Property	Units	Value	Method
Purity, minimum	Weight %	99.90	ASTM D7266
Methylcyclopentane, maximum	mg/kg	150	ASTM D7266
Methylcyclohexane, maximum	mg/kg	200	ASTM D7266
Sulfur , maximum	mg/kg	1	ASTM D7183
Color , maximum	Pt-Co Scale	10	ASTM D1209
Distillation range including the temperature 80.7°C at 101.3 kPa (760 mm Hg) pressure	°C	1 - 1.1	ASTM 1078
Benzene, maximum	mg/kg	50	ASTM D7266

Available in ocean-going vessels (world-wide), barges (regionally), and tank truck or rail car (North America)

MSDS #895

Revision Date November 2012

Another quality product from



Before using this product, the user is advised and cautioned to make its own determination and assessment of the safety and suitability of the product for the specific use in question and is further advised against relying on the information contained herein as it may relate to any specific use or application. It is the ultimate responsibility of the user to ensure that the product is suited and the information is applicable to the user's specific application. Chevron Phillips Chemical Company LP does not make, and expressly disclaims, all warranties, including warranties of merchantability or fitness for a particular purpose, regardless of whether oral or written, express or implied, or allegedly arising from any usage of any trade or from any course of dealing in connection with the use of the information contained herein or the product itself. The user expressly assumes all risk and liability, whether based in contract, tort or otherwise, in connection with the use of the information contained herein or the product itself. Further, information contained herein is given without reference to any intellectual property issues, as well as federal, state or local laws which may be encountered in the use thereof. Such questions should be investigated by the user.