

Greenbase™ Drispac® Polymer



Greenbase™ Drispac® Polymer is a high performance Polyanionic cellulose, suspended in an in a glycol ether base fluid. Greenbase™ Drispac® Polymer suspension is uniquely stable, easily handled and useful in both oilfield and non-oilfield applications.

Drilling Specialties' Greenbase™ Drispac® Polymer will not experience the separation, evident in other suspension products. It is not subject to settling or fluid separation under normal storage or transport conditions. Starting with a glycol ether and utilizing our unique suspension technology, we eliminate settling of the Drispac® Polymer particles while the product remains fully pourable. The long-term stability of the suspension provides for consistent, reliable product properties at your field locations any place in the world.

Packaging the Drispac® Polymer as a liquid suspension allows for accurate metering, and provides complete dispersion of the particles in your treating fluids before hydration begins. This quality eliminates problems of polymer lumping and incomplete viscosity development, even when facing adverse field mixing conditions.

Advantages

- Easy to handle and mixes well in low shear environments
- Meets Oil & Grease test requirements for the Gulf of Mexico
- Stable suspension provides reliable properties
- Highly cost effective
- Controls fluid loss
- Produces a thin, slick, tough filter cake
- Retards drilled solids build up
- Promotes faster penetration rates
- Performs well in fresh water, sea water, brine and saturated salt environments
- Improves mud stability by increasing resistance of clay muds to contamination
- Reduces clean up time
- Eliminates need for preservatives: non-fermenting
- Freeze/thaw cycle does not affect stability or performance of the product

Benefits

- Friction reducer and lubricant for horizontal drilling
- Superior carrying capacity

Technical Information

- Activity 3.1 lb/gal 35.3% active polymer by weight
- Flash Point 220 °F (105 °C)
- Pour Point -35 °F
- Density 9.1 lb/gal
- Color Cream

Cost

The performance characteristics of Drispac® Polymer are well established in oilfield and non oil field applications. As a liquid suspension this polymer disperses in water and develops viscosity very quickly.

Mud Types

Most water-based mud formulations

Mixing Requirements

Mix through a mud hopper or may be added directly to a well agitated pit.

Handling

For specific instruction on handling, refer to the MSDS

Packaging

Greenbase™ Drispac® Polymer is packaged in disposable pails, containing a net weight of 44 lbs of product or (15.53 lbs of Drispac® Polymer) There are 3.1 pounds of Drispac® Polymer in each gallon of Greenbase™ Drispac® Polymer. There are 32 pails per pallet.

Before using this product, the user is advised and cautioned to make its own determination and assessment of the safety and suitability of the product for the specific use in question and is further advised against relying on the information contained herein as it may relate to any specific use or application. It is the ultimate responsibility of the user to ensure that the product is suited and the information is applicable to the user's specific application. Drilling Specialties Company does not make, and expressly disclaims, all warranties, including warranties of merchantability or fitness for a particular purpose, regardless of whether oral or written, express or implied, or allegedly arising from any usage of any trade or from any course of dealing in connection with the use of the information contained herein or the product itself. The user expressly assumes all risk and liability, whether based in contract, tort or otherwise, in connection with the use of the information contained herein or the product itself. Further, information contained herein is given without reference to any intellectual property issues, as well as federal, state or local laws which may be encountered in the use thereof. Such questions should be investigated by the user.

Greenbase™ Drispac® Polymer



Application	Normal Use Range
Fluid loss control	0.16 to 1.6 gal/BBL
Inhibition/encapsulation	0.50 to 1.6 gal/BBL
Improve filter cake	0.40 gal/BBL
Improved & stabilized rheology	0.40 to 0.8 gal/BBL
Reduced stuck pipe frequency	0.40 to 0.8 gal/BBL
Improve hole cleaning	0.15 to 0.94 gal/BBL

Before using this product, the user is advised and cautioned to make its own determination and assessment of the safety and suitability of the product for the specific use in question and is further advised against relying on the information contained herein as it may relate to any specific use or application. It is the ultimate responsibility of the user to ensure that the product is suited and the information is applicable to the user's specific application. Drilling Specialties Company does not make, and expressly disclaims, all warranties, including warranties of merchantability or fitness for a particular purpose, regardless of whether oral or written, express or implied, or allegedly arising from any usage of any trade or from any course of dealing in connection with the use of the information contained herein or the product itself. The user expressly assumes all risk and liability, whether based in contract, tort or otherwise, in connection with the use of the information contained herein or the product itself. Further, information contained herein is given without reference to any intellectual property issues, as well as federal, state or local laws which may be encountered in the use thereof. Such questions should be investigated by the user.