

Wellman Engineering Resins

MATERIAL SAFETY DATA SHEET

Section 1. Chemical Product and Company Identification

Product Code(s)

MR259 22LH-xxx, MR409 22H-xxx, MR410 22H-xxx, MR1304-xxx, MR1660-xxx, MR1846-xxx, MRB40K004-xxx, MRT1487-xxx, WE1695

Product Name

WELLAMID™ Nylon

Manufacturer's Name

Wellman Engineering Resins

Emergency Telephone Number

800-821-6022

Address (Number, Street, City, State, and ZIP Code)

520 Kingsburg Highway

Telephone Number For Information

800-821-6022

P.O. Drawer 188

Date Prepared

March 3, 2009

Johnsonville, SC 29555-0188

Signature of Preparer (optional)

Section 2. Composition / Information on Ingredients

Component	CAS Registry #	wt. %	Exposure Limits	
			ACGIH TLV	OSHA PEL
Nylon (polyamide) polymer resin	32131-17-2	> 50	None Established	None Established
Inorganic Mineral	Not Applicable	25 – 45	10 mg/m ³	15 mg/m ³
Non-Regulated Toughener	Not Applicable	0 - 10	10 mg/m ³	15 mg/m ³
Non-Regulated Colorants, Stabilizers, Lubricants	Not Applicable	< 7	10 mg/m ³	15 mg/m ³
Carbon Black	1333-86-4	0 – 2	3.5 mg/m ³	3.5 mg/m ³
Titanium Dioxide	13463-67-7	0 – 3	10 mg/m ³	15 mg/m ³

Section 3. Hazards Identification

☆☆

EMERGENCY OVERVIEW

This product, as shipped is not considered hazardous as defined by the OSHA Hazard Communication Standard 29CFR 1910.12

Heating the polymer near or above its melting point (500°F), such as in injection molding operations, may release small amounts of organic decomposition products such as acrid fumes, toxic oxides of nitrogen, amine type fumes, ammonia.

Burning the polymer may produce the same decomposition products and dense smoke.

☆☆

POTENTIAL HEALTH EFFECTS:

EYE CONTACT :

As a solid the same as other nuisance dusts and powders.

Contact with viscous melt >500°F will cause severe burns, exposure to decomposition fumes may cause eye irritation.

INHALATION :

As a solid these nylon resins are not likely to be hazardous by inhalation.

Dizziness and nausea may occur if fumes from molten or burning polymer are inhaled.

Wellman Engineering Resins

SKIN CONTACT :

As a solid no effect, nylon resins are normally not irritating to the skin.
Contract with the viscous melt (>500°F) will cause severe skin and body burns.

INGESTION :

Solid nylon polymer presents no problem since it is insoluble in body fluids and biologically inert.

CHRONIC EFFECTS / CARCINOGENICITY:

Carbon black has been listed by IARC, NTP, OSHA or ACGIH as a 2B carcinogen.

TERATOLOGY (BIRTH DEFECT) INFORMATION :

REPRODUCTION INFORMATION :

Section 4. First Aid Measures

INHALATION :

The compound is not likely to be inhaled. Remove to fresh air and get medical attention if dizziness or nausea occurs.

EYE CONTACT :

No specific treatment for exposure under normal conditions. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation persists.
For contact with viscous melt get immediate medical attention.

SKIN CONTACT :

In case of contact, wash with plenty of soap and water. No specific treatment under normal conditions as nylon is not irritating to the skin.
For contact with viscous melt get immediate medical attention.

INGESTION :

No specific treatment since nylon polymer is biologically inert. Seek medical attentions and treat as symptomatic.

NOTE TO PHYSICIAN :

Wellman Engineering Resins

Section 5. Fire Fighting Measures

FLAMMABLE PROPERTIES:

FLASH POINT : Not determined for solid product. METHOD USED : NA

FLAMMABLE LIMITS

LFL : NA UFL: NA

EXTINGUISHING MEDIA :

Water Spray, Foam, Dry Chemical, CO₂

FIRE & EXPLOSION HAZARDS :

Accumulation of dust from grinding or machining operations could present a fire hazard

FIRE FIGHTING INSTRUCTIONS :

FIRE FIGHTING EQUIPMENT :

Wear self-contained breathing apparatus, MSHA/NIOSH approved (or equivalent) and full protective gear. Use water, foam, dry chemical, and/or CO₂.

Section 6. Accidental Release Measures

No protective measure required unless the polymer is involved in a fire situation. See section 5 above.

Spilled pellets are a slip hazard, contain and vacuum or sweep up material for salvage or disposal.

Section 7. Handling and Storage

Store material in original packing or suitable containers under dry conditions in accordance with good material handling practices.

Section 8. Exposure Controls / Personal Protection

ENGINEERING CONTROLS :

Good general ventilation should be sufficient to control normal airborne levels. Add local exhaust ventilation as needed.

RESPIRATORY PROTECTION :

None should be needed for normal working operations.

Wellman Engineering Resins

SKIN PROTECTION :

For solid materials normal good industrial hygiene practice to minimize skin contact.

For working with potential contact with molten material use heat resistant gloves with sleeve protection for arms and facemasks are recommended for eye and face protection.

EYE PROTECTION :

Wear safety glasses or goggles for all operations. When working with molten material ensure protection from splashes.

EXPOSURE GUIDELINE (S) :

As a nuisance dust: TLV 10 mg/m³
PEL 15 mg/m³

Section 9. Physical and chemical Properties

APPEARANCE :	Cylindrical Pellets	PHYSICAL STATE :	Solid
BOILING POINT :	Not applicable	SOLUBILITY IN WATER :	Insoluble
EVAPORATION RATE :	Not applicable	SPECIFIC GRAVITY :	>1.0
FREEZING POINT :	NA	VAPOR DENSITY :	NA
MELTING POINT :	250-260°C (480-500°F)	VAPOR PRESSURE :	NA
MOLECULAR WEIGHT :	NA	VISCOSITY :	NA
ODOR :	None	% VOLATILE :	0.5% max at 220°F
pH :	NA		

Section 10. Stability and Reactivity

CHEMICAL STABILITY :

Stable. Temperatures above 650°F will cause decomposition in the presence of oxygen.

INCOMPATIBILITY :

Incompatible or attacked by concentrated acids and oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS :

Organic decomposition products such as acrid fumes, toxic oxides of nitrogen, amine type fumes, ammonia, carbon monoxide, carbon dioxide.

HAZARDOUS POLYMERIZATION :

Will not occur.

Section 11. Toxicological Information

SKIN :

Nylon 66 resins are not a skin irritant in tests with animals.

INGESTION :

Single high dosage exposure can cause decreased body weight. Long-term exposure has caused no significant toxicological effects in test animals.

INHALATION :

Repeated inhalation exposure with animals caused changes in the lungs and kidneys.

CARCINOGENICITY :

Nylon 66 has not caused cancers in tests with animals.

Wellman Engineering Resins

Section 12. Ecological Information

ECOTOXICOLOGICAL INFORMATION :

Nylon polymer is non-toxic. Nylon pellets should be kept out of waterways and other locations where they could be ingested by wildlife and eventually fill the stomach of an animal.

DISTRIBUTION :

Pellets will flow and fall easily from damaged packages, leaks in air conveying lines and bulk containers such as silos.

CHEMICAL FATE INFORMATION :

Nylon polymer will not degrade biologically except at an infinitesimal rate and so will remain in place until cleaned up.

Wellman Engineering Resins

Section 13. Disposal Considerations

Treatment, storage, transportation and disposal must be in accordance with applicable Federal, State / Provincial and local regulations

Section 14. Transport Information (Not meant to be all inclusive)

D.O.T. SHIPPING NAME :	Not regulated
TECHNICAL SHIPPING NAME :	Canada
D.O.T. HAZARD CLASS :	TDG Class: Not regulated
U.N. / N.A. NUMBER :	
PRODUCT RQ (LBS) :	International Civil Aviation Organization
D.O.T. LABEL :	ICAO Class: Not regulated
D.O.T. PLACARD :	
FREIGHT CLASS BULK :	International Maritime Dangerous Goods
FREIGHT CLASS PACKAGE :	IMDG Class: Not Regulated
PRODUCT LABEL :	

Section 15. Regulatory Information (Not meant to be all inclusive – selected regulation represented)

OSHA STATUS :

TSCA STATUS: In compliance with TSCA Inventory requirements for commercial purposes.

CERCLA REPORTABLE QUANTITY :

SARA TITLE III:

SECTION 302 EXTREMELY HAZARDOUS SUBSTANCES :

SECTION 311/312 HAZARDOUS CATEGORIES :

SECTION 313 TOXIC CHEMICALS :

RCRA STATUS :

CALIFORNIA PROPOSITION 65 : In this product, carbon black is not supplied in the form regulated in California.

Section 16. Other Information

MSDS STATUS: