

Wellman Engineering Resins

MATERIAL SAFETY DATA SHEET

Section 1. Chemical Product and Company Identification

Product Code(s)

GF100-xxx, GF119-BK1, MRGF101-xxx, MRGF102-xxx, MRGF117-xxx

Product Name

WELLPET™ PET

Manufacturer's Name

Wellman Engineering Resins

Emergency Telephone Number

800-821-6022

Address (Number, Street, City, State, and ZIP Code)

520 Kingsburg Highway

Telephone Number For Information

800-821-6022

P.O. Drawer 188

Date Prepared

March 3, 2009

Johnsonville, SC 29555-0188

Signature of Preparer (optional)

Section 2. Composition / Information on Ingredients

Component	CAS Registry #	Wt. %	Exposure Limits	
			ACGIH TLV	OSHA PEL
Polyester resin	24938-04-3	> 40	None Established	None Established
Glass Reinforcement	65997-17-3	< 60	5 mg/m ³	15 mg/m ³
Inorganic Mineral	Not Applicable	< 20	10 mg/m ³	15 mg/m ³
Non-Regulated Additives, Colorants, Stabilizers, Lubricants	Not Applicable	< 15	10 mg/m ³	15 mg/m ³
Carbon Black	1333-86-4	0-1	3.5 mg/m ³	3.5 mg/m ³

Section 3. Hazards Identification

☆☆

EMERGENCY OVERVIEW

This product, as shipped is not considered hazardous as defined by the OSHA Hazard Communication Standard 29CFR 1910.12

Burning the polymer will produce irritating, toxic and/or flammable fumes and vapors.

☆☆

POTENTIAL HEALTH EFFECTS:

EYE CONTACT :

As a solid the same as other nuisance dusts and powders.

Contact with viscous melt (>480°F) will cause severe burns, exposure to decomposition fumes may cause eye irritation.

INHALATION :

As a solid these PET resins are not likely to be hazardous by inhalation.

Dizziness and nausea may occur if fumes from molten or burning polymer are inhaled.

Wellman Engineering Resins

MATERIAL SAFETY DATA SHEET

SKIN CONTACT :

As a solid no effect, PET resins are normally not irritating to the skin.
Contact with the viscous melt (>480°F) will cause severe skin and body burns.

INGESTION :

Solid PET polymer presents no problem since it is insoluble in body fluids and biologically inert.

CHRONIC EFFECTS / CARCINOGENICITY:

None of the components in these materials at greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as carcinogens.

TERATOLOGY (BIRTH DEFECT) INFORMATION :

REPRODUCTION INFORMATION :

Section 4. First Aid Measures

INHALATION :

Remove to fresh air and get medical attention if dizziness or nausea occurs.

EYE CONTACT :

Flush eyes with running water. Get medical attention if irritation develops or persists.
For contact with viscous melt get immediate medical attention.

SKIN CONTACT :

No specific treatment under normal conditions as PET is not irritating to the skin.
For contact with viscous melt get immediate medical attention.

INGESTION :

No specific treatment since PET polymer is biologically inert. Seek medical attentions and treat as symptomatic.

NOTE TO PHYSICIAN :

Wellman Engineering Resins

MATERIAL SAFETY DATA SHEET

Section 5. Fire Fighting Measures

FLAMMABLE PROPERTIES:

FLASH POINT : Not determined for solid product.

METHOD USED : NA

FLAMMABLE LIMITS

LFL : NA

UFL: NA

EXTINGUISHING MEDIA :

Water Spray, Foam, Dry Chemical, CO₂

FIRE & EXPLOSION HAZARDS :

Accumulation of dust from grinding or machining operations could present a fire hazard

FIRE FIGHTING INSTRUCTIONS :

FIRE FIGHTING EQUIPMENT :

Wear self-contained breathing apparatus, MSHA/NIOSH approved (or equivalent) and full protective gear.

Section 6. Accidental Release Measures

No protective measure required unless the polymer is involved in a fire situation. See section 5 above.

Spilled pellets are a slip hazard, contain and vacuum or sweep up material for salvage or disposal.

Section 7. Handling and Storage

Store material in original packing or suitable containers under dry conditions in accordance with good material handling practices.

Section 8. Exposure Controls / Personal Protection

ENGINEERING CONTROLS :

Good general ventilation should be sufficient to control normal airborne levels. Local exhaust ventilation as needed.

RESPIRATORY PROTECTION :

None should be needed for normal working operations.

Wellman Engineering Resins

MATERIAL SAFETY DATA SHEET

Forms published by ChemSW (707)864-0845

SKIN PROTECTION :

For solid materials normal good industrial hygiene practice to minimize skin contact.
For working with potential contact with molten material use heat resistant gloves with sleeve protection for arms and facemasks are recommended for eye and face protection.

EYE PROTECTION :

Wear safety glasses or goggles for all operations. When working with molten material ensure protection from splashes.

EXPOSURE GUIDELINE (S) :

As a nuisance dust: TLV 10 mg/m³
PEL 15 mg/m³

Section 9. Physical and chemical Properties

APPEARANCE :	Cylindrical Pellets	PHYSICAL STATE :	Solid
BOILING POINT :	Not applicable	SOLUBILITY IN WATER :	Insoluble
EVAPORATION RATE :	Not applicable	SPECIFIC GRAVITY :	
FREEZING POINT :	NA	VAPOR DENSITY :	NA
MELTING POINT :	480°F	VAPOR PRESSURE :	NA
MOLECULAR WEIGHT :	NA	VISCOSITY :	NA
ODOR :	Slight	% VOLATILE :	Not Determined
pH :			

Section 10. Stability and Reactivity

CHEMICAL STABILITY :

Stable. Avoid open flame and extreme temperatures.

INCOMPATIBILITY :

Can react with strong acids, strong bases and oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS :

Organic decomposition products such as carbon monoxide, and carbon dioxide. The specific materials generated will vary depending physical and thermal variables.

HAZARDOUS POLYMERIZATION :

Will not occur.

Section 11. Toxicological Information

EYE :

SKIN :

INGESTION :

INHALATION :

Wellman Engineering Resins

MATERIAL SAFETY DATA SHEET

SUBCHRONIC:

CHRONIC / CARCINOGENICITY :

TERATOLOGY :

REPRODUCTION :

MUTAGENICITY :

SENSITIZATION :

Section 12. Ecological Information

ECOTOXICOLOGICAL INFORMATION :

PET polymer is non toxic. PET pellets should be kept out of waterways and other locations where they could be ingested by wildlife and eventually fill the stomach of an animal.

DISTRIBUTION :

Pellets will flow and fall easily from damaged packages, leaks in air conveying lines and bulk containers such as silos.

CHEMICAL FATE INFORMATION :

PET polymer will not degrade biologically except at an infinitesimal rate and so will remain in place until cleaned up.

Wellman Engineering Resins

MATERIAL SAFETY DATA SHEET

Section 13. Disposal Considerations

Treatment, storage, transportation and disposal must be in accordance with applicable Federal, State / Provincial and local regulations

Section 14. Transport Information (Not meant to be all inclusive)

D.O.T. SHIPPING NAME :	Not regulated
TECHNICAL SHIPPING NAME :	
D.O.T. HAZARD CLASS :	TDG Class: Not regulated
U.N. / N.A. NUMBER :	
PRODUCT RQ (LBS) :	International Civil Aviation Organization
D.O.T. LABEL :	ICAO Class: Not regulated
D.O.T. PLACARD :	
FREIGHT CLASS BULK :	International Maritime Dangerous Goods
FREIGHT CLASS PACKAGE :	IMDG Class: Not Regulated
PRODUCT LABEL :	

Section 15. Regulatory Information (Not meant to be all inclusive – selected regulation represented)

OSHA STATUS : No

TSCA STATUS : All components listed on inventory.

CERCLA REPORTABLE QUANTITY :

SARA TITLE III:

SECTION 302 EXTREMELY HAZARDOUS SUBSTANCES :

SECTION 311/312 HAZARDOUS CATEGORIES : None

SECTION 313 TOXIC CHEMICALS : No

RCRA STATUS :

CALIFORNIA PROPOSITION 65 :

Section 16. Other Information

MSDS STATUS: