

PLATAMID®

TECHNICAL DATA SHEET

PLATAMID® HX 2667 POWDER

COPOLYAMIDE POWDER

PLATAMID® HX 2667 POWDER is a thermoplastic copolyamide hot melt adhesive. This medium melt viscosity grade is suitable for manufacturing of of of fusible interlinings. It offers an excellent laundry resistance up to 60°C and an excellent resistance to all kind of steam treatment.

This product is available in different grain sizes:

- PA80 (0-80 µm paste dot)
- PTA 170/20 (0-170 µm power dot)
- PTA 170 (80-170 µm double dot)

TYPE

PA*

MAIN APPLICATIONS

- Adhesives - Apparel/Interlining

DELIVERY FORM

- Powder

TRANSFORMATION PROCESSES

- Scattering, paste, double dot

RHEOLOGICAL PROPERTIES

PROPERTIES	VALUE	UNIT	TEST STANDARD
Melt volume flow rate (MVR), 160°C / 2.16 kg (320°F / 4.4 lb)	30	cm ³ /10min	ISO 1133

THERMAL PROPERTIES

PROPERTIES	VALUE	UNIT	TEST STANDARD
Melting temperature, 23°C (73°F)	128	°C	ISO 11357-1/-3

PACKAGING

Available packaging:

- 20 kg / 44 lb bags

SHELF LIFE

Two years from the date of delivery, when stored properly (sealed bags, appropriate moisture, UV protection and temperature). For any use above this limit, please refer to our technical services.