

# PLATAMID® M 1425 PELLETS

## Platamid® M 1425 Pellets

Copolyamide Hot Melt Adhesive / Extrusion Applications

**Platamid® M 1425 Pellets** is a standard thermoplastic copolyamide hot melt adhesive available in pellet form and is used in solvent based processes.

**Platamid® M 1425 Pellets** is a semi-crystalized copolyamide product which has been developed for use in the wire coating industry.

PROPERTIES	DRY / COND	UNIT	TEST STANDARD
<b>RHEOLOGICAL PROPERTIES</b>			
Melt Volume-Flow Rate	21 / *	cm <sup>3</sup> /10min	ISO 1133
Temperature	230 / *	°C	-
	446 / *	°F	
Load	2.16 / *	kg	-
	4.76 / *	lb	
<b>THERMAL PROPERTIES</b>			
Melting Temperature, 10°C/min	150 / *	°C	ISO 11357-1/-3

## AVAILABLE GRADES

This product is available:

- undried (M 1425 F)

## PACKAGING

- Platamid® M 1425 F is delivered in 25 kg sealed bags.

This grade is ready to be processed.

## SHELF LIFE

Two years from the date of delivery. For any use above this limit, please refer to our technical services.

<b>PROCESSING</b>	
Film Extrusion	
<b>DELIVERY FORM</b>	
Pellets	
<b>SPECIAL CHARACTERISTICS</b>	
Adhesive	
<b>REGIONAL AVAILABILITY</b>	
North America, Europe, Asia Pacific, South and Central America, Near East/Africa	