

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## DryFilm RA/IPA

Version 7.0      Revision Date: 2025/06/18      SDS Number: 1328667-00048      Date of last issue: 2024/10/09  
Date of first issue: 2017/02/27

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : DryFilm RA/IPA

SDS-Identcode : 130000001461

#### Manufacturer or supplier's details

Company : The Chemours Chemical (Shanghai) Co., Ltd.

Address : 9F, SCG Parkside, 868 Yinghua Road, Pudong New District  
201204, Shanghai, China

Telephone : 86 400 8056 528

Emergency telephone number : 86 532 8388 9090

E-mail address : SDS.ChinaPSR@chemours.com

Telefax : 86 21 2612 0862

#### Recommended use of the chemical and restrictions on use

Recommended use : Dry lubricant

Restrictions on use : For industrial use only.  
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

### 2. HAZARDS IDENTIFICATION

#### Emergency Overview

Appearance : liquid  
Colour : translucent, white to off-white  
Odour : alcohol-like

Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness.

#### GHS Classification

Flammable liquids : Category 2  
Serious eye damage/eye irritation : Category 2A



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## DryFilm RA/PA

Version 7.0      Revision Date: 2025/06/18      SDS Number: 1328667-00048      Date of last issue: 2024/10/09  
Date of first issue: 2017/02/27

Specific target organ toxicity - single exposure : Category 3

### GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

Precautionary statements :

#### Prevention:

P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P261 Avoid breathing mist or vapours.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

#### Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P304 + P340 + P319 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical help if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P317 If eye irritation persists: Get medical help.

#### Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

#### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## DryFilm RA/IPA

Version 7.0      Revision Date: 2025/06/18      SDS Number: 1328667-00048      Date of last issue: 2024/10/09  
Date of first issue: 2017/02/27

### Physical and chemical hazards

Highly flammable liquid and vapour.

### Health hazards

Causes serious eye irritation. May cause drowsiness or dizziness.

### Environmental hazards

Not classified based on available information.

### Additional Labelling

|| The following percentage of the mixture consists of ingredient(s) with unknown hazards to the aquatic environment: 18 %

### Other hazards which do not result in classification

The thermal decomposition vapours of fluorinated plastics may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco.  
Vapours may form explosive mixture with air.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
Propan-2-ol	67-63-0	>= 70 -< 90

## 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.  
Remove contaminated clothing and shoes.  
Get medical attention if symptoms occur.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and : Inhalation may provoke the following symptoms:  
Polymer fume fever



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## DryFilm RA/PA

Version	Revision Date:	SDS Number:	Date of last issue: 2024/10/09
7.0	2025/06/18	1328667-00048	Date of first issue: 2017/02/27

- tive equipment and emergency procedures
- Ventilate the area.  
Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g. by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapours/mists with a water spray jet.  
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

## 7. HANDLING AND STORAGE

### Handling

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.  
Use explosion-proof electrical, ventilating and lighting equipment.
- Advice on safe handling : Avoid breathing mist or vapours.  
Do not swallow.  
Do not get in eyes.  
Avoid prolonged or repeated contact with skin.  
Wash skin thoroughly after handling.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Non-sparking tools should be used.



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## DryFilm RA/PA

Version 7.0      Revision Date: 2025/06/18      SDS Number: 1328667-00048      Date of last issue: 2024/10/09  
Date of first issue: 2017/02/27

Keep container tightly closed.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.

Do not breathe decomposition products.

Avoidance of contact : Oxidizing agents

### Storage

Conditions for safe storage : Keep in properly labelled containers.  
Store locked up.  
Keep tightly closed.  
Keep in a cool, well-ventilated place.  
Store in accordance with the particular national regulations.  
Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:  
Self-reactive substances and mixtures  
Organic peroxides  
Oxidizing agents  
Flammable gases  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Poisonous gases  
Explosives

Packaging material : Unsuitable material: None known.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Propan-2-ol	67-63-0	PC-TWA	350 mg/m <sup>3</sup>	CN OEL
		PC-STEL	700 mg/m <sup>3</sup>	CN OEL
		TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH

### Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrofluoric acid	7664-39-3	MAC	2 mg/m <sup>3</sup>	CN OEL

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## DryFilm RA/IPA

Version 7.0      Revision Date: 2025/06/18      SDS Number: 1328667-00048      Date of last issue: 2024/10/09  
Date of first issue: 2017/02/27

			(Fluorine)	
		TWA	0.5 ppm (Fluorine)	ACGIH
		C	2 ppm (Fluorine)	ACGIH
Carbonyl difluoride	353-50-4	PC-TWA	5 mg/m3	CN OEL
		PC-STEL	10 mg/m3	CN OEL
		TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
Carbon dioxide	124-38-9	PC-TWA	9,000 mg/m3	CN OEL
		PC-STEL	18,000 mg/m3	CN OEL
		TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
Carbon monoxide	630-08-0	PC-TWA	20 mg/m3	CN OEL
		PC-STEL	30 mg/m3	CN OEL
		MAC	20 mg/m3	CN OEL
		MAC	15 mg/m3	CN OEL
		TWA	25 ppm	ACGIH

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Propan-2-ol	67-63-0	Acetone	Urine	End of shift at end of work-week	40 mg/l	ACGIH BEI

**Engineering measures** : Processing may form hazardous compounds (see section 10).  
Minimize workplace exposure concentrations.  
If sufficient ventilation is unavailable, use with local exhaust ventilation.  
Use explosion-proof electrical, ventilating and lighting equipment.

### Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates, acidic gas/vapour and organic vapour type

Eye/face protection : Wear the following personal protective equipment:  
Safety goggles



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## DryFilm RA/PA

Version	Revision Date:	SDS Number:	Date of last issue: 2024/10/09
7.0	2025/06/18	1328667-00048	Date of first issue: 2017/02/27

**Skin and body protection** : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

### Hand protection

**Material** : Chemical-resistant gloves

**Remarks** : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Take note that the product is flammable, which may impact the selection of hand protection. Wash hands before breaks and at the end of workday.

**Hygiene measures** : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** : liquid

**Colour** : translucent, white to off-white

**Odour** : alcohol-like

**Odour Threshold** : No data available

**pH** : 4 - 7

**Melting point/freezing point** : -89 °C

**Initial boiling point and boiling range** : 82 °C



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## DryFilm RA/PA

Version	Revision Date:	SDS Number:	Date of last issue: 2024/10/09
7.0	2025/06/18	1328667-00048	Date of first issue: 2017/02/27

---

Flash point	:	12 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Ignitable (see flash point)
Upper explosion limit / Upper flammability limit	:	12.0 %(V)
Lower explosion limit / Lower flammability limit	:	2.0 %(V)
Vapour pressure	:	44 hPa (20 °C)
Relative vapour density	:	2.07 (Air = 1.0)
Relative density	:	0.96 (22 °C)
Solubility(ies) Water solubility	:	partly soluble
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	399 °C
Decomposition temperature	:	300 °C
Viscosity Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle characteristics Particle size	:	Not applicable

---

### 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## DryFilm RA/IPA

Version 7.0      Revision Date: 2025/06/18      SDS Number: 1328667-00048      Date of last issue: 2024/10/09  
Date of first issue: 2017/02/27

Possibility of hazardous reactions : Highly flammable liquid and vapour.  
Vapours may form explosive mixture with air.  
Can react with strong oxidizing agents.  
Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

### Hazardous decomposition products

Thermal decomposition : Hydrofluoric acid  
Carbonyl difluoride  
Carbon dioxide  
Carbon monoxide

## 11. TOXICOLOGICAL INFORMATION

Exposure routes : Inhalation  
Skin contact  
Ingestion  
Eye contact

### Acute toxicity

Not classified based on available information.

### Components:

#### Propan-2-ol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Acute inhalation toxicity : LC50 (Rat): > 25 mg/l  
Exposure time: 6 h  
Test atmosphere: vapour  
Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

### Skin corrosion/irritation

Not classified based on available information.

### Components:

#### Propan-2-ol:

Species : Rabbit  
Result : No skin irritation

### Serious eye damage/eye irritation

Causes serious eye irritation.

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## DryFilm RA/IPA

Version 7.0      Revision Date: 2025/06/18      SDS Number: 1328667-00048      Date of last issue: 2024/10/09  
Date of first issue: 2017/02/27

### Components:

#### Propan-2-ol:

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

### Components:

#### Propan-2-ol:

Test Type : Buehler Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

### Germ cell mutagenicity

Not classified based on available information.

### Components:

#### Propan-2-ol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative  
  
Test Type: In vitro mammalian cell gene mutation test  
Result: negative  
  
Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Result: negative

### Carcinogenicity

Not classified based on available information.

### Components:

#### Propan-2-ol:

Species : Rat  
Application Route : inhalation (vapour)  
Exposure time : 104 weeks  
Method : OECD Test Guideline 451



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## DryFilm RA/IPA

Version 7.0      Revision Date: 2025/06/18      SDS Number: 1328667-00048      Date of last issue: 2024/10/09  
Date of first issue: 2017/02/27

||Result : negative

### Reproductive toxicity

Not classified based on available information.

### Components:

#### Propan-2-ol:

||Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Result: negative

||Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative

### STOT - single exposure

May cause drowsiness or dizziness.

### Components:

#### Propan-2-ol:

||Assessment : May cause drowsiness or dizziness.

### STOT - repeated exposure

Not classified based on available information.

### Repeated dose toxicity

### Components:

#### Propan-2-ol:

||Species : Rat  
NOAEL : 12.5 mg/l  
Application Route : inhalation (vapour)  
Exposure time : 104 Weeks

### Aspiration toxicity

Not classified based on available information.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

### Components:

#### Propan-2-ol:

||Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 9,640 mg/l



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## DryFilm RA/IPA

Version 7.0      Revision Date: 2025/06/18      SDS Number: 1328667-00048      Date of last issue: 2024/10/09  
Date of first issue: 2017/02/27

Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 24 h

Toxicity to microorganisms : EC50 (Pseudomonas putida): > 1,050 mg/l  
Exposure time: 16 h

### Persistence and degradability

#### Components:

##### Propan-2-ol:

Biodegradability : Result: rapidly degradable

BOD/COD : BOD: 1,19 (BOD5)  
COD: 2,23  
BOD/COD: 53 %

### Bioaccumulative potential

#### Components:

##### Propan-2-ol:

Partition coefficient: n-octanol/water : log Pow: 0.05

### Mobility in soil

No data available

### Other adverse effects

No data available

## 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Do not dispose of waste into sewer.  
Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## DryFilm RA/IPA

Version	Revision Date:	SDS Number:	Date of last issue: 2024/10/09
7.0	2025/06/18	1328667-00048	Date of first issue: 2017/02/27

### 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

UN number : UN 1219  
Proper shipping name : ISOPROPANOL SOLUTION  
Class : 3  
Packing group : II  
Labels : 3  
Environmentally hazardous : no

##### IATA-DGR

UN/ID No. : UN 1219  
Proper shipping name : Isopropanol solution  
Class : 3  
Packing group : II  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 364  
Packing instruction (passenger aircraft) : 353

##### IMDG-Code

UN number : UN 1219  
Proper shipping name : ISOPROPANOL SOLUTION  
  
Class : 3  
Packing group : II  
Labels : 3  
EmS Code : F-E, S-D  
Marine pollutant : no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### National Regulations

##### GB 6944/12268

UN number : UN 1219  
Proper shipping name : ISOPROPANOL SOLUTION  
Class : 3  
Packing group : II  
Labels : 3  
Marine pollutant : no

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## DryFilm RA/IPA

Version 7.0      Revision Date: 2025/06/18      SDS Number: 1328667-00048      Date of last issue: 2024/10/09  
Date of first issue: 2017/02/27

### 15. REGULATORY INFORMATION

#### National regulatory information

##### Law on the Prevention and Control of Occupational Diseases

##### Regulations on Safety Management of Hazardous Chemicals

Catalogue of Hazardous Chemicals : Listed

Identification of Major Hazard Installations for Hazardous Chemicals (GB 18218)

No. / Code	Chemical name / Category	Threshold quantity
W5.3	Flammable liquids	1,000 t

Hazardous Chemicals for Priority Management under SAWS : Not listed

Catalogue of Specially Controlled Hazardous Chemicals : Listed

List of Explosive Precursors : Not listed

##### Regulations on Labour Protection in Workplaces where Toxic Substances are Used

Catalogue of Highly Toxic Chemicals : Not listed

##### Regulation of Environmental Management on the First Import of Chemicals and the Import and Export of Toxic Chemicals

China Severely Restricted Toxic Chemicals for Import and Export : Not listed

##### Regulation on the Administration of Precursor Chemicals

Catalogue and Classification of Precursor Chemicals : Not listed

##### Yangtze River Protection Law

This product does not contain any dangerous chemicals prohibited for inland river transport.

##### Regulations of Ozone Depleting Substances Management

List of Controlled Ozone Depleting Substances Import and Export : Not listed

List of Controlled Ozone Depleting Substances : Listed

##### Environmental Protection Law

List of Priority Controlled Chemicals : Not listed

List of Key Controlled New Pollutants : Not listed

Montreal Protocol : Reaction mass of (3R,4R)-1,1,1,2,2,3,4,5,5,5-decafluoropentane and (3S,4S)-1,1,1,2,2,3,4,5,5,5-



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## DryFilm RA/PA

Version 7.0      Revision Date: 2025/06/18      SDS Number: 1328667-00048      Date of last issue: 2024/10/09  
Date of first issue: 2017/02/27

decafluoropentane

### 16. OTHER INFORMATION

Revision Date : 2025/06/18

Other information : Chemours™ and the Chemours Logo are trademarks of The Chemours Company.  
Before use read Chemours safety information.  
For further information contact the local Chemours office or nominated distributors.

#### Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Date format : yyyy/mm/dd

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)  
CN OEL : Occupational exposure limits for hazardous agents in the workplace - Chemical hazardous agents.

ACGIH / TWA : 8-hour, time-weighted average  
ACGIH / STEL : Short-term exposure limit  
ACGIH / C : Ceiling limit  
CN OEL / PC-TWA : Permissible concentration - time weighted average  
CN OEL / PC-STEL : Permissible concentration - short term exposure limit  
CN OEL / MAC : Maximum allowable concentration

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Or-

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## DryFilm RA/IPA

Version	Revision Date:	SDS Number:	Date of last issue: 2024/10/09
7.0	2025/06/18	1328667-00048	Date of first issue: 2017/02/27

---

ganisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CN / EN

