

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Freon™ 408A (R-408A) Refrigerant

Version 8.0      Revision Date: 2025/10/19      SDS Number: 1336385-00049      Date of last issue: 2025/05/27  
Date of first issue: 2017/02/27

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Freon™ 408A (R-408A) Refrigerant  
SDS-Identcode : 130000050988

#### Manufacturer or supplier's details

Company : The Chemours Chemical (Shanghai) Co., Ltd.  
Address : 9F, SCG Parkside, 868 Yinghua Road, Pudong New District  
201204, Shanghai, China  
Telephone : 86 400 8056 528  
Emergency telephone number : 86 532 8388 9090  
E-mail address : SDS.ChinaPSR@chemours.com  
Telefax : 86 21 2612 0862

#### Recommended use of the chemical and restrictions on use

Recommended use : Refrigerant  
Restrictions on use : For professional users only.

### 2. HAZARDS IDENTIFICATION

#### Emergency Overview

**Appearance** : Liquefied gas  
**Colour** : clear, colourless  
**Odour** : slight, ether-like

Contains gas under pressure; may explode if heated. Causes eye irritation. May cause drowsiness or dizziness. May damage fertility or the unborn child. Harms public health and the environment by destroying ozone in the upper atmosphere.

#### GHS Classification

Gases under pressure : Liquefied gas  
Serious eye damage/eye irritation : Category 2B  
Reproductive toxicity : Category 1B  
Specific target organ toxicity - single exposure : Category 3  
Hazardous to the ozone layer : Category 1

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Freon™ 408A (R-408A) Refrigerant

Version  
8.0

Revision Date:  
2025/10/19

SDS Number:  
1336385-00049

Date of last issue: 2025/05/27  
Date of first issue: 2017/02/27

### GHS label elements

Hazard pictograms



Signal word

: Danger

Hazard statements

: H280 Contains gas under pressure; may explode if heated.  
H320 Causes eye irritation.  
H336 May cause drowsiness or dizziness.  
H360 May damage fertility or the unborn child.  
H420 Harms public health and the environment by destroying ozone in the upper atmosphere.

Precautionary statements

: **Prevention:**

P203 Obtain, read and follow all safety instructions before use.  
P261 Avoid breathing gas.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

**Response:**

P304 + P340 + P319 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical help if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P318 IF exposed or concerned, get medical advice.  
P337 + P317 If eye irritation persists: Get medical help.

**Storage:**

P405 Store locked up.  
P410 + P403 Protect from sunlight. Store in a well-ventilated place.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.  
P502 Refer to manufacturer or supplier for information on recovery or recycling.

### Physical and chemical hazards

Contains gas under pressure; may explode if heated.

### Health hazards

Causes eye irritation. May damage fertility or the unborn child. May cause drowsiness or dizziness.



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Freon™ 408A (R-408A) Refrigerant

Version 8.0      Revision Date: 2025/10/19      SDS Number: 1336385-00049      Date of last issue: 2025/05/27  
Date of first issue: 2017/02/27

### Environmental hazards

Harms public health and the environment by destroying ozone in the upper atmosphere.

### Other hazards which do not result in classification

Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.

Misuse or intentional inhalation abuse may cause death without warning symptoms, due to cardiac effects.

Rapid evaporation of the product may cause frostbite.

May displace oxygen and cause rapid suffocation.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
Chlorodifluoromethane	75-45-6	47
1,1,1-Trifluoroethane#	420-46-2	46
Pentafluoroethane#	354-33-6	7

# Voluntarily-disclosed substance

## 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
If not breathing, give artificial respiration.  
If breathing is difficult, give oxygen.  
Get medical attention immediately.
- In case of skin contact : Thaw frosted parts with lukewarm water. Do not rub affected area.  
Get medical attention immediately.
- In case of eye contact : Get medical attention immediately.
- If swallowed : Ingestion is not considered a potential route of exposure.
- Most important symptoms and effects, both acute and delayed : May cause cardiac arrhythmia.  
Other symptoms potentially related to misuse or inhalation abuse are  
Cardiac sensitisation  
Anaesthetic effects  
Light-headedness  
Dizziness  
confusion  
Lack of coordination  
Drowsiness  
Unconsciousness

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Freon™ 408A (R-408A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 2025/05/27
8.0	2025/10/19	1336385-00049	Date of first issue: 2017/02/27

Causes eye irritation.  
May cause drowsiness or dizziness.  
May damage fertility or the unborn child.  
Gas reduces oxygen available for breathing.  
Contact with liquid or refrigerated gas can cause cold burns and frostbite.

Protection of first-aiders : No special precautions are necessary for first aid responders.

Notes to physician : Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, that may be used in situations of emergency life support should be used with special caution.

### 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Not applicable  
Will not burn

Unsuitable extinguishing media : Not applicable  
Will not burn

Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Carbon oxides  
Fluorine compounds

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Fight fire remotely due to the risk of explosion.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.  
Use personal protective equipment.

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.  
Avoid skin contact with leaking liquid (danger of frostbite).  
Ventilate the area.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Freon™ 408A (R-408A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue:
8.0	2025/10/19	1336385-00049	2025/05/27
			Date of first issue: 2017/02/27

- Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Retain and dispose of contaminated wash water.
- Methods and materials for containment and cleaning up : Ventilate the area.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### 7. HANDLING AND STORAGE

#### Handling

- Technical measures : Use equipment rated for cylinder pressure. Use a backflow preventative device in piping. Close valve after each use and when empty.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Avoid breathing gas.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Wear cold insulating gloves/ face shield/ eye protection.  
Valve protection caps and valve outlet threaded plugs must remain in place unless container is secured with valve outlet piped to use point.  
Prevent backflow into the gas tank.  
Use a check valve or trap in the discharge line to prevent hazardous back flow into the cylinder.  
Use a pressure reducing regulator when connecting cylinder to lower pressure (<3000 psig) piping or systems.  
Close valve after each use and when empty. Do NOT change or force fit connections.  
Prevent the intrusion of water into the gas tank.  
Never attempt to lift cylinder by its cap.  
Do not drag, slide or roll cylinders.  
Use a suitable hand truck for cylinder movement.  
Keep away from heat and sources of ignition.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.
- Avoidance of contact : Oxidizing agents

#### Storage

- Conditions for safe storage : Cylinders should be stored upright and firmly secured to prevent falling or being knocked over.



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Freon™ 408A (R-408A) Refrigerant

Version 8.0      Revision Date: 2025/10/19      SDS Number: 1336385-00049      Date of last issue: 2025/05/27  
Date of first issue: 2017/02/27

Separate full containers from empty containers.  
Do not store near combustible materials.  
Avoid area where salt or other corrosive materials are present.  
Keep in properly labelled containers.  
Keep in a cool, well-ventilated place.  
Store in accordance with the particular national regulations.

Keep away from direct sunlight.

- Materials to avoid : Do not store with the following product types:  
Explosives
- Recommended storage temperature : < 52 °C
- Storage period : > 10 yr
- Further information on storage stability : The product has an indefinite shelf life when stored properly.
- Packaging material : Unsuitable material: None known.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Chlorodifluoromethane	75-45-6	PC-TWA	3,500 mg/m <sup>3</sup>	CN OEL
		TWA	1,000 ppm	ACGIH

**Engineering measures** : Ensure adequate ventilation, especially in confined areas.  
Minimize workplace exposure concentrations.

#### Personal protective equipment

Respiratory protection : Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown.

Eye/face protection : Wear the following personal protective equipment:  
Chemical resistant goggles must be worn.  
Face-shield

Skin and body protection : Skin should be washed after contact.

Hand protection  
Material : Low temperature resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Freon™ 408A (R-408A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 2025/05/27
8.0	2025/10/19	1336385-00049	Date of first issue: 2017/02/27

on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

Protective measures : Wear cold insulating gloves/ face shield/ eye protection.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Liquefied gas

Colour : clear, colourless

Odour : slight, ether-like

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : -44.6 °C

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : Will not burn

Upper explosion limit / Upper flammability limit : Upper flammability limit  
Method: ASTM E681  
None.

Lower explosion limit / Lower flammability limit : Lower flammability limit  
Method: ASTM E681  
None.

Vapour pressure : 11,710 hPa (25 °C)



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Freon™ 408A (R-408A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 2025/05/27
8.0	2025/10/19	1336385-00049	Date of first issue: 2017/02/27

33,400 hPa (70 °C)

Relative vapour density : 3.1

Relative density : 1.06 (25 °C)

Density : 1.061 g/cm<sup>3</sup> (25 °C)  
(as liquid)

Solubility(ies)  
Water solubility : No data available

Partition coefficient: n-  
octanol/water : Not applicable

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity  
Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics  
Particle size : Not applicable

### 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable if used as directed. Follow precautionary advice and avoid incompatible materials and conditions.

Possibility of hazardous reactions : Can react with strong oxidizing agents.

Conditions to avoid : This substance is not flammable in air at temperatures up to 100 °C (212 °F) at atmospheric pressure. However, mixtures of this substance with high concentrations of air at elevated pressure and/or temperature can become combustible in the presence of an ignition source. This substance can also become combustible in an oxygen enriched environment (oxygen concentrations greater than that in air). Whether a mixture containing this substance and air, or this substance in an oxygen enriched atmosphere become combustible depends on the inter-relationship of 1) the temperature 2) the pressure, and 3) the proportion of oxygen in the mixture. In general, this

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Freon™ 408A (R-408A) Refrigerant

Version 8.0      Revision Date: 2025/10/19      SDS Number: 1336385-00049      Date of last issue: 2025/05/27  
Date of first issue: 2017/02/27

substance should not be allowed to exist with air above atmospheric pressure or at high temperatures; or in an oxygen enriched environment. For example this substance should NOT be mixed with air under pressure for leak testing or other purposes.  
Heat, flames and sparks.

Incompatible materials : Oxidizing agents  
Hazardous decomposition products : No hazardous decomposition products are known.

### 11. TOXICOLOGICAL INFORMATION

Exposure routes : Inhalation  
Skin contact  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Components:

##### Chlorodifluoromethane:

Acute inhalation toxicity : LC50 (Mouse): > 150000 ppm  
Exposure time: 4 h  
Test atmosphere: gas  
Method: Expert judgement

No observed adverse effect concentration (Dog): 25000 ppm  
Test atmosphere: gas

Lowest observed adverse effect concentration (Dog): 50000 ppm  
Test atmosphere: gas

Cardiac sensitisation threshold limit (Dog): 175,000 mg/m<sup>3</sup>  
Test atmosphere: gas

##### 1,1,1-Trifluoroethane:

Acute inhalation toxicity : LC0 (Rat): > 591000 ppm  
Exposure time: 4 h  
Test atmosphere: gas

##### Pentafluoroethane:

Acute inhalation toxicity : LC50 (Rat): > 800000 ppm  
Exposure time: 4 h  
Test atmosphere: gas  
Method: OECD Test Guideline 403

No observed adverse effect concentration (Dog): 75000 ppm  
Remarks: Cardiac sensitisation



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Freon™ 408A (R-408A) Refrigerant

Version  
8.0

Revision Date:  
2025/10/19

SDS Number:  
1336385-00049

Date of last issue: 2025/05/27  
Date of first issue: 2017/02/27

Cardiac sensitisation threshold limit (Dog): 368.159 mg/m<sup>3</sup>  
Remarks: Cardiac sensitisation

### Skin corrosion/irritation

Not classified based on available information.

### Serious eye damage/eye irritation

Causes eye irritation.

### Components:

#### Chlorodifluoromethane:

Result : Irritation to eyes, reversing within 7 days

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

### Components:

#### Chlorodifluoromethane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: positive

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

#### 1,1,1-Trifluoroethane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: Chromosome aberration test in vitro

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Freon™ 408A (R-408A) Refrigerant

Version 8.0      Revision Date: 2025/10/19      SDS Number: 1336385-00049      Date of last issue: 2025/05/27  
Date of first issue: 2017/02/27

Genotoxicity in vivo : Result: negative  
Test Type: In vitro mammalian cell gene mutation test  
Result: negative  
Remarks: Based on data from similar materials  
: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: inhalation (gas)  
Result: negative

### **Pentafluoroethane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative  
Test Type: In vitro mammalian cell gene mutation test  
Result: negative  
Remarks: Based on data from similar materials  
Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative  
Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative

### **Carcinogenicity**

Not classified based on available information.

### **Components:**

#### **Chlorodifluoromethane:**

Species : Mouse  
Application Route : inhalation (gas)  
Exposure time : 581 days  
Result : negative  
Remarks : The mechanism or mode of action is not relevant in humans.

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

#### **1,1,1-Trifluoroethane:**

Species : Rat  
Application Route : Ingestion  
Exposure time : 72 weeks  
Result : negative



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Freon™ 408A (R-408A) Refrigerant

Version  
8.0

Revision Date:  
2025/10/19

SDS Number:  
1336385-00049

Date of last issue: 2025/05/27  
Date of first issue: 2017/02/27

### Reproductive toxicity

May damage fertility or the unborn child.

#### Components:

##### Chlorodifluoromethane:

Reproductive toxicity - Assessment : Clear evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments

##### 1,1,1-Trifluoroethane:

Effects on fertility : Test Type: Three-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (gas)  
Result: negative  
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 414  
Result: negative

##### Pentafluoroethane:

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative  
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 414  
Result: negative

### STOT - single exposure

May cause drowsiness or dizziness.

#### Components:

##### Chlorodifluoromethane:

Assessment : May cause drowsiness or dizziness.

### STOT - repeated exposure

Not classified based on available information.

#### Components:

##### Chlorodifluoromethane:

Exposure routes : inhalation (gas)

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Freon™ 408A (R-408A) Refrigerant

Version 8.0      Revision Date: 2025/10/19      SDS Number: 1336385-00049      Date of last issue: 2025/05/27  
Date of first issue: 2017/02/27

Assessment : No significant health effects observed in animals at concentrations of 250 ppmV/6h/d or less.

### Repeated dose toxicity

#### Components:

##### Chlorodifluoromethane:

Species : Mouse, male and female  
NOAEL : 10000 ppm  
LOAEL : 50000 ppm  
Application Route : inhalation (gas)  
Exposure time : 581 d

##### 1,1,1-Trifluoroethane:

Species : Rat  
NOAEL : > 40000 ppm  
Application Route : inhalation (gas)  
Exposure time : 13 Weeks  
Method : OECD Test Guideline 413

##### Pentafluoroethane:

Species : Rat  
NOAEL :  $\geq$  50000 ppm  
Application Route : inhalation (gas)  
Exposure time : 13 Weeks  
Method : OECD Test Guideline 413

### Aspiration toxicity

Not classified based on available information.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

##### Chlorodifluoromethane:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 777 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 433 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (algae): 377.6 mg/l  
Exposure time: 72 h  
Method: ECOSAR (Ecological Structure Activity Relationships)

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Freon™ 408A (R-408A) Refrigerant

Version 8.0      Revision Date: 2025/10/19      SDS Number: 1336385-00049      Date of last issue: 2025/05/27  
Date of first issue: 2017/02/27

### 1,1,1-Trifluoroethane:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EC0 (Pseudokirchneriella subcapitata (green algae)): > 44 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials
- Toxicity to microorganisms : EC0 (Pseudomonas putida): > 730 mg/l  
Exposure time: 6 h

### Pentafluoroethane:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials
- NOEC (Pseudokirchneriella subcapitata (green algae)): > 1 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

### Persistence and degradability

#### Components:

#### Chlorodifluoromethane:

- Biodegradability : Result: Not readily biodegradable.  
Method: OECD Test Guideline 301D

#### 1,1,1-Trifluoroethane:

- Biodegradability : Result: Not inherently biodegradable.  
Biodegradation: 3 %  
Exposure time: 28 d



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Freon™ 408A (R-408A) Refrigerant

Version 8.0      Revision Date: 2025/10/19      SDS Number: 1336385-00049      Date of last issue: 2025/05/27  
Date of first issue: 2017/02/27

Remarks: Based on data from similar materials

### Pentafluoroethane:

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 5 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

### Bioaccumulative potential

### Components:

#### Chlorodifluoromethane:

Partition coefficient: n-octanol/water : log Pow: 1.13 (25 °C)

#### 1,1,1-Trifluoroethane:

Partition coefficient: n-octanol/water : log Pow: 1.06 - < 1.35  
Remarks: Based on data from similar materials

#### Pentafluoroethane:

Partition coefficient: n-octanol/water : Pow: 1.48  
Method: OECD Test Guideline 107

### Mobility in soil

No data available

### Other adverse effects

### Components:

#### Chlorodifluoromethane:

Ozone-Depletion Potential : 0.055  
Where a range of ODPs is indicated, the highest value in that range shall be used for the purposes of the Protocol. The ODPs listed as a single value have been determined from calculations based on laboratory measurements. Those listed as a range are based on estimates and are less certain. The range pertains to an isomeric group. The upper value is the estimate of the ODP of the isomer with the highest ODP, and the lower value is the estimate of the ODP of the isomer with the lowest ODP.  
Regulation: UNEP - Handbook for the Montreal Protocol on Substances that Deplete the Ozone Layer (Update: 2016-11-23)  
Group: Annex C - Group I: HCFCs (consumption and production)

0.055  
This category is mainly used in refrigerants, foaming agents, fire extinguishing agents, cleaning agents, aerosol, etc. As

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Freon™ 408A (R-408A) Refrigerant

Version 8.0      Revision Date: 2025/10/19      SDS Number: 1336385-00049      Date of last issue: 2025/05/27  
Date of first issue: 2017/02/27

specified in the accelerated phase-out proposal of hydrochlorofluorocarbons (HCFCs) pursuant to the Montreal Protocol, the production and use of this category in 2013 shall be the average of that in 2009 and 2010; the production and use of this category in 2015 shall be cut by 10% from the average said; that in 2020 by 35%; that in 2025 by 67.5%. By 2030, except for repair and special purposes, this category shall be eliminated completely.

Regulation: Regulations of Ozone Depleting Substances Management (Update: 2021-10-08)  
Group: Category V Hydrochlorofluorocarbons

Permits required  
Regulation: Regulations of Ozone Depleting Substances Management (Update: 2021-10-25)  
Number: 2903710000

### 1,1,1-Trifluoroethane:

Ozone-Depletion Potential : Permits required  
Regulation: Regulations of Ozone Depleting Substances Management (Update: 2021-10-25)  
Number: 2903399045

### Pentafluoroethane:

Ozone-Depletion Potential : Permits required  
Regulation: Regulations of Ozone Depleting Substances Management (Update: 2021-10-25)  
Number: 2903399047

## 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Dispose of in accordance with local regulations.  
Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty pressure vessels should be returned to the supplier.  
If not otherwise specified: Dispose of as unused product.

## 14. TRANSPORT INFORMATION

### International Regulations

#### UNRTDG

UN number : UN 3163  
Proper shipping name : LIQUEFIED GAS, N.O.S.  
(Chlorodifluoromethane, 1,1,1-Trifluoroethane)

Class : 2.2  
Packing group : Not assigned by regulation



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Freon™ 408A (R-408A) Refrigerant

Version 8.0      Revision Date: 2025/10/19      SDS Number: 1336385-00049      Date of last issue: 2025/05/27  
Date of first issue: 2017/02/27

- || Labels : 2.2
- Environmentally hazardous : no
- IATA-DGR**
- UN/ID No. : UN 3163
- Proper shipping name : Liquefied gas, n.o.s.  
(Chlorodifluoromethane, 1,1,1-Trifluoroethane)
- || Class : 2.2
- Packing group : Not assigned by regulation
- || Labels : Non-flammable, non-toxic Gas
- Packing instruction (cargo aircraft) : 200
- Packing instruction (passenger aircraft) : 200
- IMDG-Code**
- UN number : UN 3163
- Proper shipping name : LIQUEFIED GAS, N.O.S.  
(Chlorodifluoromethane, 1,1,1-Trifluoroethane)
- || Class : 2.2
- Packing group : Not assigned by regulation
- || Labels : 2.2
- || EmS Code : F-C, S-V
- Marine pollutant : no

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### National Regulations

#### GB 6944/12268

- UN number : UN 3163
- Proper shipping name : LIQUEFIED GAS, N.O.S.  
(Chlorodifluoromethane, 1,1,1-Trifluoroethane)
- || Class : 2.2
- Packing group : Not assigned by regulation
- || Labels : 2.2
- Marine pollutant : no

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 15. REGULATORY INFORMATION

### National regulatory information

#### Law on the Prevention and Control of Occupational Diseases

#### Regulations on Safety Management of Hazardous Chemicals

Catalogue of Hazardous Chemicals : Listed

Identification of Major Hazard Installations for Hazardous Chemicals (GB 18218) : Not listed



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Freon™ 408A (R-408A) Refrigerant

Version 8.0      Revision Date: 2025/10/19      SDS Number: 1336385-00049      Date of last issue: 2025/05/27  
Date of first issue: 2017/02/27

Hazardous Chemicals for Priority Management under SAWS : Not listed

Catalogue of Specially Controlled Hazardous Chemicals : Not listed

List of Explosive Precursors : Not listed

### Regulations on Labour Protection in Workplaces where Toxic Substances are Used

Catalogue of Highly Toxic Chemicals : Not listed

### Regulation of Environmental Management on the First Import of Chemicals and the Import and Export of Toxic Chemicals

China Severely Restricted Toxic Chemicals for Import and Export : Not listed

### Regulation on the Administration of Precursor Chemicals

Catalogue and Classification of Precursor Chemicals : Not listed

### Yangtze River Protection Law

This product does not contain any dangerous chemicals prohibited for inland river transport.

### Regulations of Ozone Depleting Substances Management

List of Controlled Ozone Depleting Substances Import and Export : Listed

List of Controlled Ozone Depleting Substances : Listed

### Environmental Protection Law

List of Priority Controlled Chemicals : Not listed

List of Key Controlled New Pollutants : Not listed

List of Toxic and Hazardous Water Pollutants : Not listed

List of Toxic and Hazardous Air Pollutants : Not listed

List of Toxic and Hazardous Soil Pollutants : Not listed

### Measures for the Administration of Non-Medical Use of Narcotic Drugs and Psychotropic Substances

Catalogue of Controlled Narcotic Drugs and Psychotropic Substances with Non-Medical Use : Not listed

### Measures for the Administration on Import and Export Licenses for Dual-Use Items and Technologies

Catalogue for Dual-Use Items and Technologies : Not listed

Montreal Protocol : Chlorodifluoromethane



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Freon™ 408A (R-408A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 2025/05/27
8.0	2025/10/19	1336385-00049	Date of first issue: 2017/02/27

1,1,1-Trifluoroethane  
Pentafluoroethane

### 16. OTHER INFORMATION

Revision Date : 2025/10/19

Other information : Freon™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC. Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information. For further information contact the local Chemours office or nominated distributors.

#### Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Date format : yyyy/mm/dd

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
CN OEL : Occupational exposure limits for hazardous agents in the workplace - Chemical hazardous agents.

ACGIH / TWA : 8-hour, time-weighted average  
CN OEL / PC-TWA : Permissible concentration - time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MERCOSUR - The Agreement for the Facilitation of the Transport of Dangerous Goods; n.o.s. -

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Freon™ 408A (R-408A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 2025/05/27
8.0	2025/10/19	1336385-00049	Date of first issue: 2017/02/27

Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CN / EN

