

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## HP 152a Aerosol Propellant

Version 6.0      Revision Date: 2025/05/29      SDS Number: 1324410-00039      Date of last issue: 2025/03/05  
Date of first issue: 2017/02/27

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : HP 152a Aerosol Propellant

SDS-Identcode : 130000000071

#### Manufacturer or supplier's details

Company : The Chemours Chemical (Shanghai) Co., Ltd.

Address : 9F, SCG Parkside, 868 Yinghua Road, Pudong New District  
201204, Shanghai, China

Telephone : 86 400 8056 528

Emergency telephone number : 86 532 8388 9090

E-mail address : SDS.ChinaPSR@chemours.com

Telefax : 86 21 2612 0862

#### Recommended use of the chemical and restrictions on use

Recommended use : Propellant

Restrictions on use : For industrial use only.

### 2. HAZARDS IDENTIFICATION

#### Emergency Overview

**Appearance** : Liquefied gas  
**Colour** : clear, colourless  
**Odour** : slight, ether-like

Extremely flammable gas. Contains gas under pressure; may explode if heated. May cause drowsiness or dizziness.

#### GHS Classification

Flammable gases : Category 1A  
Gases under pressure : Liquefied gas  
Specific target organ toxicity - single exposure : Category 3

#### GHS label elements



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## HP 152a Aerosol Propellant

Version 6.0      Revision Date: 2025/05/29      SDS Number: 1324410-00039      Date of last issue: 2025/03/05  
Date of first issue: 2017/02/27

Hazard pictograms	:	  
Signal word	:	Danger
Hazard statements	:	H220 Extremely flammable gas. H280 Contains gas under pressure; may explode if heated. H336 May cause drowsiness or dizziness.
Precautionary statements	:	<b>Prevention:</b> P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. P261 Avoid breathing gas. P271 Use only outdoors or in a well-ventilated area. <b>Response:</b> P304 + P340 + P319 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical help if you feel unwell. P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely. P381 Eliminate all ignition sources if safe to do so. <b>Storage:</b> P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P410 + P403 Protect from sunlight. Store in a well-ventilated place. <b>Disposal:</b> P501 Dispose of contents/ container to an approved waste disposal plant.

### Physical and chemical hazards

Extremely flammable gas. Contains gas under pressure; may explode if heated.

### Health hazards

May cause drowsiness or dizziness.

### Environmental hazards

Not classified based on available information.

### Other hazards which do not result in classification

Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.

Misuse or intentional inhalation abuse may cause death without warning symptoms, due to cardiac effects.

Rapid evaporation of the product may cause frostbite.

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## HP 152a Aerosol Propellant

Version 6.0      Revision Date: 2025/05/29      SDS Number: 1324410-00039      Date of last issue: 2025/03/05  
Date of first issue: 2017/02/27

May displace oxygen and cause rapid suffocation.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance  
Substance name : 1,1-Difluoroethane  
CAS-No. : 75-37-6

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
1,1-Difluoroethane	75-37-6	$\geq 99.9$ - $\leq 100$

### 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.  
If not breathing, give artificial respiration.  
If breathing is difficult, give oxygen.  
Get medical attention immediately.

In case of skin contact : Thaw frosted parts with lukewarm water. Do not rub affected area.  
Get medical attention immediately.

In case of eye contact : Get medical attention immediately.

If swallowed : Ingestion is not considered a potential route of exposure.

Most important symptoms and effects, both acute and delayed : May cause cardiac arrhythmia.  
Other symptoms potentially related to misuse or inhalation abuse are  
Cardiac sensitisation  
Anaesthetic effects  
Light-headedness  
Dizziness  
confusion  
Lack of coordination  
Drowsiness  
Unconsciousness  
Gas reduces oxygen available for breathing.  
Contact with liquid or refrigerated gas can cause cold burns and frostbite.  
May cause drowsiness or dizziness.

Protection of first-aiders : No special precautions are necessary for first aid responders.



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## HP 152a Aerosol Propellant

Version	Revision Date:	SDS Number:	Date of last issue: 2025/03/05
6.0	2025/05/29	1324410-00039	Date of first issue: 2017/02/27

Notes to physician : Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, that may be used in situations of emergency life support should be used with special caution.

### 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : None known.

Specific hazards during fire-fighting : Vapours may form flammable mixture with air  
Exposure to combustion products may be a hazard to health.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Hydrogen fluoride  
carbonyl fluoride  
Carbon oxides

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Fight fire remotely due to the risk of explosion.  
Use water spray to cool unopened containers.  
Leaking gas fire: Do not extinguish, unless leak can be stopped safely.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.  
Use personal protective equipment.

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.  
Only trained personnel should re-enter the area.  
Remove all sources of ignition.  
Avoid skin contact with leaking liquid (danger of frostbite).  
Ventilate the area.  
Follow safe handling advice (see section 7) and personal pro-



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## HP 152a Aerosol Propellant

Version	Revision Date:	SDS Number:	Date of last issue:
6.0	2025/05/29	1324410-00039	2025/03/05
			Date of first issue: 2017/02/27

protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Retain and dispose of contaminated wash water.

Methods and materials for containment and cleaning up : Ventilate the area.  
Non-sparking tools should be used.  
Suppress (knock down) gases/vapours/mists with a water spray jet.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### 7. HANDLING AND STORAGE

#### Handling

Technical measures : Use equipment rated for cylinder pressure. Use a backflow preventative device in piping. Close valve after each use and when empty.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.  
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Advice on safe handling : Avoid breathing gas.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Keep container tightly closed.  
Wear cold insulating gloves/ face shield/ eye protection.  
Valve protection caps and valve outlet threaded plugs must remain in place unless container is secured with valve outlet piped to use point.  
Prevent backflow into the gas tank.  
Use a check valve or trap in the discharge line to prevent hazardous back flow into the cylinder.  
Use a pressure reducing regulator when connecting cylinder to lower pressure (<3000 psig) piping or systems.  
Close valve after each use and when empty. Do NOT change or force fit connections.  
Prevent the intrusion of water into the gas tank.  
Never attempt to lift cylinder by its cap.  
Do not drag, slide or roll cylinders.



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## HP 152a Aerosol Propellant

Version	Revision Date:	SDS Number:	Date of last issue: 2025/03/05
6.0	2025/05/29	1324410-00039	Date of first issue: 2017/02/27

Use a suitable hand truck for cylinder movement.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.

Avoidance of contact : Oxidizing agents

### Storage

Conditions for safe storage : Cylinders should be stored upright and firmly secured to prevent falling or being knocked over.  
Separate full containers from empty containers.  
Do not store near combustible materials.  
Avoid area where salt or other corrosive materials are present.  
Keep in properly labelled containers.  
Keep tightly closed.  
Keep in a cool, well-ventilated place.  
Keep away from direct sunlight.  
Store in accordance with the particular national regulations.  
Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:  
Self-reactive substances and mixtures  
Organic peroxides  
Oxidizing agents  
Flammable liquids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Explosives

Recommended storage temperature : < 52 °C

Storage period : > 10 yr

Further information on storage stability : The product has an indefinite shelf life when stored properly.  
Keep container tightly closed in a dry and well-ventilated place.

Packaging material : Unsuitable material: None known.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Engineering measures : Minimize workplace exposure concentrations.



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## HP 152a Aerosol Propellant

Version 6.0	Revision Date: 2025/05/29	SDS Number: 1324410-00039	Date of last issue: 2025/03/05 Date of first issue: 2017/02/27
----------------	------------------------------	------------------------------	---

If sufficient ventilation is unavailable, use with local exhaust ventilation.  
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

### Personal protective equipment

- Respiratory protection : Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown.
- Eye/face protection : Wear the following personal protective equipment:  
Chemical resistant goggles must be worn.  
Face-shield
- Skin and body protection : Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
- Hand protection  
Material : Heat resistant gloves
- Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!
- Protective measures : Wear cold insulating gloves/ face shield/ eye protection.
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Liquefied gas
- Colour : clear, colourless



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## HP 152a Aerosol Propellant

Version 6.0      Revision Date: 2025/05/29      SDS Number: 1324410-00039      Date of last issue: 2025/03/05  
Date of first issue: 2017/02/27

---

Odour : slight, ether-like

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : -117 °C

Initial boiling point and boiling range : -24.7 °C (1,013 hPa)

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : Flammable

Self-ignition : The substance or mixture is not classified as pyrophoric.

Upper explosion limit / Upper flammability limit : Upper flammability limit  
16.9 %(V)  
Method: ASTM E681

Lower explosion limit / Lower flammability limit : Lower flammability limit  
3.9 %(V)  
Method: ASTM E681

Vapour pressure : 5,146.24 hPa (25 °C)

Relative vapour density : 2.4  
(Air = 1.0)

Density : 0.90 g/cm<sup>3</sup> (25 °C)  
(as liquid)

Solubility(ies)  
Water solubility : 0.2 g/l (25 °C)

Partition coefficient: n-octanol/water : log Pow: 1.13 (25 °C)

Auto-ignition temperature : 440 °C

Decomposition temperature : No data available

Viscosity  
Viscosity, kinematic : Not applicable

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## HP 152a Aerosol Propellant

Version 6.0      Revision Date: 2025/05/29      SDS Number: 1324410-00039      Date of last issue: 2025/03/05  
Date of first issue: 2017/02/27

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics  
Particle size : Not applicable

### 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable if used as directed. Follow precautionary advice and avoid incompatible materials and conditions.

Possibility of hazardous reactions : Vapours may form flammable mixture with air  
Can react with strong oxidizing agents.  
Extremely flammable gas.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

### 11. TOXICOLOGICAL INFORMATION

Exposure routes : Inhalation  
Skin contact  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Components:

##### 1,1-Difluoroethane:

Acute oral toxicity : Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 437500 ppm  
Exposure time: 4 h  
Test atmosphere: gas

No observed adverse effect concentration (Dog): 50000 ppm  
Test atmosphere: gas  
Method: Cardiac sensitisation study

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## HP 152a Aerosol Propellant

Version 6.0      Revision Date: 2025/05/29      SDS Number: 1324410-00039      Date of last issue: 2025/03/05  
Date of first issue: 2017/02/27

Lowest observed adverse effect concentration (Dog): 150000 ppm  
Test atmosphere: gas  
Method: Cardiac sensitisation study

Cardiac sensitisation threshold limit (Dog): 405,000 mg/m3  
Test atmosphere: gas  
Method: Cardiac sensitisation study

Acute dermal toxicity : Assessment: The substance or mixture has no acute dermal toxicity

### Skin corrosion/irritation

Not classified based on available information.

#### Components:

##### 1,1-Difluoroethane:

Result : No skin irritation

### Serious eye damage/eye irritation

Not classified based on available information.

#### Components:

##### 1,1-Difluoroethane:

Result : No eye irritation

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

#### Components:

##### 1,1-Difluoroethane:

Exposure routes : Skin contact  
Result : negative

Exposure routes : Inhalation  
Species : Rat  
Result : negative

### Germ cell mutagenicity

Not classified based on available information.



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## HP 152a Aerosol Propellant

Version 6.0      Revision Date: 2025/05/29      SDS Number: 1324410-00039      Date of last issue: 2025/03/05  
Date of first issue: 2017/02/27

### Components:

#### 1,1-Difluoroethane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: positive

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ  
cell mutagen.

### **Carcinogenicity**

Not classified based on available information.

### Components:

#### 1,1-Difluoroethane:

Species : Rat  
Application Route : inhalation (gas)  
Exposure time : 104 weeks  
Method : OECD Test Guideline 453  
Result : negative

Carcinogenicity - Assessment : Weight of evidence does not support classification as a car-  
cinogen

### **Reproductive toxicity**

Not classified based on available information.

### Components:

#### 1,1-Difluoroethane:

Effects on fertility : Test Type: Rodent dominant lethal test (germ cell) (in vivo)  
Species: Mouse  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 478  
Result: negative  
Remarks: Based on data from similar materials

Test Type: Combined Chronic Toxicity/Carcinogenicity Studies



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## HP 152a Aerosol Propellant

Version 6.0      Revision Date: 2025/05/29      SDS Number: 1324410-00039      Date of last issue: 2025/03/05  
Date of first issue: 2017/02/27

	Species: Rat Application Route: inhalation (gas) Method: OECD Test Guideline 453 Result: negative
Effects on foetal development	: Test Type: Prenatal development toxicity study (teratogenicity) Species: Rat Application Route: inhalation (vapour) Method: OECD Test Guideline 414 Result: negative
	Test Type: Prenatal development toxicity study (teratogenicity) Species: Rabbit Application Route: inhalation (gas) Method: OECD Test Guideline 414 Result: negative Remarks: Based on data from similar materials
Reproductive toxicity - Assessment	: Weight of evidence does not support classification for reproductive toxicity

### STOT - single exposure

May cause drowsiness or dizziness.

#### Components:

##### 1,1-Difluoroethane:

Exposure routes : inhalation (gas)  
Assessment : No significant health effects observed in animals at concentrations of 20000 ppmV/4h or less

Exposure routes : Skin contact  
Assessment : No significant health effects observed in animals at concentrations of 2000 mg/kg bw or less

Exposure routes : Ingestion  
Assessment : No significant health effects observed in animals at concentrations of 2000 mg/kg bw or less

### STOT - repeated exposure

Not classified based on available information.

#### Components:

##### 1,1-Difluoroethane:

Exposure routes : inhalation (gas)  
Assessment : No significant health effects observed in animals at concentrations of 250 ppmV/6h/d or less.

Exposure routes : Skin contact  
Assessment : No significant health effects observed in animals at concentra-

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## HP 152a Aerosol Propellant

Version 6.0      Revision Date: 2025/05/29      SDS Number: 1324410-00039      Date of last issue: 2025/03/05  
Date of first issue: 2017/02/27

||      tions of 200 mg/kg bw or less.

|| Exposure routes : Ingestion  
|| Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

### Repeated dose toxicity

#### Components:

##### 1,1-Difluoroethane:

|| Species : Rat, male and female  
|| NOAEL : 25000 ppm  
|| LOAEL : >25000 ppm  
|| Application Route : inhalation (gas)  
|| Exposure time : 104 Weeks  
|| Method : OECD Test Guideline 453

### Aspiration toxicity

Not classified based on available information.

#### Components:

##### 1,1-Difluoroethane:

|| No aspiration toxicity classification

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

##### 1,1-Difluoroethane:

|| Toxicity to fish : LC50 (Fish): 295.783 mg/l  
Exposure time: 96 h  
Method: ECOSAR (Ecological Structure Activity Relationships)

|| Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 146.695 mg/l  
Exposure time: 48 h  
Method: ECOSAR (Ecological Structure Activity Relationships)

|| Toxicity to algae/aquatic plants : EC50 (algae): 47.755 mg/l  
Method: ECOSAR (Ecological Structure Activity Relationships)

### Ecotoxicology Assessment

|| Acute aquatic toxicity : This product has no known ecotoxicological effects.



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## HP 152a Aerosol Propellant

Version 6.0      Revision Date: 2025/05/29      SDS Number: 1324410-00039      Date of last issue: 2025/03/05  
Date of first issue: 2017/02/27

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

### Persistence and degradability

#### Components:

##### 1,1-Difluoroethane:

Biodegradability : Result: Not readily biodegradable.

### Bioaccumulative potential

#### Components:

##### 1,1-Difluoroethane:

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 1.13 (25 °C)

### Mobility in soil

#### Components:

##### 1,1-Difluoroethane:

Distribution among environmental compartments : Koc: 4.47

### Other adverse effects

#### Components:

##### 1,1-Difluoroethane:

Ozone-Depletion Potential : Permits required  
Regulation: Regulations of Ozone Depleting Substances Management (Update: 2021-10-25)  
Number: 2903399044

## 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty pressure vessels should be returned to the supplier.  
If not otherwise specified: Dispose of as unused product.



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## HP 152a Aerosol Propellant

Version	Revision Date:	SDS Number:	Date of last issue: 2025/03/05
6.0	2025/05/29	1324410-00039	Date of first issue: 2017/02/27

### 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

UN number : UN 1030  
Proper shipping name : 1,1-DIFLUOROETHANE  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
Environmentally hazardous : no

##### IATA-DGR

UN/ID No. : UN 1030  
Proper shipping name : 1,1-Difluoroethane  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : Flammable Gas  
Packing instruction (cargo aircraft) : 200  
Packing instruction (passenger aircraft) : Not permitted for transport

##### IMDG-Code

UN number : UN 1030  
Proper shipping name : 1,1-DIFLUOROETHANE  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U  
Marine pollutant : no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### National Regulations

##### GB 6944/12268

UN number : UN 1030  
Proper shipping name : 1,1-DIFLUOROETHANE  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
Marine pollutant : no

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## HP 152a Aerosol Propellant

Version	Revision Date:	SDS Number:	Date of last issue: 2025/03/05
6.0	2025/05/29	1324410-00039	Date of first issue: 2017/02/27

### 15. REGULATORY INFORMATION

#### National regulatory information

##### Regulations on Safety Management of Hazardous Chemicals

Catalogue of Hazardous Chemicals : Listed

Identification of Major Hazard Installations for Hazardous Chemicals (GB 18218)

No. / Code	Chemical name / Category	Threshold quantity
------------	--------------------------	--------------------

W2	Flammable gases	10 t
----	-----------------	------

Hazardous Chemicals for Priority Management under SAWS : Not listed

Catalogue of Specially Controlled Hazardous Chemicals : Not listed

List of Explosive Precursors : Not listed

##### Regulations on Labour Protection in Workplaces where Toxic Substances are Used

Catalogue of Highly Toxic Chemicals : Not listed

##### Regulation of Environmental Management on the First Import of Chemicals and the Import and Export of Toxic Chemicals

China Severely Restricted Toxic Chemicals for Import and Export : Not listed

##### Regulation on the Administration of Precursor Chemicals

Catalogue and Classification of Precursor Chemicals : Not listed

##### Yangtze River Protection Law

This product does not contain any dangerous chemicals prohibited for inland river transport.

##### Regulations of Ozone Depleting Substances Management

List of Controlled Ozone Depleting Substances Import and Export : Listed

List of Controlled Ozone Depleting Substances : Listed

##### Environmental Protection Law

List of Priority Controlled Chemicals : Not listed

List of Key Controlled New Pollutants : Not listed

Montreal Protocol : 1,1-Difluoroethane

### 16. OTHER INFORMATION

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## HP 152a Aerosol Propellant

Version	Revision Date:	SDS Number:	Date of last issue: 2025/03/05
6.0	2025/05/29	1324410-00039	Date of first issue: 2017/02/27

---

Revision Date : 2025/05/29

Other information : Chemours™ and the Chemours Logo are trademarks of The Chemours Company.  
Before use read Chemours safety information.  
For further information contact the local Chemours office or nominated distributors.

### Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Date format : yyyy/mm/dd

### Full text of other abbreviations

AIIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recom-

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## HP 152a Aerosol Propellant

Version	Revision Date:	SDS Number:	Date of last issue: 2025/03/05
6.0	2025/05/29	1324410-00039	Date of first issue: 2017/02/27

---

recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CN / EN

