

RANGE OF POLYAMIDES

Radici Plastics offers a wide range of polyamide engineering thermoplastics used in a great variety of automotive, electrical/electronics, industrial and consumer goods applications.

Our range of polyamides includes both traditional products and highly innovative specialities, such as materials suitable for continuous service at high temperatures, grades specifically designed for metal replacement and others with superior resistance to chemical agents.






			PA6						
			RADILON S HS	RADILON S 40E	RADILON S HSX	RADILON S USZ200	RADILON S RCP3010LW	RADILON S RV300W	RADILON S RV350W
TENSILE MODULUS	ISO 527-2/1A	MPa	3000/1200	3000/1150	2600/1050	1650/600	8200/6250	9600/6400	11300/7250
STRESS AT BREAK/ YIELD STRESS	ISO 527-2/1A	MPa	80/45	75/42	65/40	40/20	95/65	180/115	195/120
STRAIN AT BREAK/ NORMAL STRAIN AT BREAK	ISO 527-2/1A	%	50/>50	>50/>50	55/>100	>100/>100	2,9/10	3,5/8,0	3,5/6,5
YIELD STRAIN	ISO 527-2/1A	%	4/30	4,1/25	4,2/20	5,0/30	-	-	-
FLEXURAL MODULUS	ISO 178	MPa	2600/850	2450/750	2300/	1400/	7700/	8600/	9800/
FLEXURAL STRENGTH	ISO 178	MPa	105/30	100/30	90/	55/	165/	265/	280/
CHARPY IMPACT STRENGTH, 23°C	ISO 179/1 eU	kJ/m2	NB/NB	NB/NB	NB/NB	NB/NB	45/52	95/110	100/110
CHARPY IMPACT STRENGTH, -30°C	ISO 179/1 eU	kJ/m2	NB/	NB/	NB/	NB/	44/	85/	90/
CHARPY NOTCHED IMPACT STRENGTH, 23°C	ISO 179/1 eA	kJ/m2	7,5/13	7,4/15	15/65	90/130	6/8,5	15/25	18/33
CHARPY NOTCHED IMPACT STRENGTH, -30°C	ISO 179/1 eA	kJ/m2	4,5/	4,6/	10/	85/	5,1/	11/	13/
MELTING POINT	ISO 11357-1-3	°C	220	220	220	220	220	220	220
HEAT DEFLECTION TEMPERATURE 1.8 MPA	ISO 75/2 A f	°C	60	60	60	50	200	200	205
HEAT DEFLECTION TEMPERATURE 0.45 MPA	ISO 75/2 B f	°C	170	170	160	135	210	215	215
VICAT SOFTENING TEMPERATURE	ISO 306/B50 50N	°C	190	195	185	150	210	210	210
FLAMMABILITY	UL 94	mm/class	0,8/V2	0,8/HB	0,8/HB	0,8/HB	0,8/HB	0,8/HB	0,8/HB
DENSITY	ISO 1183	kg/m3	1140	1140	1110	1060	1330	1350	1400
PROCESSING			Injection moulding	Extrusion Injection moulding	Injection moulding	Injection moulding	Injection moulding	Injection moulding	Injection moulding

Double entries refer to Dry As Moulded / Cond. RH50 (ISO 1110) conditions

MATERIAL DESCRIPTION

TYPICAL APPLICATIONS

PA6	RADILON S HS	PA6 unfilled for injection moulding.	Standard viscosity, general purpose grade.
	RADILON S 40E	PA6 high viscosity extrusion grade. Lubricated.	Suitable for injection moulding of high thickness items.
	RADILON S HSX	PA6 injection moulding grade. Toughened.	Suitable for parts requiring improved impact resistance.
	RADILON S USZ200	PA6 injection moulding grade. Toughened.	Suitable for parts requiring excellent impact resistance, even at low temperatures.
	RADILON S RCP3010LW	PA6 30% glass fiber and mineral filler reinforced injection moulding grade. Heat stabilized.	Suitable for parts requiring improved stiffness and dimensional stability.
	RADILON S RV300W	PA6 30% glass fiber reinforced injection moulding grade. Heat stabilized.	Suitable for parts requiring high stiffness and good mechanical resistance.
	RADILON S RV350W	PA6 35% glass fiber reinforced injection moulding grade. Heat stabilized.	Suitable for parts requiring high stiffness and good mechanical resistance.
	RADILON S ERV3808K	PA6 30% glass fiber reinforced injection moulding grade. Toughened, heat stabilized.	Suitable for parts requiring improved impact strength along with high stiffness.
	RADILON S BMX200K	PA6 high viscosity blow moulding grade.	Suitable for blow-moulding of tubes and containers.
RADILON S URV600LW	PA6 60% glass fiber reinforced injection moulding grade. Very high flowability. Heat stabilized.	Suitable for metal replacement applications.	
PA6.6	RADILON A HS	PA66 unfilled for injection moulding.	Standard viscosity grade, suitable for high productivity items
	RADILON A 42K	PA66 high viscosity extrusion grade. Heat stabilized.	Suitable for injection moulding of high thickness items.
	RADILON A HSX88	PA66 injection moulding grade. Toughened.	Suitable for parts requiring improved impact resistance.
	RADILON A USZ200	PA66 injection moulding grade. Toughened.	Suitable for parts requiring excellent impact resistance, even at low temperatures.
	RADILON A RV300W	PA66 30% glass fiber reinforced injection moulding grade. Heat stabilized.	Suitable for parts requiring high stiffness and good mechanical resistance.
	RADILON A RV350W	PA66 35% glass fiber reinforced injection moulding grade. Heat stabilized.	Suitable for parts requiring high stiffness and good mechanical resistance.
	RADILON A RV500RW	PA66 50% glass fiber reinforced injection moulding grade. Heat stabilized.	Suitable for technical parts requiring very high mechanical resistance. Especially fit for metal replacement applications.
	RADILON A CF300K	PA66 30% carbon fiber reinforced injection moulding grade. Heat stabilized.	Suitable for parts requiring very high mechanical properties, higher electrical and thermal conductivity.
	RADILON A ERV130LK	PA66 13% glass fiber reinforced injection moulding grade. Toughened, heat stabilized.	Suitable for parts requiring improved impact strength along with enhanced stiffness.
	RADILON A RV350HHR	PA66 35% glass fiber reinforced injection moulding grade with enhanced thermal resistance in contact with hot air.	Suitable for continuous use at air temperatures of up to 210 °C
PA6.10	RADILON D HS	PA610 injection moulding grade. Nucleated and lubricated, fast cycling.	Suitable for injection moulded parts. This grade is partially renewably-sourced (60% of base polymer by weight).
	RADILON D RV300W	PA610, 30% glass fiber reinforced injection moulding grade. Heat stabilized.	Suitable for parts requiring high stiffness and mechanical resistance. This grade is partially renewably-sourced (60% of base polymer by weight).
	RADILON D 40EP25ZW	PA610 flexible, high viscosity extrusion grade. Toughened and plasticized.	Suitable for extrusion of pipes, profiles and cable jackets. This grade is partially renewably-sourced (60% of base polymer by weight).
	RADILON D 40P50K	PA610 flexible, high viscosity extrusion grade. Plasticized.	Suitable for extrusion of air pressure pipes. This grade is partially renewably-sourced (60% of base polymer by weight).
PA6.12	RADILON DT 40EP75W	PA612 semi-rigid, high viscosity extrusion grade. Toughened. Heat stabilized.	Suitable for extrusion of profiles, tubes and pipes.
PA-Xt HIGH TEMPERATURE PA	RADILON XTREME RV350HHR	High Temperature polyamide, 35% glass fiber reinforced. Highly improved thermal resistance in contact with hot air.	Suitable for applications at continuous service temperatures of up to 220-230 °C
	RADILON XTREME RV500HHR	High Temperature polyamide, 50% glass fiber reinforced. Highly improved thermal resistance in contact with hot air.	Suitable for applications at continuous service temperatures of up to 220-230 °C
PA6/PA6.6 SELF EXTINGUISHING	RADIFLAM S FR	PA6 flame retardant injection moulding grade. Halogen and phosphorus free.	Suitable for parts requiring fire retardancy. Rated V-0 at 0.4 mm according to UL-94.
	RADIFLAM A FR	PA66 flame retardant injection moulding grade. Halogen and phosphorus free.	Suitable for parts requiring fire retardancy. Rated V-0 at 0.4 mm according to UL-94.
	RADIFLAM A RV250K AE	PA66 flame retardant injection moulding grade. 25% glass fiber reinforced.	Suitable for parts requiring fire retardancy and good mechanical resistance. Rated V-0 according to UL-94.
	RADIFLAM A RV300 HF	PA66 flame retardant, halogen and phosphorus free injection moulding grade. 30% glass fiber reinforced.	Suitable for parts requiring fire retardancy and good mechanical resistance. Rated V-0 according to UL-94.
	RADIFLAM A RV350 AF	PA66 flame retardant injection moulding grade with red phosphorus. 35% glass fiber reinforced.	Suitable for parts requiring fire retardancy and good mechanical resistance. Rated V-0 according to UL-94.
	RADIFLAM S RV300 HF	PA6 flame retardant injection moulding grade, halogen and red phosphorus free. 30% glass fiber reinforced.	Suitable for parts requiring fire retardancy and good mechanical resistance. Good electrical insulating properties. Rated V-0 according to UL-94.



RADICI NOVACIPS SpA

Via Bedeschi, 20 – 24040 Chignolo d'Isola (BG) – I
Tel. +39 035 4991311 - Fax +39 035 994386
e-mail: italia.plastics@radicigroup.com

RADICI NOVACIPS SpA

Via Provinciale, 1331 – 24020 Villa d'Ogna (BG) – I
Tel. +39 0346 22453 – Fax +39 0346 23730
e-mail: italia.plastics@radicigroup.com

RADICI PLASTICS GmbH

Glockengiesserwall 2 – 20095 Hamburg - D
Tel. +49 40 3095410 – Fax +49 40 30954199
e-mail: deutschland.plastics@radicigroup.com

Production:

Elsö-Klöver-Strasse, 10 – Industriegebiet Hafen
21337 Lüneburg - D

RADICI PLASTICS IBERICA SL


Avda. Josep Tarradellas, 130 5^o1^a
08029 Barcelona (ES)
Tel. +34 93 5416500 – Fax +34 93 4943326
e-mail: iberica.plastics@radicigroup.com

RADICI PLASTICS UK Ltd.

High Hill House, 6A Hampstead High Street
London NW3 1PR – UK
Tel. +44 20 74314554 – Fax +44 20 74314544
e-mail: uk.plastics@radicigroup.com

RADICI PLASTICS FRANCE SA

65, Rue du Dauphiné – 69800 St. Priest – F
Tel. +33 4 72782090 – Fax +33 4 72782089
e-mail: france.plastics@radicigroup.com



RADICI PLASTICS LTDA

Rua Giuseppe Marchiori, 497
CEP 18147-970 Araçariçuama – São Paulo – BR
Tel. +55 11 4136 6500 – Fax +55 11 4136 2166
e-mail: brasil.plastics@radicigroup.com

RADICI PLASTICS USA Inc.

960 Seville Road, Wadsworth, OH 44281 - USA
Tel. +1 330 3367611 – Fax +1 330 3362143
e-mail: usa.plastics@radicigroup.com

RADICI PLASTICS (Suzhou) CO., LTD.

No. 49 Ping Sheng Road, SIP
215126 Suzhou, Jiangsu Province – PR China
Tel. +86 512 62952290 – Fax +86 512 62952291
e-mail: china.plastics@radicigroup.com

RADICI PLASTICS INDIA PVT. LTD.

C-5 1st Floor, Amar Colony Market, Lajpat Nagar-IV
New Delhi - 110024 - IN
Tel. +91 11 41638170
e-mail: info.plastics@radicigroup.com

RADICI PLASTICS MEXICO S. DE R.L. DE C.V.

Av. Francisco Zarco 2688
C.P. 47810 - Col. Loma Bonita - Ocotlán Jalisco -MX
Tel. +52 392 923 2390
e-mail: info.plastics@radicigroup.com

RADICI PLASTICS B.V.

Verloren Van Themaatweg 9 – 6121RG, Born, Netherland
Tel. +49 40 3095410 – Fax +49 40 30954199
e-mail: deutschland.plastics@radicigroup.com

The information provided in this documentation corresponds to our knowledge on the subject at the date of its publication. This information may be subject to revision as new knowledge and experience become available. The data provided reflects the average values of the properties measured over an adequate number of different production cycles and relates only to the designated material; this data may not be valid for such material used in combination with any other materials or additives or in any process, unless expressly indicated otherwise. The data provided should not be used to establish specification limits nor used alone as the basis of design; it is not intended to substitute for any testing you may need to conduct to determine for yourself the suitability of a specific material for your particular purposes. Since Radici Plastics cannot anticipate all variations in actual end-use conditions Radici Plastics makes no warranties and assumes no liability in connection with any use of this information. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent rights.