

Technical Data Sheet

ECOZEN[®] HB



ECOZEN

ECOZEN

. BPA

가

ECOZEN

가

-
- 가
-

●

- Color
-

SK



ECOZEN[®] HB

ASTM

Test			
	ASTM D792	-	1.33
	ASTM D955	%	0.2 ~ 0.5
	ASTM D785	R-scale	>115
@	ASTM D638	Kgf/cm2	610
@	ASTM D638	Kgf/cm2	440
@	ASTM D638	%	5.0
@	ASTM D638	%	200
	ASTM D790	Kgf/cm2	880
	ASTM D790	Kgf/cm2	24,500
@ 23	ASTM D256	J/m	65
@0.455 MPa @1.820 MPa	ASTM D648		73 / 62
	ASTM D1003	%	< 1.0
	ASTM D1003	%	87

SK



ECOZEN[®] HB

ISO

Test			
	ASTM D792	-	1.33
	ASTM D955	%	0.2 ~ 0.5
	ASTM D785	R-scale	>115
@	ISO 527	MPa	57
@	ISO 527	MPa	30
@	ISO 527	%	4.0
@	ISO 527	%	300
	ISO 178	MPa	77
	ISO 178	MPa	2,400
@ 23	ISO 180	KJ/m2	4.5
@0.455 MPa @1.820 MPa	ISO 75		74 / 63
	ASTM D1003	%	< 1.0
	ASTM D1003	%	87

SK

