

Zytel® XT70G50HSL BK044A (PRELIMINARY)

ZYTEL® PLUS & XT NYLON RESIN

Zytel® XT70G50HSL BK044A is a 50% glass fiber reinforced, heat stabilized polyamide 66 resin for injection molding.

Product information

Resin Identification	PA66-GF50	ISO 1043
Part Marking Code	>PA66-GF50<	ISO 11469
ISO designation	ISO 16396-PA66,GF50,M1CGHR,S14-160	

Rheological properties

	dry/cond.		
Melt mass-flow rate	9/*	g/10min	ISO 1133
Melt mass-flow rate, Temperature	275/*	°C	
Melt mass-flow rate, Load	5/*	kg	
Viscosity number	145 ^[1] /*	cm³/g	ISO 307, 1628
Moulding shrinkage, parallel	0.2/-	%	ISO 294-4, 2577
Moulding shrinkage, normal	0.8/-	%	ISO 294-4, 2577
Moulding shrinkage, parallel, annealed	0.3/*	%	ISO 294-4
Moulding shrinkage, normal, annealed	1/*	%	ISO 294-4

[1]: sulfuric acid 96% (132 cm³/g in formic acid 90%)

Typical mechanical properties

	dry/cond.		
Tensile modulus	17000/11500	MPa	ISO 527-1/-2
Tensile stress at break, 5mm/min	240/170	MPa	ISO 527-1/-2
Tensile strain at break, 5mm/min	2.6/5	%	ISO 527-1/-2
Flexural modulus	15000/-	MPa	ISO 178
Flexural strength	340/-	MPa	ISO 178
Charpy impact strength, 23°C	90/105	kJ/m²	ISO 179/1eU
Charpy notched impact strength, 23°C	15/19	kJ/m²	ISO 179/1eA
Charpy notched impact strength, -30°C	13/-	kJ/m²	ISO 179/1eA
Poisson's ratio	0.33/0.33		

Thermal properties

	dry/cond.		
Melting temperature, 10°C/min	259/*	°C	ISO 11357-1/-3
Glass transition temperature, 10°C/min	70/20	°C	ISO 11357-1/-3
Temperature of deflection under load, 1.8 MPa	245/*	°C	ISO 75-1/-2
Coefficient of linear thermal expansion (CLTE), parallel	19/*	E-6/K	ISO 11359-1/-2
Coefficient of linear thermal expansion (CLTE), normal	65/*	E-6/K	ISO 11359-1/-2
TGA curve	available		ISO 11359-1/-2

Flammability

FMVSS Class	B	ISO 3795 (FMVSS 302)
Burning rate, Thickness 1 mm	22 mm/min	ISO 3795 (FMVSS 302)

Zytel® XT70G50HSL BK044A (PRELIMINARY)

ZYTEL® PLUS & XT NYLON RESIN

Physical/Other properties

	dry/cond.		
Humidity absorption, 2mm	1.2 / *	%	Sim. to ISO 62
Density	1590 / -	kg/m ³	ISO 1183

Injection

Drying Recommended	yes
Drying Temperature	80 °C
Drying Time, Dehumidified Dryer	2 - 4 h
Processing Moisture Content	≤0.2 %
Melt Temperature Optimum	285 °C
Min. melt temperature	275 °C
Max. melt temperature	295 °C
Mold Temperature Optimum	100 °C
Min. mould temperature	70 °C
Max. mould temperature	120 °C
Ejection temperature	205 °C

Characteristics

Processing	Injection Moulding
Delivery form	Pellets
Additives	Release agent
Special characteristics	Heat stabilised or stable to heat


Automotive

OEM	STANDARD	ADDITIONAL INFORMATION
BMW	GS93016-PA66-GF50	(Highly Heat Aging Resistant)
Valeo	PDTNVC15006 RevE	PA66-GF50 Class 5B

Zytel® XT70G50HSL BK044A (PRELIMINARY)

ZYTEL® PLUS & XT NYLON RESIN


Viscosity-shear rate



Zytel® XT70G50HSL BK044A (PRELIMINARY)

ZYTEL® PLUS & XT NYLON RESIN


Shearstress-shear rate



Zytel® XT70G50HSL BK044A (PRELIMINARY)

ZYTEL® PLUS & XT NYLON RESIN


Dynamic Tensile modulus-temperature (dry)



Zytel® XT70G50HSL BK044A (PRELIMINARY)

ZYTEL® PLUS & XT NYLON RESIN


Stress-strain (dry)



Zytel® XT70G50HSL BK044A (PRELIMINARY)

ZYTEL® PLUS & XT NYLON RESIN


Stress-strain (cond.)



Zytel® XT70G50HSL BK044A (PRELIMINARY)

ZYTEL® PLUS & XT NYLON RESIN


Secant modulus-strain (dry)



Zytel® XT70G50HSL BK044A (PRELIMINARY)

ZYTEL® PLUS & XT NYLON RESIN


Secant modulus-strain (cond.)



Zytel® XT70G50HSL BK044A (PRELIMINARY)

ZYTEL® PLUS & XT NYLON RESIN


Stress-strain (isochronous) 110°C (dry)



Zytel® XT70G50HSL BK044A (PRELIMINARY)

ZYTEL® PLUS & XT NYLON RESIN


Creep modulus-time 110°C (dry)



Zytel® XT70G50HSL BK044A (PRELIMINARY)

ZYTEL® PLUS & XT NYLON RESIN


Tensile modulus-temperature (dry)



Zytel® XT70G50HSL BK044A (PRELIMINARY)

ZYTEL® PLUS & XT NYLON RESIN


Tensile modulus-temperature (cond.)



Zytel® XT70G50HSL BK044A (PRELIMINARY)

ZYTEL® PLUS & XT NYLON RESIN

Tensile Fatigue, 10Hz, R=0.1 @ 2mm (dry)



Zytel® XT70G50HSL BK044A (PRELIMINARY)

ZYTEL® PLUS & XT NYLON RESIN

Chemical Media Resistance

Acids

- ✓ Acetic Acid (5% by mass), 23°C
- ✓ Citric Acid solution (10% by mass), 23°C
- ✓ Lactic Acid (10% by mass), 23°C
- ✗ Hydrochloric Acid (36% by mass), 23°C
- ✗ Nitric Acid (40% by mass), 23°C
- ✗ Sulfuric Acid (38% by mass), 23°C
- ✗ Sulfuric Acid (5% by mass), 23°C
- ✗ Chromic Acid solution (40% by mass), 23°C

Bases

- ✗ Sodium Hydroxide solution (35% by mass), 23°C
- ✓ Sodium Hydroxide solution (1% by mass), 23°C
- ✓ Ammonium Hydroxide solution (10% by mass), 23°C

Alcohols

- ✓ Isopropyl alcohol, 23°C
- ✓ Methanol, 23°C
- ✓ Ethanol, 23°C

Hydrocarbons

- ✓ n-Hexane, 23°C
- ✓ Toluene, 23°C
- ✓ iso-Octane, 23°C

Ketones

- ✓ Acetone, 23°C

Ethers

- ✓ Diethyl ether, 23°C

Mineral oils

- ✓ SAE 10W40 multigrade motor oil, 23°C
- ✓ SAE 10W40 multigrade motor oil, 130°C
- ✓ SAE 80/90 hypoid-gear oil, 130°C
- ✓ Insulating Oil, 23°C
- ✓ Motor oil OS206 304 Ref.Eng.Oil, ISP, 135°C
- ✓ Automatic hypoid-gear oil Shell Donax TX, 135°C
- ✓ Hydraulic oil Pentosin CHF 202, 125°C

Standard Fuels

- ✓ ISO 1817 Liquid 1 - E5, 60°C
- ✓ ISO 1817 Liquid 2 - M15E4, 60°C
- ✓ ISO 1817 Liquid 3 - M3E7, 60°C
- ✓ ISO 1817 Liquid 4 - M15, 60°C
- ✓ Standard fuel without alcohol (pref. ISO 1817 Liquid C), 23°C
- ✓ Standard fuel with alcohol (pref. ISO 1817 Liquid 4), 23°C
- ✓ Diesel fuel (pref. ISO 1817 Liquid F), 23°C
- ✓ Diesel fuel (pref. ISO 1817 Liquid F), 90°C
- ✓ Diesel fuel (pref. ISO 1817 Liquid F), >90°C
- ✓ Diesel EN 590, 100°C

Zytel® XT70G50HSL BK044A (PRELIMINARY)

ZYTEL® PLUS & XT NYLON RESIN

Salt solutions

- ✓ Sodium Chloride solution (10% by mass), 23 °C
- ✗ Sodium Hypochlorite solution (10% by mass), 23 °C
- ✓ Sodium Carbonate solution (20% by mass), 23 °C
- ✓ Sodium Carbonate solution (2% by mass), 23 °C
- ✗ Zinc Chloride solution (50% by mass), 23 °C

Other

- ✓ Ethyl Acetate, 23 °C
- ✗ Hydrogen peroxide, 23 °C
- ✓ DOT No. 4 Brake fluid, 130 °C
- ✓ DOT No. 4 Brake fluid, 120 °C
- ✓ Ethylene Glycol (50% by mass) in water, 108 °C
- ✓ 1% nonylphenoxy-polyethyleneoxy ethanol in water, 23 °C
- ✓ 50% Oleic acid + 50% Olive Oil, 23 °C
- ✓ Water, 23 °C
- ✓ Water, 90 °C
- ✗ Phenol solution (5% by mass), 23 °C

Symbols used:

- ✓ possibly resistant
Defined as: Supplier has sufficient indication that contact with chemical can be potentially accepted under the intended use conditions and expected service life. Criteria for assessment have to be indicated (e.g. surface aspect, volume change, property change).
- ✗ not recommended - see explanation
Defined as: Not recommended for general use. However, short-term exposure under certain restricted conditions could be acceptable (e.g. fast cleaning with thorough rinsing, spills, wiping, vapor exposure).

The above data are preliminary and are subject to change as additional data are developed on subsequent lots.

NOTICE TO USERS: Values shown are based on testing of laboratory test specimens and represent data that fall within the standard range of properties for natural material. These values alone do not represent a sufficient basis for any part design and are not intended for use in establishing maximum, minimum, or ranges of values for specification purposes. Colourants or other additives may cause significant variations in data values. Properties of moulded parts can be influenced by a wide variety of factors including, but not limited to, material selection, additives, part design, processing conditions and environmental exposure. Other than those products expressly identified as medical grade (including by MT® product designation or otherwise), Celanese's products are not intended for use in medical or dental implants. Regardless of any such product designation, any determination of the suitability of a particular material and part design for any use contemplated by the users and the manner of such use is the sole responsibility of the users, who must assure themselves that the material as subsequently processed meets the needs of their particular product or use. To the best of our knowledge, the information contained in this publication is accurate; however, we do not assume any liability whatsoever for the accuracy and completeness of such information. The information contained in this publication should not be construed as a promise or guarantee of specific properties of our products. It is the sole responsibility of the users to investigate whether any existing patents are infringed by the use of the materials mentioned in this publication. Moreover, there is a need to reduce human exposure to many materials to the lowest practical limits in view of possible adverse effects. To the extent that any hazards may have been mentioned in this publication, we neither suggest nor guarantee that such hazards are the only ones that exist. We recommend that persons intending to rely on any recommendation or to use any equipment, processing technique or material mentioned in this publication should satisfy themselves that they can meet all applicable safety and health standards. We strongly recommend that users seek and adhere to the manufacturer's current instructions for handling each material they use, and entrust the handling of such material to adequately trained personnel only. Please call the telephone numbers listed for additional technical information. Call Customer Services for the appropriate Materials Safety Data Sheets (MSDS) before attempting to process our products.

© 2025 Celanese or its affiliates. All rights reserved. Celanese®, registered C-ball design and all other trademarks identified herein with ®, TM, SM, unless otherwise noted, are trademarks of Celanese or its affiliates. Fortron is a registered trademark of Fortron Industries LLC.