



Geon™ CPVC EE105

Chlorinated Polyvinyl Chloride

Key Characteristics

Product Description

Geon EE105 CPVC is an extrusion grade rigid compound ideally suited for a variety of applications. EE105 offers excellent electrical properties, chemical resistance and is designed for applications where enhanced resistance at elevated temperatures is needed. EE105 demonstrates ease of processing with excellent thermal stability. All colors of EE105 are UL certified and are made with virgin materials.

General

Material Status	• Commercial: Active		
Regional Availability	• Africa & Middle East	• Europe	• North America
	• Asia Pacific	• Latin America	
Uses	• Profiles		
Forms	• Pellets		
Processing Method	• Extrusion		

Technical Properties ¹

Physical	Typical Value (English)	Typical Value (SI)	Test Method
Specific Gravity	1.50	1.50	ASTM D792
Mechanical	Typical Value (English)	Typical Value (SI)	Test Method
Tensile Modulus ²			ASTM D638
73°F (23°C), 0.125 in (3.18 mm), Compression Molded	325000 psi	2240 MPa	
Tensile Strength ²			ASTM D638
Yield, 73°F (23°C), 0.125 in (3.18 mm), Compression Molded	7500 psi	51.7 MPa	
Tensile Elongation ²			ASTM D638
Break, 73°F (23°C), 0.125 in (3.18 mm)	24 %	24 %	
Flexural Modulus			ASTM D790
73°F (23°C), 0.125 in (3.18 mm)	350000 psi	2410 MPa	
Flexural Strength			ASTM D790
73°F (23°C), 0.125 in (3.18 mm)	11000 psi	75.8 MPa	
Impact	Typical Value (English)	Typical Value (SI)	Test Method
Drop Impact Resistance ³ (73°F (23°C))	1.50 in-lb/mil	66.7 J/cm	ASTM D4226
Hardness	Typical Value (English)	Typical Value (SI)	Test Method
Durometer Hardness			ASTM D2240
Shore D, 15 sec, 0.125 in (3.18 mm)	80	80	
Thermal	Typical Value (English)	Typical Value (SI)	Test Method
Deflection Temperature Under Load			ASTM D648
66 psi (0.45 MPa), Annealed, 0.125 in (3.18 mm)	232 °F	111 °C	
Deflection Temperature Under Load			ASTM D648
264 psi (1.8 MPa), Annealed, 0.125 in (3.18 mm)	221 °F	105 °C	
CLTE - Flow	4.0E-5 in/in/°F	7.2E-5 cm/cm/°C	ASTM D696
RTI Elec (0.04 to 0.12 in (1.0 to 3.0 mm))	221 °F	105 °C	UL 746
RTI Imp (0.04 to 0.12 in (1.0 to 3.0 mm))	221 °F	105 °C	UL 746
RTI Str (0.04 to 0.12 in (1.0 to 3.0 mm))	221 °F	105 °C	UL 746

Copyright © 2016 PolyOne Corporation. PolyOne makes no representations, guarantees, or warranties of any kind with respect to the Information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the Information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the Information. PolyOne makes no warranties or guarantees respecting suitability of either PolyOne's products or the Information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the Information and/or use or handling of any product. POLYONE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the Information or products reflected by the Information. This data sheet shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.

Electrical	Typical Value (English)	Typical Value (SI)	Test Method
High Amp Arc Ignition (HAI) 0.120 in (3.05 mm)	0.00	0.00	UL 746
Flammability	Typical Value (English)	Typical Value (SI)	Test Method
Flame Rating			UL 94
> 0.04 in (> 1.0 mm)	V-0	V-0	
> 0.06 in (> 1.5 mm)	5VA	5VA	

Processing Information

Extrusion	Typical Value (English)	Typical Value (SI)
Melt Temperature	375 to 390 °F	191 to 199 °C

Notes

¹ Typical values are not to be construed as specifications.

² 2.0 in/min (51 mm/min)

³ Procedure A, C.125

CONTACT INFORMATION

Americas

United States - Avon Lake
+1 440 930 1000

United States - McHenry
+1 815 385 8500

Asia

China - Guangzhou
+86 20 8732 7260

China - Shenzhen
+86 755 2969 2888

China - Suzhou
+86 512 6823 24 38

China - Suzhou
+86 512 6265 2600

Hong Kong -
+852 2690 5332

Taiwan - Yonghe City,
+886 9396 99740, +886 2929 1849

Europe

Germany - Gaggenau
+49 7225 6802 0

Spain - Barbastro (Huesca)
+34 974 310 314



Beyond Polymers.

Better Business Solutions. SM

www.polyone.com

PolyOne Americas

33587 Walker Road
Avon Lake, Ohio 44012
United States
+1 440 930 1000
+1 866 POLYONE

PolyOne Asia

No. 88 Guoshoujing Road
Z.J Hi-tech Park, Pudong
Shanghai, 201203, China
+86 21 5080 1188

PolyOne Europe

6 Giällewee
+352 269 050 35

Copyright ©, 2016 PolyOne Corporation. PolyOne makes no representations, guarantees, or warranties of any kind with respect to the Information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the Information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the Information. PolyOne makes no warranties or guarantees respecting suitability of either PolyOne's products or the Information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the Information and/or use or handling of any product. POLYONE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the Information or products reflected by the Information. This data sheet shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.