



# Geon™ Bold L5000

## Polyvinyl Chloride Alloy

### Key Characteristics

#### Product Description

PVC alloy for dark color capstock, profiles or sheet requiring good weathering in both horizontal (colors with L values greater than 60) and vertical applications. Comes in high gloss but may be customized for an application.

#### General

Material Status	• Commercial: Active		
Regional Availability	• Africa & Middle East • Asia Pacific	• Europe • Latin America	• North America
Features	• Good Chemical Resistance • Good Weather Resistance • High Gloss		
Uses	• Capstock • Construction Applications	• Decorative Railing • Profiles	• Sheet • Windows & Doors
Forms	• Cube		
Processing Method	• Extrusion		

### Technical Properties <sup>1</sup>

Physical	Typical Value (English)	Typical Value (SI)	Test Method
Specific Gravity	1.40	1.40	ASTM D792
Mechanical	Typical Value (English)	Typical Value (SI)	Test Method
Tensile Modulus <sup>2</sup>	328000 psi	2260 MPa	ASTM D638
Tensile Strength <sup>2</sup> (Yield)	6370 psi	43.9 MPa	ASTM D638
Flexural Modulus	361000 psi	2490 MPa	ASTM D790
Flexural Strength	11100 psi	76.6 MPa	ASTM D790
Impact	Typical Value (English)	Typical Value (SI)	Test Method
Notched Izod Impact 73°F (23°C), 0.125 in (3.18 mm), Compression Molded	1.9 ft·lb/in	100 J/m	ASTM D256A
Drop Impact Resistance			ASTM D4226
73°F (23°C) <sup>3</sup>	1.63 in·lb/mil	72.5 J/cm	
73°F (23°C) <sup>4</sup>	> 4.00 in·lb/mil	> 178 J/cm	
Hardness	Typical Value (English)	Typical Value (SI)	Test Method
Durometer Hardness (Shore D, 15 sec)	77	77	ASTM D2240
Thermal	Typical Value (English)	Typical Value (SI)	Test Method
Deflection Temperature Under Load <sup>5</sup> 66 psi (0.45 MPa), Annealed, 0.125 in (3.18 mm)	160 °F	71.0 °C	ASTM D648
Deflection Temperature Under Load <sup>5</sup> 264 psi (1.8 MPa), Annealed	157 °F	69.3 °C	ASTM D648
CLTE - Flow	3.8E-5 in/in/°F	6.8E-5 cm/cm/°C	ASTM D696

#### Additional Information

Note: Physical properties based on Geon Bold L5000 LHB Brown 3481 Lot# 4699345 sample.

### Processing Information

Extrusion	Typical Value (English)	Typical Value (SI)
Melt Temperature	360 to 380 °F	182 to 193 °C

#### Extrusion Notes

Melt flow and downstream calibration similar to standard rigid PVC. Wider processing window allows sheet extrusion.

Copyright © 2015 PolyOne Corporation. PolyOne makes no representations, guarantees, or warranties of any kind with respect to the Information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the Information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the Information. PolyOne makes no warranties or guarantees respecting suitability of either PolyOne's products or the Information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the Information and/or use or handling of any product. POLYONE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the Information or products reflected by the Information. This data sheet shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.

**Notes**

- <sup>1</sup> Typical values are not to be construed as specifications.

---

- <sup>2</sup> Type I, 0.20 in/min (5.1 mm/min)

---

- <sup>3</sup> Procedure A, C.125 Dart

---

- <sup>4</sup> Procedure B, C.125 Dart

---

- <sup>5</sup> Conditioned at 50 deg.C

**CONTACT INFORMATION**

**Americas**

United States - Avon Lake  
+1 440 930 1000

United States - McHenry  
+1 815 385 8500

**Asia**

China - Guangzhou  
+86 20 8732 7260

China - Shenzhen  
+86 755 2969 2888

China - Suzhou  
+86 512 6823 24 38

China - Suzhou  
+86 512 6265 2600

Hong Kong -  
+852 2690 5332

Taiwan - Yonghe City,  
+886 9396 99740, +886 2929 1849

**Europe**

Germany - Gaggenau  
+49 7225 6802 0

Spain - Barbastro (Huesca)  
+34 974 310 314



*Beyond Polymers.*

*Better Business Solutions. SM*

[www.polyone.com](http://www.polyone.com)

**PolyOne Americas**

33587 Walker Road  
Avon Lake, Ohio 44012  
United States  
+1 440 930 1000  
+1 866 POLYONE

**PolyOne Asia**

No. 88 Guoshoujing Road  
Z.J Hi-tech Park, Pudong  
Shanghai, 201203, China  
+86 21 5080 1188

**PolyOne Europe**

6 Giällewee  
+352 269 050 35

Copyright ©, 2015 PolyOne Corporation. PolyOne makes no representations, guarantees, or warranties of any kind with respect to the Information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the Information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the Information. PolyOne makes no warranties or guarantees respecting suitability of either PolyOne's products or the Information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the Information and/or use or handling of any product. POLYONE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the Information or products reflected by the Information. This data sheet shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.