



Geon™ Vinyl Flexible XV3855

Flexible Polyvinyl Chloride

Key Characteristics

Product Description

XV3855 is a flexible (57A durometer) vinyl compound formulated from FDA-santioned raw materials. XV3855 Clear 1869 has been tested to USP Class VI.

General

Material Status	• Commercial: Active		
Regional Availability	• Africa & Middle East • Asia Pacific	• Europe • Latin America	• North America
Uses	• Medical Devices • Medical/Healthcare Applications		
Agency Ratings	• FDA Unspecified Rating		
Appearance	• Clear/Transparent		
Forms	• Pellets		
Processing Method	• Blow Molding		

Technical Properties ¹

Physical	Typical Value (English)	Typical Value (SI)	Test Method
Density / Specific Gravity	1.16	1.16	ASTM D792
Mechanical	Typical Value (English)	Typical Value (SI)	Test Method
Tensile Strength ² (100% Strain)	450 psi	3.10 MPa	ASTM D638
Tensile Strength ² (Break)	1550 psi	10.7 MPa	ASTM D638
Tensile Elongation ² (Break)	490 %	490 %	ASTM D638
Hardness	Typical Value (English)	Typical Value (SI)	Test Method
Durometer Hardness (Shore A, 10 sec)	57	57	ASTM D2240

Additional Information

NOTE: All ingredients used in the formulation of this compound are listed in the United States FDA Code of Federal Regulations, Title 21. The only restriction is that the plasticizer is "For foods of high water content only". This statement is only an overview of the FDA listings for this product. It is the customer's responsibility to ensure that the compound is suitable for its intended application.

Notes

¹ Typical values are not to be construed as specifications.

² Type IV, 20 in/min (510 mm/min)