



## SAFETY DATA SHEET

### North America U.S. GHS Format

Print date: 25-Mar-2015

Revision Number: 2

Revision date: 25-Mar-2015

#### 1. IDENTIFICATION OF THE SUBSTANCE AND COMPANY

<b>Trademark:</b>	LUBRICOMP™
<b>Product Code:</b>	RFL36L - NC
<b>Product Description:</b>	Polyamide 66 [CASRN 32131-17-2] glass fiber filled
<b>Product Type:</b>	Commercial Product
<b>Recommended use:</b>	May be used to produce molded or extruded articles or as a component of other industrial products.
<b>Company:</b>	SABIC Innovative Plastics US LLC One Plastics Avenue Pittsfield, MA 01201 USA (413) 448-5800 www.sabic-ip.com
<b>Manufacturer:</b>	SABIC Innovative Plastics US LLC 251 South Bailey Road Thorndale, Pennsylvania 19372 United States
<b>Emergency Telephone Number:</b>	800/447-4545
<b>Emergency Transportation/CHEMTREC (24 HOUR):</b>	800 424-9300 (USA) +1 703-527-3887 (globally, outside USA)
<b>E-mail:</b>	productinquiries@sabic-ip.com
<b>Website Address:</b>	<a href="http://www.sabic-ip.com">www.sabic-ip.com</a>

## 2. HAZARDS IDENTIFICATION

The additives in this product are bound in a thermoplastic resin matrix. In accordance with GHS for the classification of the product, the hazard potential may be assessed with respect to the physico-chemical form and/or bioavailability of the individual components in the thermoplastic resin.

Where GHS classifications are shown below, these are based on the individual components in the thermoplastic resin matrix. Under the typical use conditions for the resin, these hazardous components are unlikely to contribute to workplace exposure. Please read the entire safety data sheet and/or consult an EHS professional for a complete understanding.

### Classification

#### **OSHA Regulatory Status**

This product is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

### GHS-Labeling

#### **Emergency Overview**

**Not classified**

The product contains no substances which at their given concentration, are considered to be hazardous to health

**Appearance:** Pellets

**Physical State:** Solid

**Odor:** None or slight

#### **Hazards not otherwise classified (HNOC)**

Not applicable

#### **Other Information**

Not applicable

Other hazards which do not result in classification:

#### **SABIC Emergency Overview**

- Pellets with slight or no odor
- Spilled material may create slipping hazard
- Can burn in a fire creating dense, toxic smoke
- Molten plastic can cause severe thermal burns
- Fumes produced during melt processing may cause eye, skin, and respiratory tract irritation. Severe over-exposure may result in nausea, headache, chills, and fever. See below for additional effects.
- Secondary operations, such as grinding, sanding, or sawing can produce dust which may present an explosion or respiratory hazard.

#### **Other Information:**

OSHA, IARC and/or NTP have listed carbon, titanium dioxide, crystalline silica (quartz), respirable glass and certain heavy metals, present in some colorants and fillers, as carcinogens. If these materials are present in this product at significant quantities, they are shown in Section 2/3. These materials are essentially bound to the plastic matrix and are unlikely to contribute to workplace exposure under recommended processing conditions.

#### **Processing Issues:**

Processing vapors may cause irritation to the eyes, skin, and respiratory tract. In cases of severe exposure, nausea and headache can also occur. Grease-like processing vapor condensates on ventilation ductwork, molds, and other surfaces can cause irritation and injury to skin.

**Aggravated Medical Conditions:** MEDICAL RESTRICTIONS: There are no known health effects aggravated by exposure to this product. However, certain sensitive individuals and individuals with respiratory impairments may be affected by exposure to components in the processing vapors.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Product Type** Mixture

**HAZARDOUS COMPONENTS:**

Chemical Name	CAS Number	Weight %
Fiberglass, EU/GHS classified	65997-17-3	30 - 70

The non-hazardous components and exact percentage (concentration) of the composition have been withheld as a trade secret.

This product consists primarily of high molecular weight polymers which are not expected to be hazardous. The ingredients in this product are present within the polymer matrix and are not expected to be hazardous.

### 4. FIRST AID MEASURES

<b>If Inhalation:</b>	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. If symptoms persist, call a physician.
<b>On skin contact:</b>	Immediately cool the skin by rinsing with cold water after contact with hot material. Wash off immediately with soap and plenty of water. Consult a physician.
<b>On contact with eyes:</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. If eye irritation persists, consult a specialist.
<b>On ingestion:</b>	Not probable due to nature of the product. If a large amount of pellet material is swallowed, consult a physician for medical treatment.
<b>Precautions:</b>	Processing vapors inhalation may be irritating to the respiratory tract. If symptoms are experienced remove victim from the source of contamination or move victim to fresh air and obtain medical advice.

## 5. FIRE-FIGHTING MEASURES

<b>Autoignition Temperature:</b>	No information available
<b>Explosive Properties:</b>	Material is not sensitive to mechanical impact, but is sensitive to static discharge under dust cloud conditions.
<b>Suitable Extinguishing Media:</b>	Use dry chemical, CO2, water spray or "alcohol" foam. Water is the best extinguishing medium. Carbon dioxide and dry chemical are not generally recommended because their lack of cooling capacity may permit re-ignition on larger resin fires (blobs, drools, etc.).
<b>Unsuitable Extinguishing Media for Safety Reasons:</b>	Do not use a solid water stream as it may scatter and spread fire.
<b>Hazards from Combustion Products:</b>	Fire will produce dense black smoke containing hazardous combustion products, carbon oxides, hydrocarbon fragments.
<b>Special Protective Equipment for Firefighters:</b>	Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products.
<b>Specific Hazards:</b>	Take precautionary measures against static discharges. During processing, dust may form explosive mixture in air. Thermal decomposition can lead to release of irritating gases and vapors.

## 6. ACCIDENTAL RELEASE MEASURES

<b>Clean up:</b>	Sweep up and shovel into suitable containers for disposal. Do not create a powder cloud by using a brush or compressed air.
<b>Personal Precautions:</b>	See section 8.
<b>Environmental Precautions:</b>	Do not flush into surface water or sanitary sewer system. Material should not be released into the environment.

## 7. HANDLING AND STORAGE

<b>Handling:</b>	Handle in accordance with good industrial hygiene and safety practices. Provide for appropriate exhaust ventilation and dust collection at machinery. Avoid dust formation. All metal parts of the mixing and processing equipment must be earthed.
<b>Storage:</b>	Store in closed container in a dry and cool area. Keep away from heat sources and sources of ignition.
<b>Incompatible Products:</b>	No special restrictions on storage with other products.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Exposure limits:**

No components with information, unless noted below

Chemical Name	US OSHA PEL (8 Hr)	ACGIH	Canada - Alberta (8 Hr)	Mexico OEL Data	SABIC Recommend (8 Hr)*
Fiberglass, EU/GHS classified 65997-17-3	No Information	Inhalable fraction - TWA: 5 mg/m <sup>3</sup> ; Notations: Not Classifiable as a Human Carcinogen ; Crit Eff: Upper respiratory tract irritation ~cr~Respirable fibers - TWA: 1 f/cc ; Notations: Not Classifiable as a Human Carcinogen Respirable fibers - Crit Eff: Upp	OEL_8 hr: 1 f/cc OEL_Ceiling: 1 f/cc	LMPE-PPT: 10 mg/m <sup>3</sup> polvo	No Information

*\*SABIC Recommended Exposure Limits have been established for certain chemicals.*

**Engineering Measures to Exposure:**

Handle in accordance with good industrial hygiene and safety practice. Provide for appropriate exhaust ventilation at machinery. Processing fume condensate may be a fire hazard and toxic; remove periodically from exhaust hoods, ductwork, and other surfaces using appropriate personal protection. In the case of hazardous fumes, wear self-contained breathing apparatus. Wear face-shield and protective suit for abnormal processing problems. Handle in accordance with good industrial hygiene and safety practice for diagnostics. Provide appropriate exhaust ventilation at machinery and at places where dust can be generated.

**Hand Protection:**

Protective gloves should be worn

**Eye Protection:**

Safety glasses with side-shields or chemical goggles. In addition, use full-face shield when cleaning processing vapor condensates from hood, ducts, and other surfaces.

**Respiratory Protection:**

When using this product at elevated temperatures, implement engineering systems, administrative controls or a respiratory protection program (including a respirator approved for protection from organic vapors, acid, gases, and particulate matter) if processing vapors are not adequately controlled or operators experience symptoms of overexposure. If dust or powder are produced from secondary operations such as sawing or grinding, use a respirator approved for protection from dust.

**Body Protection:**

Long sleeved clothing

**Hygiene Measures:**

When using, do not eat, drink or smoke.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<p><b>Physical State:</b></p> <p><b>Appearance:</b></p> <p><b>Color:</b></p> <p><b>Odor:</b></p> <p><b>Odor Threshold:</b></p> <p><b>pH</b></p> <p><b>Boiling point/range:</b></p> <p><b>Melting point/range:</b></p> <p><b>Autoignition Temperature:</b></p> <p><b>Flash Point:</b></p> <p><b>Flammability (solid, gas):</b></p> <p><b>Vapor Pressure:</b></p> <p><b>Water Solubility:</b></p> <p><b>Partition coefficient:</b> (n-octanol/water)</p> <p><b>Vapor Density:</b></p> <p><b>Evaporation Rate:</b></p> <p><b>Decomposition temp. (°C) :</b></p> <p><b>Specific gravity:</b></p> <p><b>VOC content (%):</b></p> <p><b>Explosive Limits</b></p> <p style="padding-left: 100px;"><b>upper:</b></p> <p style="padding-left: 100px;"><b>lower:</b></p>	<p>Solid</p> <p>Pellets</p> <p>Same as color code</p> <p>None or slight</p> <p>No information available</p> <p>No data available</p> <p>Not determined</p> <p>This product does not exhibit a sharp melting point but softens gradually over a wide range of temperatures.</p> <p>No information available</p> <p>The product is not flammable</p> <p>No information available</p> <p>Negligible</p> <p>Insoluble</p> <p>No information available</p> <p>Not determined</p> <p>Negligible</p> <p>Not determined</p> <p>&gt;1; (water = 1)</p> <p>Negligible</p> <p>Not determined</p> <p>Not determined</p>
--	--

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable under ambient conditions. Hazardous polymerization does not occur.
<b>Conditions to Avoid:</b>	To avoid thermal decomposition, avoid elevated temperatures. Heating can result in the formation of gaseous decomposition products, some of which may be hazardous. Do not exceed melt temperature recommendations in product literature. Purgings of hot material should be collected in small, flat, thin shapes and quenched with water to allow for rapid cooling. Do not allow product to remain in barrel at elevated temperatures for extended periods of time.
<b>Materials to avoid:</b>	If polyacetal and polyoxymethylene resin is molded or handled in your equipment, this material can rapidly decompose at the temperatures to process this resin. Inadvertent contamination of this resin with polyacetal resin from the material handling system of other equipment can result in rapid, possibly violent, release of decomposition fumes when the contaminated material is brought to molding temperature. To avoid, thoroughly clean molding equipment with purging compound prior to product changeover and prevent cross contamination of material handling systems.
<b>Hazardous Decomposition Products:</b>	Process vapors under recommended processing conditions may include trace levels of hydrocarbons, carbon oxides, nitrogen oxides (NO <sub>x</sub> ), ammonia, hydrogen cyanide (hydrocyanic acid), aldehydes, cyclopentanone, sulfur oxides, hydrogen fluoride, carbonyl fluoride, perfluorohydrocarbon fragments.
<b>Incompatible Products:</b>	None known

## 11. TOXICOLOGICAL INFORMATION

### Acute Toxicity

<b>LD50/oral/rat:</b>	>5000 mg/kg
<b>LD50/dermal/rabbit:</b>	>2000 mg/kg
<b>Inhalation:</b>	Pellet inhalation unlikely due to physical form. Irritating to respiratory system; avoid inhalation of dusts.
<b>Eye Contact:</b>	Resin particles, like other inert materials, are mechanically irritating to eyes.
<b>Skin Contact:</b>	Not a hazard with pellets during normal industrial use. Contact causes skin irritation.
<b>Ingestion:</b>	Pellet ingestion unlikely due to physical form.
<b>Chronic Toxicity:</b>	No information available.
<b>Subchronic Toxicity:</b>	No information available
<b>Primary Irritation:</b>	Substance does not generally irritate and is only mildly irritating to the skin. Skin irritation.
<b>IARC:</b>	Not listed
<b>OSHA:</b>	Not regulated
<b>NTP:</b>	Not tested
<b>Remarks:</b>	The toxicological data has been taken from products of similar composition.
<b>Special Studies:</b>	<p>No Information</p> <p>Thermal degradation of the fluoropolymer additives in this product may result in the release of pyrolysis products and fumes. Short term inhalation exposure may cause influenza-like symptoms such as chest pain/tightness, shortness of breath, sore throat, fever and chills, malaise and sometimes headache (also known as "polymer fume fever"). Following removal from exposure, complete resolution is expected within 12-48 hours. Prolonged and repeated exposure to high levels may lead to effects such as pulmonary edema and lung disease.</p>

## 12. ECOLOGICAL INFORMATION

<b>Ecotoxicity Effects:</b>	Do not flush into surface water or sanitary sewer system.
<b>Other information:</b>	Ecological damages are not known or expected under normal use.

### 13. DISPOSAL CONSIDERATIONS

<b>Waste from residues / unused products:</b>	Where possible recycling is preferred to disposal or incineration. Dispose of in accordance with local regulations.
<b>Contaminated Packaging:</b>	Empty containers should be taken for local recycling, recovery or waste disposal.
<b>Waste Disposal:</b>	Recycling is encouraged. Landfill or incinerate in accordance with federal, state and local requirements. Collected processing fume condensates and incinerator ash should be tested to determine waste classification.

### 14. TRANSPORT INFORMATION

**Transport Classification:** Not regulated as hazardous for shipment, unless noted below, under current transportation guidelines.

DOT

ADR/RID/ADN

IMDG

ICAO

IATA-DGR

MEXICO

CANADA/TDG

### 15. REGULATORY INFORMATION

**International Inventories:**

<b>TSCA (USA):</b>	Listed
<b>DSL (Canada):</b>	Listed
<b>EINECS/ELINCS (Europe):</b>	Listed
<b>ENCS (Japan):</b>	Listed
<b>IECSC (China):</b>	Listed
<b>KECL (Korea):</b>	Listed
<b>PICCS (Philippines):</b>	Listed
<b>AICS (Australia):</b>	Listed
<b>NZIoC (New Zealand):</b>	Listed

**Other Inventory Information:**

A "Listed" entry above means all chemical components are on the respective inventory list and/or a qualifying exemption exists for one or more components. A "Not listed" entry above indicates one or more components is restricted from import or manufacture into that country/region. Articles are exempt from registration and are therefore not listed on the national chemical inventories.

**SVHC (REACH Regulation (EC) No 1907/2006 and 453/2010, as amended):**

This product does not intentionally contain SVHC chemicals except as noted below. Incidental amounts of impurities, if present, would be below the threshold limit of 0.1% by weight.

**SARA (313) Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA):**

This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

**SARA (311, 312) hazard class:**

Acute Health Hazard	N
Chronic Health Hazard	N
Fire Hazard	N
Sudden Release of Pressure Hazard	N
Reactive Hazard	N

**Canada - WHMIS Classification:**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR. Unless noted below, this product is non-controlled. Some classifications may not apply to the entire product.

**California Proposition 65:**

Components in this product known to the State of California to cause cancer and/or reproductive effects, are listed below:

Chemical Name	Weight %	California Proposition 65:
Fiberglass, EU/GHS classified 65997-17-3	30 - 70	Listed: July 1, 1990 Carcinogenic. (airborne, unbound particles of respirable size)

**RoHS EU Directive 2011/65/EU:**

The subject product is in compliance with EU RoHS Directive 2011/65/EU. All below chemicals are not employed in the manufacture of the product: a.Cadmium and its compounds, b.Lead and its compounds, c.Mercury and its compounds, d.Hexavalent chromium compounds, e.Polybrominated biphenyls (PBBs), f.Polybrominated diphenyl ethers (PBDEs including Deca-BDE). The trace levels of heavy metals may be present as impurities within threshold limits (<0.1% for Pb, Hg, Cr VI, and <0.01% for Cd). We are disclosing this information, to the best of our knowledge, based upon data from our raw material manufacturers.

**HMIS Rating**

Health: 0

Flammability: 1

Reactivity: 0

## 16. OTHER INFORMATION

**SABIC and brands marked with ™ are trademarks of SABIC or its subsidiaries or affiliates.**

Visit our public website to search, view and print Safety Data Sheets for commercial products:

<http://eur.sabic-ip.com/ordeur/pages/msds/MSDSSearch.jsp?app=sabic-ip>

**SDS Scope:**

USA: Conforms to 29 CFR 1910.1200 (2012 OSHA Hazard Communication Standard)

This document is also applicable in other countries and regions.

**Prepared by:** Product Stewardship & Toxicology

**Reason for revision:** Update to GHS format

DISCLAIMER: This Safety Data Sheet [SDS] information is provided based on the Hazard Communication Regulations for your region or country and for the use of the persons required to receive this information under those regulations. The information is neither designed nor recommended for any other use or for use by any other person, including for compliance with other laws. SABIC Innovative Plastics does not warrant the suitability for use of this SDS for any other material or product not specifically identified herein. SABIC Innovative Plastics does not warrant the accuracy or authenticity of this SDS unless it has been obtained directly from SABIC Innovative Plastics, or posted or viewed on a SABIC Innovative Plastics website. Modification of this SDS, unless specifically authorized by SABIC Innovative Plastics, is strictly prohibited. This SDS is based on information that is believed to be reliable, but may be subject to change as new information becomes available. Because it is not possible to anticipate all conditions of use, additional safety precautions may be required. Since the use of this material is not under SABIC Innovative Plastics' control, each user is responsible for making its own determination as to the safe and proper handling of this material in its own particular use of this material. SABIC INNOVATIVE PLASTICS MAKES NO REPRESENTATION OR WARRANTY, EITHER EXPRESS OR IMPLIED, INCLUDING AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Each user should read and understand this information and incorporate it into individual site safety programs as required by applicable hazard communication standards and regulations.

**End of Safety Data Sheet**