

SAFETY DATA SHEET

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier	UBESTA 3030JI26L Polyamide 12 CAS No.: 24937-16-4
1.2 Relevant identified uses of the substance or mixture and uses advised against	Relevant Identified uses: Extrusion, Injection etc. Uses advised against: MEDICAL APPLICATIONS such as any implantation in the human body or any contact with internal body fluids/tissues are PROHIBITED, since compliance with medical regulations is not assured.
1.3 Details of the supplier of the safety data sheet	UBE Corporation Performance Polymers & Chemicals Division, Nylon Polymer Business Department / Composite Business Department Seavans North Building, 1-2-1 Shibaura Minato-ku, Tokyo 105-8449, Japan (Nylon Polymer Business Department) / Urbannet Nagoya Buliding, 1-1-10, Higashisakura, Higashi-ku, Nagoya, Aichi 461-0005, Japan (Composite Business Department) Telephone: +81-3-5419-6173 (Nylon Polymer Business Department) / +81-52-961-1373 (Composite Business Department) Telefax: +81-3-5419-6254 (Nylon Polymer Business Department) / +81-52-961-1379 (Composite Business Department) E-mail: msds_nylon@ube.com
1.4 Emergency telephone number	UBE Corporation Telephone: +81-3-5419-6173 / +81-52-961-1373 (within business hours)

Section 2: Hazards identification

2.1 Classification of the substance or mixture	
GHS classification	This product is not classified as hazardous under GHS.
2.2 Label elements	
Hazard pictograms	None
Signal word	None
Hazard statements	None
Precautionary statements	
Prevention response	None
storage	None
disposal	None
Supplemental information (EU)	Hazard Not applicable



Unsuitable extinguishing media	None
5.2 Special hazards arising from the substance or mixture	May produce harmful gasses, primary CO, CO ₂ and small amount of HCN and NH ₃ .
5.3 Advice for firefighters	Remove containers from fire and cool them with water spray. Firefighters should wear an approved self-contained breathing apparatus and full protective clothing. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures	For large-scale spills, ensure full personal protection is worn (see Section 8). Stop leak if possible without personal risk.
6.2 Environmental precautions	Prevent from contaminating soil and/or from entering, sewage, drainage systems and/or bodies of water.
6.3 Methods and material for containment and cleaning up	Sweep up to prevent slipping on polymer pellets and collect into suitable containers for disposal.
6.4 Reference to other sections	For recommended personal protective equipment, see Section 8. For disposal considerations, see Section 13.

Section 7: Handling and storage

7.1 Precautions for safe handling	At molding process, avoid inhalation of vapours from machine and contacting with molten polymer. Reinforcing material and polymer dust may cause irritation and redness of skin and eye. After handling, wash with soap and plenty of clean water. Not to eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas.
7.2 Conditions for safe storage, including any incompatibilities	In case of pellet, transfer of polymer pellets will produce static electricity. This should be reduced or eliminated as much as possible since they provide a source of ignition for flammable vapour or gasses that may be present in an industrial area or can shock operators.
7.3 Specific end use(s)	No additional information available.

Section 8: Exposure controls/personal protection

8.1 Control parameters

JP limit values	Not available
US limit values (ACGIH)	Not available
Other: human health (DNELs)	As BBSA: (workers) 2,5 mg/m ³ , Inhalative, DNEL (Long-term exposure – systemic effects) (General population) 0,26 mg/kg bw/day, Oral, DNEL(Systemic effects-Long-term) 0,45 mg/m ³ , Inhalative, DNEL(Systemic effects-Long-term exposure)



Other: environmental (PNEC)	As BBSA: 0,037 mg/l, PNEC (freshwater) 0,0037 mg/l, PNEC (marine water) 0,37 mg/l, PNEC (intermittent, release) 0,091 mg/kg d.w, PNEC (soil) 60 mg/L, PNEC (STP) 0,563 mg/kg sed, PNEC sediment (freshwater) 0,056 mg/kg sed, PNEC sediment (marine water)
-----------------------------	---

8.2 Exposure controls

Appropriate engineering controls	Adequate ventilation should be maintained at handing. Additionally, local exhaust ventilation recommended at molding process.
Personal protection equipment	<p><u>Eye/face protection</u>: Safety goggles should be worn. At treating hot polymer or molding, face shield should be recommended.</p> <p><u>Skin protection</u>: Safety shoes or boots. Chemical resistant clothes</p> <p><u>Hand protection</u>: Unnecessary under normal processing.</p> <p><u>Other</u>: Unnecessary under normal processing.</p> <p><u>Respiratory protection</u>: Unnecessary under normal processing.</p> <p><u>Thermal hazards</u>: At treating hot polymer or molding process, heat-resistant leather gloves should be required, and face shield should be recommended. Wear a respirator conforming to EN140 at least with Type A filter.</p>
Environmental exposure controls	Refer to Section 6.

Section 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	Black pellets
Odour	Slight odour
Odour threshold	Not applicable.
pH	Not applicable
Melting point / freezing point	Not determined for mixture. 173 - 183 °C (PA 12)
Initial boiling point and boiling range	Not tested
Flash point	Not tested
Evaporation rate	Not applicable for solid
Flammability (solid, gas)	As a mixture: non-flammable; In conformity with United Nations Recommendations 4.1 Burning rate test.
Upper/lower flammability. or explosive limits	Not applicable for solid
Vapour pressure	Not applicable for solid
Vapour density	Not applicable for solid
Relative density	Not determined for mixture. 1.01-1.02 (PA12)
Solubility(ies)	Water solubility: Negligible
Partition coefficient: n-octanol/water	Not applicable
Auto-ignition temperature	As a mixture: not self-igniting 330 °C (PA12). In conformity with United Nations Recommendations 4.2 Spontaneous combustion test.



Decomposition temperature	Not tested
Viscosity	Not applicable for solid
Explosive properties	Not explosive
Oxidising properties	Not oxidising
9.2 Other information	No additional information available

Section 10: Stability and reactivity

10.1 Reactivity	No additional information available.
10.2 Chemical stability	Stable under recommended storage and handling conditions.
10.3 Possibility of hazardous reactions	No additional information available.
10.4 Conditions to avoid	Avoid heat, flames, sparks and other sources of ignition and high temperature.
10.5 Incompatible materials	Strong acids, bases and oxidizing agents
10.6 Hazardous decomposition products	Primary CO, CO ₂ and small amount of HCN, NH ₃

Section 11: Toxicological information

11.1 Information on toxicological effects

Mixture

Acute toxicity	ATEmix (oral-rat) = 38430 mg/kg ATEmix (dermal-rabbit) = 44174 mg/kg ATEmix (inhalation-rat) = 1425 mg/L/4 h (vapours)
Skin corrosion/irritation	Not classified (Lack of data)
Serious eye damage/irritation	Not classified (Lack of data)
Respiratory or skin sensitisation	Not classified (Lack of data)
Germ cell mutagenicity	Not classified (Lack of data)
Carcinogenicity	Not classified (Lack of data)
Reproductive toxicity	Not classified (Lack of data)
STOT-single exposure	Not classified (Lack of data)
STOT-repeated exposure	Not classified (Lack of data)
Aspiration hazard	Not classified (Lack of data)

Components

BBSA

Acute toxicity	Not classified (Based on available data, the classification criteria are not met) LD ₅₀ (oral-rat) = 2070 mg/kg LD ₅₀ (dermal-rat) > 2000mg/kg LC ₅₀ (inhalation/rat) > 4.066 mg/L/4h(aerosol)
Skin corrosion/irritation	Not classified (Based on available data, the classification criteria are not met) pH: 7,5-8,5
Serious eye damage/irritation	Not classified (Lack of data) pH: 7,5-8,5



STOT-repeated exposure

May cause damage to Liver through prolonged or repeated exposure.
 NOAEL (subacute,oral,animal/male,28 days) = 50 mg/kg bodyweight
 NOAEL (subacute,oral,animal/female,28 days) = 50 mg/kg bodyweight
 NOAEL (dermal, animal/ rat, 28 days) > 1000 mg/kg bw/day

Section 12: Ecological information

12.1 Toxicity	Mixture: No information available Components: <u>BBSA:</u> Fish 96h-LC ₅₀ (Danio rerio) > 38 mg/L Aquatic invertebrates 48h-EC ₅₀ (Daphnia magna) = 56 mg/L Algae 72h-EC ₅₀ (Selenastrum-Capricornutum - Alage) = 49 mg/L
12.2 Persistence and degradability	Mixture: No information available. Components: <u>BBSA:</u> Not readily biodegradable. (Hydrolysis as a function of pH) > 90% Recovery after 5days @ pH 4 & 50°C > 90% Recovery after 5days @ pH 7 & 50°C > 90% Recovery after 5days @ pH 9 & 50°C
12.3 Bioaccumulative potential	Mixture: No information available. Components: <u>BBSA:</u> Log Pow 2.01 (20-25°C) No indication of bio-accumulation potential
12.4 Mobility in soil	No additional information available
12.5 Other adverse effects	No information available.

Section 13: Disposal considerations

13.1 Waste treatment methods	Disposal must be in accordance with current national and local regulations, which may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Chemical residues generally count as special waste. Packaging may contain residues of the product and should be treated accordingly. Do not dump this material into sewers, on the ground, or into any body of water.
-------------------------------------	--

Section 14: Transport information

14.1 UN Number	The mixture is not classified.
14.2 UN proper shipping name	The mixture is not classified.
14.3 Transport hazard class(es)	The mixture is not classified.
14.4 Packing group	The mixture is not classified.
14.5 Environmental hazards	Not classified as environmentally hazardous
14.6 Special precautions for user	No dangerous good in sense of transport regulations.



14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable

Section 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Please refer to any other regulations of each country.

Section 16: Other information

Indication of changes	Revisions: 01. April. 2022 Section 1.
Abbreviations and acronyms	GHS: Globally Harmonized System of Classification and Labelling of Chemicals ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short-term Exposure Limit DNEL: Derived No Effect Level PNEC: Predicted No Effect Concentration ATE: Acute Toxicity Estimate LD50: Median(50%) lethal dose IARC: International Agency for Research on Cancer EC50: Median Effect Concentration IC50: Half maximal (50%) inhibitory concentration LC50: Median(50%) lethal concentration NOEC: No Observed Effect Concentration OECD: Organization for Economic Cooperation and Development
Full text of hazard class and category codes	Hazardous to the aquatic environment, long-term hazard, Hazard category 3, H412: Harmful to aquatic life with long lasting effects.
Training advice	Read this Safety Data Sheet before handling the substance.

Disclaimer: This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of UBE Corporation. The data on this sheet related only the specific material designated herein. UBE Corporation assumes no legal responsibility for use or reliance upon these data.

