

# SAFETY DATA SHEET

## Section 1: Identification of the substance/mixture and of the company/undertaking

<b>1.1 Product identifier</b>	UBESTA 3030JI5L Polyamide 12 CAS No.: 24937-16-4
<b>1.2 Relevant identified uses of the substance or mixture and uses advised against</b>	Relevant Identified uses: Extrusion, Injection etc. Uses advised against: MEDICAL APPLICATIONS such as any implantation in the human body or any contact with internal body fluids/tissues are PROHIBITED, since compliance with medical regulations is not assured.
<b>1.3 Details of the supplier of the safety data sheet</b>	UBE Corporation Performance Polymers & Chemicals Division, Nylon Polymer Business Department / Composite Business Department Seavans North Building, 1-2-1 Shibaura Minato-ku, Tokyo 105-8449, Japan (Nylon Polymer Business Department) / Urbannet Nagoya Buliding, 1-1-10, Higashisakura, Higashi-ku, Nagoya, Aichi 461-0005, Japan (Composite Business Department)  Telephone: +81-3-5419-6173 (Nylon Polymer Business Department) / +81-52-961-1373 (Composite Business Department) Telefax: +81-3-5419-6254 (Nylon Polymer Business Department) / +81-52-961-1379 (Composite Business Department) E-mail: <a href="mailto:msds_nylon@ube.com">msds_nylon@ube.com</a>
<b>1.4 Emergency telephone number</b>	UBE Corporation Telephone: +81-3-5419-6173 / +81-52-961-1373 (within business hours)

## Section 2: Hazards identification

<b>2.1 Classification of the substance or mixture</b>	GHS classification	This product is not classified as hazardous under GHS.
<b>2.2 Label elements</b>	Hazard pictograms	
	Signal word	None
	Hazard statements	None
	Precautionary statements	
	Prevention response storage disposal	None None None None
	Supplemental Hazard information (EU)	Not applicable
<b>2.3 Other hazards</b>		None known



## Section 3: Composition/information on ingredients

### 3.1 Mixture

Ingredient name	Conc. (%)	EC No.	CAS No.	Classification according to GHS <sup>*1)</sup>
Polyamide 12	> 78	- (Polymer)	24937-16-4	not classified
N-Butylbenzenesulphonamide (BBSA)	< 12	222-823-6	3622-84-2	Aquatic Chronic 3, H412
Modifier	< 7	-	(Polymer)	not classified
Carbon black	< 1	215-609-9	1333-86-4	not classified
Others	< 2	-	-	not classified

\*1) See Section 16 for full text of hazard class and category codes.

## Section 4: First aid measures

### 4.1 Description of first aid measures

General advice	Move out of dangerous area. Take off all contaminated clothing immediately. Obtain immediate medical attention in case of severe exposure, even if the exposed person has no symptom. Show this safety data sheet to the doctor in attendance.
Inhalation	If exposed to vapors from heating and molding material, remove to fresh air. If symptoms, coughing and discomfort in nose and throat remain, get medical attention.
Skin contact	Wash material off skin with plenty of water and soap. If redness, itching or burning sensation develops, get medical attention. If molten polymer contacts skin, cool immediately with cold and clean water. Do not attempt to peel the solidified polymer from skin, and get medical attention for thermal burn.
Eye contact	Immediately flush with plenty of clean water for at least 15 minutes. If redness, itching or burning sensation develops, do not rub eyes and immediately get medical attention.
Ingestion	If swallowed, wash out mouth thoroughly and give water to drink. Seek immediate medical attention. Speed is essential. Do not induce vomiting, unless instructed by medical personnel.

**4.2 Most important symptoms and effects, both acute and delayed** At molten state, expected to cause burns to skin. Irreversible dermatitis will occur if you do not wash affected skin immediately and thoroughly.

**4.3 Indication of any immediate medical attention and special treatment needed** Not available.

## Section 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media Water, dry chemical and carbon dioxide



Unsuitable extinguishing media	None
<b>5.2 Special hazards arising from the substance or mixture</b>	May produce harmful gasses, primary CO, CO2 and small amount of HCN and NH3.
<b>5.3 Advice for firefighters</b>	Remove containers from fire and cool them with water spray. Firefighters should wear an approved self-contained breathing apparatus and full protective clothing. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

---

**Section 6: Accidental release measures**

---

<b>6.1 Personal precautions, protective equipment and emergency procedures</b>	For large-scale spills, ensure full personal protection is worn (see Section 8). Stop leak if possible without personal risk.
<b>6.2 Environmental precautions</b>	Prevent from contaminating soil and/or from entering, sewage, drainage systems and/or bodies of water.
<b>6.3 Methods and material for containment and cleaning up</b>	Sweep up to prevent slipping on polymer pellets and collect into suitable containers for disposal.
<b>6.4 Reference to other sections</b>	For recommended personal protective equipment, see Section 8. For disposal considerations, see Section 13.

---

**Section 7: Handling and storage**

---

<b>7.1 Precautions for safe handling</b>	At molding process, avoid inhalation of vapours from machine and contacting with molten polymer. Reinforcing material and polymer dust may cause irritation and redness of skin and eye. After handling, wash with soap and plenty of clean water. Not to eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas.
<b>7.2 Conditions for safe storage, including any incompatibilities</b>	In case of pellet, transfer of polymer pellets will produce static electricity. This should be reduced or eliminated as much as possible since they provide a source of ignition for flammable vapour or gasses that may be present in an industrial area or can shock operators.
<b>7.3 Specific end use(s)</b>	No additional information available.

---

**Section 8: Exposure controls/personal protection**

---

**8.1 Control parameters**

JP limit values	Not available
US limit values (ACGIH)	Not available
Other: human health (DNELs)	As BBSA: (workers) 2,5 mg/m <sup>3</sup> , Inhalative, DNEL (Long-term exposure – systemic effects) (General population) 0,26 mg/kg bw/day, Oral, DNEL(Systemic effects-Long-term) 0,45 mg/m <sup>3</sup> , Inhalative, DNEL(Systemic effects-Long-term exposure)
Other: environmental (PNEC)	As BBSA: 0,037 mg/l, PNEC (freshwater)



0,0037 mg/l, PNEC (marine water)  
 0,37 mg/l, PNEC (intermittent, release)  
 0,091 mg/kg d.w, PNEC (soil)  
 60 mg/L, PNEC (STP)  
 0,563 mg/kg sed, PNEC sediment (freshwater)  
 0,056 mg/kg sed, PNEC sediment (marine water)

## 8.2 Exposure controls

Appropriate engineering controls	Adequate ventilation should be maintained at handling. Additionally, local exhaust ventilation recommended at molding process.
Personal protection equipment	<p><u>Eye/face protection</u>: Safety goggles should be worn. At treating hot polymer or molding, face shield should be recommended.</p> <p><u>Skin protection</u>: Safety shoes or boots. Chemical resistant clothes</p> <p><u>Hand protection</u>: Unnecessary under normal processing.</p> <p><u>Other</u>: Unnecessary under normal processing.</p> <p><u>Respiratory protection</u>: Unnecessary under normal processing.</p> <p><u>Thermal hazards</u>: At treating hot polymer or molding process, heat-resistant leather gloves should be required.</p>
Environmental exposure controls	Refer to Section 6.

## Section 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance	Black pellets
Odour	Slight odour
Odour threshold	Not applicable.
pH	Not applicable
Melting point / freezing point	Not determined for mixture. 173 - 183 °C (PA 12)
Initial boiling point and boiling range	Not tested
Flash point	Not tested
Evaporation rate	Not applicable for solid
Flammability (solid, gas)	As a mixture: non-flammable In conformity with United Nations Recommendations 4.1 Burning rate test.
Upper/lower flammability or explosive limits	Not applicable for solid
Vapour pressure	Not applicable for solid
Vapour density	Not applicable for solid
Relative density	Not determined for mixture. 1.01-1.02 (PA12)
Solubility(ies)	Water solubility: Negligible
Partition coefficient: n-octanol/water	Not applicable
Auto-ignition temperature	As a mixture: not self-igniting 330 °C (PA12). In conformity with United Nations Recommendations 4.2 Spontaneous combustion test.
Decomposition temperature	Not tested
Viscosity	Not applicable for solid
Explosive properties	Not explosive



Oxidising properties	Not oxidising
<b>9.2 Other information</b>	No additional information available

**Section 10: Stability and reactivity**

<b>10.1 Reactivity</b>	No additional information available.
<b>10.2 Chemical stability</b>	Stable under recommended storage and handling conditions.
<b>10.3 Possibility of hazardous reactions</b>	No additional information available.
<b>10.4 Conditions to avoid</b>	Avoid heat, flames, sparks and other sources of ignition and high temperature.
<b>10.5 Incompatible materials</b>	Strong acids, bases and oxidizing agents
<b>10.6 Hazardous decomposition products</b>	Primary CO, CO <sub>2</sub> and small amount of HCN, NH <sub>3</sub>

**Section 11: Toxicological information**

**11.1 Information on toxicological effects**

Mixture

Acute toxicity	ATEmix (oral-rat) = 20374 mg/kg ATEmix (dermal-rabbit) = 23730 mg/kg ATEmix (inhalation-rat) = 1478 mg/L/4 h (vapours)
Skin corrosion/irritation	Not classified (Lack of data)
Serious eye damage/irritation	Not classified (Lack of data)
Respiratory or skin sensitisation	Not classified (Lack of data)
Germ cell mutagenicity	Not classified (Lack of data)
Carcinogenicity	Not classified (Lack of data)
Reproductive toxicity	Not classified (Lack of data)
STOT-single exposure	Not classified (Lack of data)
STOT-repeated exposure	Not classified (Lack of data)
Aspiration hazard	Not classified (Lack of data)

Components

BBSA

Acute toxicity	Not classified (Based on available data, the classification criteria are not met) LD <sub>50</sub> (oral-rat) = 2070 mg/kg LD <sub>50</sub> (dermal-rat) > 2000mg/kg LC <sub>50</sub> (inhalation/rat) > 4.066 mg/L/4h(aerosol)
Skin corrosion/irritation	Not classified (Based on available data, the classification criteria are not met) pH: 7,5-8,5
Serious eye damage/irritation	Not classified (Lack of data) pH: 7,5-8,5
STOT-repeated exposure	May cause damage to Liver through prolonged or repeated exposure. NOAEL (subacute,oral,animal/male,28 days) = 50 mg/kg bodyweight NOAEL (subacute,oral,animal/female,28 days) = 50 mg/kg bodyweight



NOAEL (dermal, animal/ rat, 28 days) > 1000 mg/kg bw/day

## Section 12: Ecological information

<b>12.1 Toxicity</b>	Mixture: No information available
<b>12.2 Persistence and degradability</b>	Components: <u>BBSA:</u> Fish 96h-LC <sub>50</sub> (Danio rerio) > 38 mg/L Aquatic invertebrates 48h-EC <sub>50</sub> (Daphnia magna) = 56 mg/L Algae 72h-EC <sub>50</sub> (Selenastrum-Capricornutum - Alage) = 49 mg/L
<b>12.3 Bioaccumulative potential</b>	Mixture: No information available. Components: <u>BBSA:</u> Not readily biodegradable. (Hydrolysis as a function of pH) > 90% Recovery after 5days @ pH 4 & 50°C > 90% Recovery after 5days @ pH 7 & 50°C > 90% Recovery after 5days @ pH 9 & 50°C
<b>12.4 Mobility in soil</b>	Mixture: No information available. Components: <u>BBSA:</u> Log Pow 2.01 (20-25°C) No indication of bio-accumulation potential
<b>12.5 Other adverse effects</b>	No additional information available
<b>12.5 Other adverse effects</b>	No information available.

## Section 13: Disposal considerations

<b>13.1 Waste treatment methods</b>	Disposal must be in accordance with current national and local regulations, which may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Chemical residues generally count as special waste. Packaging may contain residues of the product and should be treated accordingly. Do not dump this material into sewers, on the ground, or into any body of water.
-------------------------------------	--

## Section 14: Transport information

<b>14.1 UN Number</b>	The mixture is not classified.
<b>14.2 UN proper shipping name</b>	The mixture is not classified.
<b>14.3 Transport hazard class(es)</b>	The mixture is not classified.
<b>14.4 Packing group</b>	The mixture is not classified.
<b>14.5 Environmental hazards</b>	Not classified as environmentally hazardous
<b>14.6 Special precautions for user</b>	No dangerous good in sense of transport regulations.
<b>14.7 Transport in bulk according to Annex II of</b>	Not applicable



**MARPOL73/78 and the  
 IBC Code**


---

**Section 15: Regulatory information**


---

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture** Please refer to any other regulations of each country.

---

**Section 16: Other information**


---

Indication of changes	Revisions: 01. April. 2022 Section 1.
Abbreviations and acronyms	GHS: Globally Harmonized System of Classification and Labelling of Chemicals ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short-term Exposure Limit DNEL: Derived No Effect Level PNEC: Predicted No Effect Concentration ATE: Acute Toxicity Estimate STOT: Specific target organ toxicity LD50: Median(50%) lethal dose IARC: International Agency for Research on Cancer EC50: Median Effect Concentration IC50: Half maximal (50%) inhibitory concentration LC50: Median(50%) lethal concentration NOEC: No Observed Effect Concentration OECD: Organization for Economic Cooperation and Development
Full text of hazard class and category codes	Hazardous to the aquatic environment, long-term hazard, Hazard category 3, H412: Harmful to aquatic life with long lasting effects.
Training advice	Read this Safety Data Sheet before handling the substance.

*Disclaimer:* This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of UBE Corporation. The data on this sheet related only the specific material designated herein. UBE Corporation assumes no legal responsibility for use or reliance upon these data.

