

1. Identification of the substance/mixture and of the company/undertaking

Product identifier

Trade name: Absolan®
This safety data sheet pertains to the following products:
Absolan® (ALL GRADE)

Relevant identified uses of the substance or mixture and uses advised against

General use: Polymer
Basic material for chemical industry processing

Details of the supplier of the safety data sheet

Company name: Styrolution ABS (India) Limited
Street/POB-No.: 6th Floor, ABS Towers
Old Padra Road
Postal Code, city: 390 007 Vadodara, IN
India
WWW: www.styrolution.com
E-mail: infopoint.asia@styrolution.com
Telephone: +91 265-2355861-3, 2355871-3
Dept. responsible for information:
Infopoint, Telephone: + 65 (0) 6933 - 8372
E-mail: infopoint.asia@styrolution.com

Emergency telephone number

Telephone: + 65 (0) 3158 1198

2. Hazards identification

Classification of the substance or mixture

GHS classification

This substance is classified as not hazardous.

Label elements

Hazard statements: not applicable

Precautionary statements: not applicable

Other hazards

Floors may become slippery.
The melted product can cause severe burns.
Swallowing may cause gastrointestinal irritation and pain of guts.

3. Composition / information on ingredients

Substances

Chemical characterisation: $(C_8H_8 \cdot (C_3H_3)_n)_m$
Styrene-acrylonitrile copolymer

CAS-Number: 9003-54-7

Additional information: Preparation does not contain dangerous substances above limits that need to be mentioned in this section according to applicable legislation.

4. First aid measures

General information: Immediately remove any contaminated clothing, shoes or stockings.

In case of inhalation: Provide fresh air. If the symptoms persist, seek medical attention.

Following skin contact: The melted product can cause severe burns.
Do not remove the product from the skin without medical assistance.
After contact with molten product, cool skin area rapidly with cold water. Consult physician.

After eye contact: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Consult an eye specialist in the event of irritation.

After swallowing: Seek medical attention.
Never give an unconscious person anything through the mouth.
Drink one or two glasses of water.
In the event of discomfort seek medical treatment.

Most important symptoms and effects, both acute and delayed

Dusts: Can cause skin, eye and respiratory tract irritation.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.
Decontamination, vital functions

5. Firefighting measures

Extinguishing media

Suitable extinguishing media:
water fog, foam, extinguishing powder, carbon dioxide (CO₂).

Extinguishing media which must not be used for safety reasons:
High power water jet

Special hazards arising from the substance or mixture

In case of fire may be liberated: smoke, styrene, Methyl methacrylate, Hydrogen cyanide, carbon monoxide and carbon dioxide (CO₂).

In case of dust formation (Fine dust): danger of dust explosion

Advice for firefighters

Special protective equipment for firefighters:
Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information: Cool endangered containers with water jetspray.
Do not allow fire water to penetrate into surface or ground water.
Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation.
Wear personal protection equipment. Do not breathe dust.

Environmental precautions

Do not allow to penetrate into soil, waterbodies or drains.

Methods and material for containment and cleaning up

Avoid generation of dust. Remove all sources of ignition.
Collect dry and place in appropriate containers for disposal. Subsequent cleaning. (Water)

Additional information: Special danger of slipping by leaking/spilling product.

7. Handling and storage

Precautions for safe handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed. Do not breathe dust.
In the case of the formation of dust: Withdraw by suction.
Molten material: Avoid contact with the substance.

Precautions against fire and explosion:

Take precautionary measures against static discharges. Keep away from open flames, hot surfaces and sources of ignition. Use grounding equipment. Use explosion-proof equipment and non-sparking tools/utensils.
In case of dust formation (Fine dust): danger of dust explosion

Storage

Requirements for storerooms and containers:

Store in a well-ventilated place. Keep container tightly closed.
Protect against heat /sun rays.
Protect from moisture contamination.

Further details: Special danger of slipping by leaking/spilling product.

8. Exposure controls/personal protection

Control parameters

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
9003-54-7	Absolan®	USA: ACGIH: TWA	10 mg/m ³
		USA: ACGIH: TWA	3 mg/m ³
100-42-5	Styrene	USA: ACGIH: STEL	170 mg/m ³ ; 40 ppm
		USA: ACGIH: TWA	85 mg/m ³ ; 20 ppm
107-13-1	Acrylonitrile	USA: ACGIH: TWA	4.3 mg/m ³ ; 2 ppm

Additional information: The product contains very low levels of residual monomers and process chemicals (styrene, ethylbenzene and acrylonitrile) that may be evolved during thermal processing, along with possible decomposition products. As the identity and levels of these impurities evolved will depend upon the processing conditions (temperature etc.) it is the responsibility of the user to determine the adequacy of any protection or safety measures.

Exposure controls

Provide good ventilation in the work area. Additional controls are not normally necessary when handling the polymer.

Thermal extrusion: Provide local exhaust ventilation to ensure that the workplace exposure limit is not exceeded.

Use of respiratory protection may be necessary during maintenance activities.

See also information in chapter 7, section storage.

Personal protection equipment

Occupational exposure controls

Respiratory protection: Respiratory protection must be worn whenever the WEL levels have been exceeded. Use filter type A-P2 according to EN 14387.

Hand protection: Protective gloves according to EN 374.
Glove material: Nitrile rubber - Layer thickness 0.11 mm.
Breakthrough time: >480 min.
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.
In case of melting: Impervious heat protective gloves according to EN 407.
Glove material: Leather
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Eye protection: Tightly sealed goggles according to EN 166.

Body protection: Wear suitable protective clothing. Boots or Wear protective shoes.

General protection and hygiene measures:

Molten material: Avoid contact with skin.

Do not breathe vapours. Keep away from sources of ignition.

Wash hands before breaks and after work.

In case of dust formation: Particular danger of slipping on spilled product on the ground. Safety shower and eye wash station should be easily accessible to the work area.

Environmental exposure controls

Do not allow to penetrate into soil, waterbodies or drains.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance:	Form: solid, pellets Colour: colourless
Odour:	weak characteristic
Odour threshold:	no data available
pH value:	no data available
Melting point/freezing point:	> 100 °C (DIN EN ISO 306)
Initial boiling point and boiling range:	no data available
Flash point/flash point range:	> 400 °C
Evaporation rate:	no data available
Flammability:	Not highly flammable.
Explosion limits:	no data available
Vapour pressure:	no data available
Vapour density:	no data available
Density:	at 20 °C: approx. 1.05 - 1.20 g/cm ³ (DIN 53479)
Water solubility:	insoluble



Partition coefficient: n-octanol/water: no data available
 Auto-ignition temperature: Not self-igniting
 Thermal decomposition: > 320 °C

Additional information

Viscosity -
 Explosive properties: In case of dust formation (Fine dust): danger of dust explosion
 Bulk density: at 20 °C: 600 kg/m³ (DIN 53466)

10. Stability and reactivity

Reactivity: no data available
 Chemical stability: Stable under recommended storage conditions.
 Possibility of hazardous reactions: Dust may form explosive mixtures with air.
 Conditions to avoid: Keep away from open flames, hot surfaces and sources of ignition. Avoid dust formation.
 Incompatible materials: Strong oxidizing agents
 Hazardous decomposition products: In case of fire may be liberated: smoke, styrene, Methyl methacrylate, Hydrogen cyanide, carbon monoxide and carbon dioxide (CO2).
 Thermal decomposition: > 320 °C

11. Toxicological information

Information on toxicological effects

Toxicological effects: Acute toxicity (oral): Lack of data.
 Acute toxicity (dermal): Lack of data.
 Acute toxicity (inhalative): Lack of data.
 Skin corrosion/irritation: Lack of data.
 Eye damage/irritation: Lack of data.
 Sensitisation to the respiratory tract: Lack of data.
 Skin sensitisation: Lack of data.
 Germ cell mutagenicity/Genotoxicity: Lack of data.
 Carcinogenicity: Lack of data.
 Reproductive toxicity: Lack of data.
 Effects on or via lactation: Lack of data.
 Specific target organ toxicity (single exposure): Lack of data.
 Dusts: Irritating to eyes, respiratory system and skin.
 Specific target organ toxicity (repeated exposure): Lack of data.
 Aspiration hazard: Lack of data.
 Other information: When handled appropriately, even after long years of experience with this product, no adverse health effects are known.

Symptoms

Dusts: Can cause skin, eye and respiratory tract irritation.
The melted product can cause severe burns.

In case of ingestion: Swallowing may cause gastrointestinal irritation and pain of guts.

12. Ecological information

Toxicity

Effects in sewage plants: In sewage treatment plants it may be separated mechanically.

Persistence and degradability

Further details: Biodegradation: Product is not readily biodegradable.

Mobility in soil

no data available

Additional ecological information

General information: Do not allow to penetrate into soil, waterbodies or drains.

13. Disposal considerations

Waste treatment methods

Product

Recommendation: With due observance of the regulations laid down by the local authorities, this must be brought to a suitable incineration plant/waste disposal site.

Contaminated packaging

Recommendation: Dispose of waste according to applicable legislation.
Non-contaminated packages may be recycled.

14. Transport information

Sea transport (IMDG)

Proper shipping name: Not restricted

Marine pollutant: No

Air transport (IATA)

Proper shipping name: Not restricted

Further information

No dangerous good in sense of these transport regulations.

15. Regulatory information

National regulations - EC member states

EC-number: -

16. Other information

Uses advised against For toys and childcare articles
Reason of change: General revision (Regulation (EU) No 2015/830)
Date of first version: 7/11/2012

Department issuing data sheet

Contact person: see section 1: Dept. responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.