

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Styrolution® PS GPPS
This safety data sheet pertains to the following products:
Styrolution PS 145D GR2
Styrolution PS 147F GR2
Styrolution PS 147F GR21
Styrolution PS 158K GR2
Styrolution PS 158K GR21
Styrolution PS 168N GR21

CAS-Number: 9003-53-6

EC-number: -

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: Polymer
Basic material for chemical industry processing

1.3 Details of the supplier of the safety data sheet

Company name: INEOS Styrolution APAC Pte Ltd.
Street/POB-No.: 111 Somerset Road
Postal Code, city: #08-01/02 TripleOne Somerset, SG
Singapore 238164
WWW: www.styrolution.com
E-mail: infopoint.asia@styrolution.com
Telephone: +65 6933 8350
Telefax: +65 6933 8355

Dept. responsible for information:
Infopoint, Telephone: + 65 (0) 6933 - 8372
E-mail: infopoint.asia@styrolution.com

1.4 Emergency telephone number

Telephone: + 65 (0) 3158 - 1074

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP)

This substance is classified as not hazardous.

2.2 Label elements

Labelling (CLP)

Hazard statements: not applicable

Precautionary statements: not applicable

2.3 Other hazards

Dust: Can cause skin, eye and respiratory tract irritation.
In case of dust formation (Fine dust): May form explosible dust-air mixture if dispersed
The melted product can cause severe burns.

Results of PBT and vPvB assessment:

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

SECTION 3: Composition / information on ingredients

3.1 Substances

Chemical characterisation: Polymer
(C₈ H₈) *n
styrene-homopolymer, GPPS, > 96 %

CAS-Number: 9003-53-6

EC-number: -

RTECS-Number: WL6475000

Additional information: Preparation does not contain dangerous substances above limits that need to be mentioned in this section according to applicable legislation.

SECTION 4: First aid measures

4.1 Description of first aid measures

In case of inhalation: Provide fresh air. Put victim at rest and keep warm.

Following skin contact: The melted product can cause severe burns.
Do not remove the product from the skin without medical assistance.
After contact with molten product, cool skin area rapidly with cold water. Consult physician.

After eye contact: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Consult an eye specialist in the event of irritation.

After swallowing: Do not induce vomiting. Rinse mouth with water.
Drink one or two glasses of water.
Never give an unconscious person anything through the mouth.

4.2 Most important symptoms and effects, both acute and delayed

Dust: Skin irritation, eye irritations and redness

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:

Water fog, foam.
Only in case of small fires: extinguishing powder, carbon dioxide, Sand, earth.

Extinguishing media which must not be used for safety reasons:

High power water jet

5.2 Special hazards arising from the substance or mixture

In case of fire may be liberated: Smoke, styrene-monomer, aldehydes and acids (organic), carbon monoxide and carbon dioxide (CO₂).

5.3 Advice for firefighters

Special protective equipment for firefighters:

Wear self-contained breathing apparatus to prevent exposure to poisonous gases that may develop.

Additional information: Cool endangered containers with water jetspray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Wear personal protection equipment. Do not breathe dust.

6.2 Environmental precautions

Do not allow to penetrate into soil, waterbodies or drains.

6.3 Methods and material for containment and cleaning up

Avoid generation of dust. Remove all sources of ignition.
Collect dry and place in appropriate containers for disposal. Subsequent cleaning.

Additional information: Particular danger of slipping on spilled product on the ground.

6.4 Reference to other sections

Refer additionally to section 8 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed. Do not breathe dust.

In the case of the formation of dust: Withdraw by suction.

Molten material: Avoid contact with the substance.

Precautions against fire and explosion:

Take precautionary measures against static discharges. Keep away from sources of ignition. Use grounding equipment. Use explosion-proof equipment and non-sparking tools/utensils. Avoid open flames.

In case of dust formation (Fine dust): May form explosible dust-air mixture if dispersed

Dust explosion risk: Class1

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:

Store in a well-ventilated place. Keep container tightly closed.

Protect against heat /sun rays.

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Additional information: The product contains very low levels of residual monomers and process chemicals (styrene and ethylbenzene) that may be evolved during thermal processing, along with possible decomposition products. As the identity and levels of these impurities evolved will depend upon the processing conditions (temperature etc.) it is the responsibility of the user to determine the adequacy of any protection or safety measures.

8.2 Exposure controls

Provide good ventilation in the work area. Additional controls are not normally necessary when handling the polymer.

Thermal extrusion: Provide local exhaust ventilation to ensure that the workplace exposure limit is not exceeded.

Use of respiratory protection may be necessary during maintenance activities.

Personal protection equipment

Occupational exposure controls

Respiratory protection: In case of dust formation:
Use filter type A-P2 according to EN 14387.

Hand protection: Protective gloves according to EN 374.
Glove material: Nitrile rubber - Layer thickness: 0.11 mm.
Breakthrough time: >480 min.
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.
In case of melting: Impervious heat protective gloves according to EN 407.
Glove material: Leather
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Eye protection: Tightly sealed goggles according to EN 166.

Body protection: Wear suitable protective clothing.

General protection and hygiene measures:

Do not breathe vapours. Keep away from sources of ignition.
Wash hands before breaks and after work.

In case of dust formation: Particular danger of slipping on spilled product on the ground.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance: Form: solid, granulate
Colour: colourless

Odour: weak
Odour threshold: not available

pH value: not applicable

Melting point/freezing point: 105 °C up to 135 °C

Initial boiling point and boiling range: No data available

Flash point/flash point range: > 280 °C

Evaporation rate: No data available

Flammability: No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)
and Regulation (EU) No 2015/830

Revision date: 22/1/2016
Version: 14
Language: en-SG
Date of print: 30/9/2016

Styrolution® PS GPPS

Material number PS0001

Page: 5 of 8

Explosion limits:	No data available
Vapour pressure:	not applicable
Vapour density:	No data available
Density:	at 20 °C: approx. 1050 kg/m ³ (ISO 1183)
Water solubility:	insoluble
Partition coefficient: n-octanol/water:	not relevant
Auto-ignition temperature:	> 427 °C
Decomposition temperature:	> 300 °C
Viscosity, dynamic:	not applicable
Explosive properties:	In case of dust formation (Fine dust): May form explosible dust-air mixture if dispersed
Oxidizing characteristics:	not oxidising

9.2 Other information

Ignition temperature:	> 400 °C
Bulk density:	approx. 600 kg/m ³
Drop point/drop range:	79 °C up to 127 °C
Additional information:	Molar mass: 10000 - 300000 g/mol

SECTION 10: Stability and reactivity

10.1 Reactivity

refer to 10.3

10.2 Chemical stability

Product is stable under normal storage conditions.

10.3 Possibility of hazardous reactions

In case of dust formation (Fine dust): May form explosible dust-air mixture if dispersed

10.4 Conditions to avoid

Avoid open flames.
Avoid dust formation.

10.5 Incompatible materials

Strong oxidizing agents, Gasoline, aldehydes, ketone

10.6 Hazardous decomposition products

In case of fire may be liberated: Smoke, styrene-monomer, aldehydes and acids (organic), carbon monoxide and carbon dioxide (CO₂).

Thermal decomposition: > 300 °C

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity: LD50 Rat, oral: > 2000 mg/kg

LD50 Rabbit, dermal: > 2000 mg/kg

Toxicological effects: Acute toxicity (oral): Based on available data, the classification criteria are not met. Mild acute toxicity

Acute toxicity (dermal): Based on available data, the classification criteria are not met. Mild acute toxicity

Acute toxicity (inhalative): Based on available data, the classification criteria are not met. Mild acute toxicity. May cause irritations.

Skin corrosion/irritation: Lack of data.

Dust: Can cause skin, eye and respiratory tract irritation.

Processing, thermal hazards: Vapours: Can cause skin, eye and respiratory tract irritation.

Eye damage/irritation: Lack of data.

Dust: Can cause skin, eye and respiratory tract irritation.

Processing, thermal hazards: Vapours: Can cause skin, eye and respiratory tract irritation.

Sensitisation to the respiratory tract: Lack of data. The chemical structure of the polymer does not suggest a specific alert for such an effect.

Skin sensitisation: Based on available data, the classification criteria are not met. Not sensitising

Germ cell mutagenicity/Genotoxicity: Lack of data. The chemical structure of the polymer does not suggest a specific alert for such an effect.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Lack of data. The chemical structure of the polymer does not suggest a specific alert for such an effect.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): Lack of data.

Dust: Can cause skin, eye and respiratory tract irritation.

Processing, thermal hazards: Vapours: Can cause skin, eye and respiratory tract irritation.

Specific target organ toxicity (repeated exposure): Lack of data. Chronic toxic effects are not expected. The product has not been tested. The statement is derived from products of similar structure or composition.

Aspiration hazard: Lack of data.

Symptoms

Dust: Skin irritation, eye irritations and redness

The melted product can cause severe burns.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: no evidence of aquatic toxicity



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)
and Regulation (EU) No 2015/830

Styrolution® PS GPPS

Material number PS0001

Revision date: 22/1/2016

Version: 14

Language: en-SG

Date of print: 30/9/2016

Page: 7 of 8

12.2. Persistence and degradability

Further details: Biodegradation: Product is not readily biodegradable.
Degradation at UV-radiation/sunlight
Environmental half-life period: >=100 days (estimated)

12.3 Bioaccumulative potential

To avoid bioaccumulation plastics should not be disposed in the sea or in other water environments.

Partition coefficient: n-octanol/water:
not relevant

12.4 Mobility in soil

Product is not soluble in water.
Substance is heavier than water and sinks.
mobility in soil: low

12.5 Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

12.6 Other adverse effects

General information: Do not allow to enter into ground-water, surface water or drains.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste key number: 07 02 99 = Waste plastic
MFSU = manufacture, formulation, supply and use

Recommendation: With due observance of the regulations laid down by the local authorities, this must be brought to a suitable incineration plant/waste disposal site.

Contaminated packaging

Recommendation: Dispose of waste according to applicable legislation. Non-contaminated packages may be recycled.

SECTION 14: Transport information

14.1 UN number

ADR/RID, IMDG, IATA-DGR:
not applicable

14.2 UN proper shipping name

ADR/RID, IMDG, IATA-DGR:
Not restricted

14.3 Transport hazard class(es)

ADR/RID, IMDG, IATA-DGR:
not applicable

14.4 Packing group

ADR/RID, IMDG, IATA-DGR:

not applicable

14.5 Environmental hazards

Marine pollutant:

no

14.6 Special precautions for user

No dangerous good in sense of these transport regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations - Korea

Industrial Safety and Health Act

not applicable

Chemicals Control Act

not applicable

National regulations - Japan

ENCS: listed; MITI 6-120

15.2 Chemical Safety Assessment

For this substance a chemical safety assessment is not required.

SECTION 16: Other information

Further information

Reason of change: General revision

Date of first version: 8/8/2012

Department issuing data sheet

Contact person: see section 1: Dept. responsible for information

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.

